ARCTIC Freezer 36-S

Lab ID ACCLR00117

Type Air

Testing Dates: Apr 15, 2026 to Apr 18, 2026

Scheme: THETA

AMD AM5



No THETA level Intel LGA1851



Aristeidis Bitziopoulos, Certification Body General Manager

THETA Cooler Performance

THETA is a Cybenetics performance rating. It is not part of our ISO/IEC 17065 certification schemes and is outside our accreditation.

Overall Performance (OP) = W × F / T, where W is the average CPU power at the EPS connectors (W), F the average CPU frequency (MHz) and T the average CPU temperature (°C). A cooler is rated on its measured OP at 30 dB(A) normalized noise output; a cooler that cannot reach 30 dB(A) is rated on its own measured 25 dB(A) point. Air and AIO coolers have separate ladders on each test platform.

Evaluated before Revision 2.0 of the Cooling Solutions Test Protocol: the THETA level was assigned from the published results measured under Revision 1.8 (20 minutes per noise level, 10-minute cool-down). The cooler was not measured again, and the earlier procedure is not identical to the procedure of Revision 2.0.

Platform	THETA level	Test CPU	Mount	Rated at	Overall Performance (OP)
AMD AM5	**THETA Silver · Air · AMD AM5**	AMD Ryzen 9 7900X (AM5)	Default	30 dB(A)	9,814
Intel LGA1851	**No THETA level**	Intel Core Ultra 9 285K (LGA1851)	Default	-	-

General Information

Test Equipment

Noise Test Environment	Hemi Anechoic Chamber with 6dB(A) noise floor
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Climate Chamber	Giant Force GTH-800-20-CP-AR
Testing Methodology	Cybenetics Cooling Solutions Test Protocol

DUT Information

Brand	ARCTIC
Model	Freezer 36-S
Lab ID	ACCLR00117
Testing Dates	Apr 15, 2026 to Apr 18, 2026
Engineer	Aris Bitziopoulos

Climate Chamber

Noise Test Environment	Hemi Anechoic Chamber with 6dB(A) noise floor
Manufacturer	Giant Force
Model Number	GTH-800-20-CP-AR
Temperature Range	-20℃ ~ +100℃
Humidity Range	20% ~ 98% RH
Temperature/Humidity Constancy	±0.2℃; ±2.5%RH
Temperature/Humidity Uniformity at center	±0.5℃; ±4%RH
Internal Dimensions (WHD)	100 x 100 x 80 cm

External Dimensions (WHD)	145 x 190 x 135 cm
Net Weight (approximately)	450 Kg
Heat-up Time (No load, no linear)	(from 20°C to +100°C) 30min
Pull-down Time (No load, no linear)	(from 20°C to -20°C) 50min
Cooling System	Airtight compressor + evaporator fins + air-cooling condenser
Power Source	3Φ AC 380V ±5%, 50Hz±1% 10KW
Based on Standards	ISO 5801-2007, AMCA 210-0, ASHRAE 51-2007, IEC 61591-2005, GB/T 1236-200

AMD Test System

Mainboard	Asus TUF GAMING X670E-PLUS
CPU	AMD Ryzen 9 7900x
GPU	Embedded
NVMe	XPG GAMMIX S50 Lite 1TB
RAM	XPG Lancer DDR5 (2 x 16GB) 6000MHz
Power Supply	Seasonic Vertex 1200W (Cybenetics Platinum)
CPU Cooler	Device Under Test
Case	Cooler Master Test Bench

Technical Specifications

Manufacturer (OEM)	ARCTIC
Model	Freezer 36-S
Number of Fans	1
Fan #1	ARCTIC P12 Pro
Type	Air
Heatpipes	4
Heatpipe Diameter	6mm
Length	126mm
Width	88mm
Height	156mm
Block Material	Copper
Weight	685g

AMD Processors Support	AM4,AM5
Intel Processors Support	LGA1851,1700
Warranty	6 years


Noise Output and Fan Speed

Table


Fan Setting	Noise (dB(A))	Fan 1 (RPM)
40%	16.5	1435
50%	21.6	1701
60%	25.9	1979
70%	29.1	2234
80%	32.4	2564
90%	35.4	2850
100%	39.3	3100

Graphs

Noise



Fan Speed



Fan Speed at Fixed Noise Levels

Noise Level	Fan 1 (RPM)
15 dB(A)	1350
20 dB(A)	1620
25 dB(A)	1890
30 dB(A)	2260
35 dB(A)	2730


AMD System Test Results

Table


Condition	CPU Temperature (°C)	CPU Frequency (MHz)	CPU Power (W)	Overall Performance
20 dB(A)	95.1	5096	175.8	9414
25 dB(A)	95.2	5105	177.2	9504
30 dB(A)	95.2	5127	182.2	9814
35 dB(A)	95.2	5143	184.2	9947
Full fan speed	95.2	5146	184.9	9989

Graphs


CPU Temperature




CPU Frequency



CPU Power



Overall Performance



ARCTIC Freezer 36-S



本测试报告中包含的所有数据和图表均可在以下条件下由任何人使用：使用过程需提及测试结果由 Cybenetics提供。
在任何情况下都应提供原始测试结果文档的网站链接

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus www.cybenetics.com - info@cybenetics.com

Cybenetics - ARCTIC Freezer 36-S - Test Report - Page 8 / 8