# ASUS ROG-THOR-1000P2-GAMING

Serial Number

Lab ID AS10001844

Certification ID 251844

Test Result Report ID: 21PS1844A

Certificate Issue Date: May 12, 2021

115V 230V

Scheme: ETA-EMI PSU

CYBENETICS PLATINUM

115V 230V

CYBENETICS A++

Scheme: LAMBDA PSU

Aristeidis Bitziopoulos, Certification Body General Manager

# General Information

## Test Equipment

| | |
|---|---|
| Electronic Loads | Chroma 63601-5 x2<br>Chroma 63600-2<br>Chroma 63640-80-80 x10<br>Chroma 63610-80-20 |
| AC Sources | Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500 |
| Power Analyzers | Rohde & Schwarz HMC8015 & NPA701 |
| Oscilloscopes | Picoscope 4444, Siglent SDS2104X PLUS |
| Sound Analyzer | Bruel & Kjaer 2270 G4 |
| Microphone | Bruel & Kjaer Type 4955-A |
| Temperature Logger | Picoscope TC-08 |
| Tachometer | UNI-T UT372 |
| Multimeters | Keysight 34465A |
| EMI Analyzer | TekBox TBMR-110M-EU |
| Isolation Transformer | 4kVA |
| UPS | FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA |
| Testing Methodology | Cybenetics PSU Test Protocol |

## DUT Information(Non-accredited measurements)

| | |
|---|---|
| Product Identification Details | |
| Brand | ASUS |
| Model | ROG-THOR-1000P2-GAMING |
| OEM/ODM | Seasonic |
| Serial Number | |
| Product Specifications | |
| Manufacturer-Provided Information | |
| Rated Voltage (Vrms) | 100-240 |
| Rated Current (Arms) | 15-7.5 |
| Rated Frequency (Hz) | 50-60 |

| | |
|---|---|
| Rated Power (W) | 1000 |
| Operating Temperature (Continuous Full Load) (°C) | |
| Type | ATX12V |
| Cable Design | Fully Modular |
| Warranty | - |
| Cybenetics Measurements | |
| Dimensions (W x H x D) | |
| Weight | |
| Cooling | 135mm Double Ball Bearing Fan<br>(CF1325H12D) |
| Semi-Passive Operation | ✓ (selectable) |
| Cybenetics Testing Information | |
| Lab ID | AS10001844 |
| Date of receipt | May 8, 2021 |
| Testing Date | May 11, 2021 |
| Report Issued Date | May 12, 2021 |
| Engineer Name | - |
| Authorized By the Laboratory Technical Manager | Aristeidis Bitziopoulos |
| Signature | |

## Cables and Connectors(Non-accredited measurements)

| Modular Cables | | | | |
|---|---|---|---|---|
| Description | Cable Count | Connector Count (Total) | Gauge | In Cable Capacitors |
| ATX connector 20+4 pin (610mm) | 1 | 1 | 18-20AWG | No |
| 4+4 pin EPS12V (650mm) | 2 | 2 | 18AWG | No |
| 6+2 pin PCIe (680mm) | 4 | 4 | 18AWG | No |
| 6+2 pin PCIe (680mm+70mm) | 2 | 4 | 18AWG | Yes |
| SATA (350mm+150mm+150mm+150mm) | 1 | 4 | 18AWG | No |
| SATA (400mm+115mm+115mm+115mm) | 2 | 8 | 18AWG | No |
| 4 pin Molex to SATA 3.3 Adapter (160mm+160mm) | 1 | 2 | 18AWG | No |
| 4 pin Molex (350mm+120mm) | 1 | 2 | 18AWG | No |

| | | | | |
|---|---|---|---|---|
| 4 pin Molex (450mm+120mm+120mm) | 1 | 3 | 18AWG | No |
| FDD Adapter (+110mm) | 1 | 1 | 22AWG | No |
| RGB Cable (800mm) | 1 | 1 | 22AWG | No |
| RGB Sync Cable (800mm) | 1 | 1 | 24AWG | No |

## Power Specifications

| Rail | | 3.3V | 5V | 12V | 5VSB | -12V |
|---|---|---|---|---|---|---|
| Max. Power | Amps | 25 | 25 | 83 | 3 | 0.3 |
| | Watts | 125 | | 996 | 15 | 3.6 |
| Total Max. Power (W) | | 1000 | | | | |

## Parts Description

| | |
|---|---|
| General Data | - |
| Manufacturer (OEM) | Seasonic |
| PCB Type | Double Sided |
| Primary Side | - |
| Transient Filter | 6x Y caps, 3x X caps, 2x CM chokes, 1x MOV, 1x Champion CM02X (Discharge IC) |
| Inrush Protection | NTC Thermistor MF72 5D-20L (5 Ohm) & Relay |
| Bridge Rectifier(s) | 2x Vishay LVB2560 (600V, 25A @ 105°C) |
| APFC MOSFETs | 2x Infineon IPP60R080P7 (600V, 23A @ 100°C, Rds(on): 0.08Ohm) |
| APFC Boost Diode | 1x CREE C3D08060 (600V, 8A @ 152°C) |
| Bulk Cap(s) | 2x Nippon Chemi-Con (420V, 680uF & 390uF each or 1,070uF combined, 2,000h @ 105°C, KHE) |
| Main Switchers | 4x Infineon IPP60R180P7 (600V, 11A @ 100°C, Rds(on): 0.18Ohm) |
| IC Drivers | 2x Silicon Labs Si8230BD |
| APFC Controller | On Semiconductor NCP1654 |
| Resonant Controller | Champion CM6901T2X |
| Current Sensor IC | Allegro ACS725T |
| Topology | Primary side: APFC, Full-Bridge & LLC converter<br>Secondary side: Synchronous Rectification & DC-DC converters |
| Secondary Side | - |
| +12V MOSFETs | 8x Nexperia PSMN1R4-40YLD (40V, 214A @ 100°C, Rds(on): 2.65mOhm) |
| 5V & 3.3V | DC-DC Converters |

| | |
|---|---|
| Filtering Capacitors | Electrolytic: 2x Nippon Chemi-Con (105°C, W), 8x Nippon Chemi-Con (4-10,000h @ 105°C, KY),2x Rubycon (3-6,000h @ 105°C, ZLQ), 1x Rubycon (3-6,000h @ 105°C, YXG), 1x Rubycon (6-10,000h @ 105°C, ZLJ)<br>Polymer: 30x FPCAP, 12x NIC |
| Supervisor IC | Weltrend WT7527V (OCP, OVP, UVP, SCP, PG) |
| Fan Model | Champion CF1325H12D (135mm, 12V, 0.60A, Double Ball Bearing Fan) |
| Fan Controller | Atmel SAM4N8 |
| Flash Memory | Microchip SST26VF016B |
| 5VSB Circuit | - |
| Rectifier | 1x MCC MBR1045ULPS SBR (45V, 10A) & 1x Infineon IPA65R1K5CE FET (650V, 3.3A @ 100°C, Rds(on): 1.5Ohm) |
| Standby PWM Controller | Leadtrend LD7750R |

# Test Results

## Temperature & Compliance Info

| | |
|---|---|
| Temperature Range (°C /°F) | 28-32 / 82.4-89.6 |
| ErP Lot 3/6 Ready | ✓ |
| (EU) No 617/2013 Compliance | ✓ |

## Performance Summary 115V

| | |
|---|---|
| Accredited | |
| Average Efficiency (>1450 load combinations) | 89.879% |
| Average Noise Output (>1450 Load Combinations) | 11.39dBA |
| Average PF (>1450 Load Combinations) | 0.990 |
| Efficiency With 10W (≤500W) or 2% (>500W) Load | 63.468% |
| Standby Power Consumption | 0.0560W |
| Non-Accredited | |
| 12V Ripple (Full Load) | 20.60mV |
| 5V Ripple (Full Load) | 11.50mV |
| 3.3V Ripple (Full Load) | 17.35mV |
| 5VSB Ripple (Full Load) | 28.77mV |
| 12V Load Regulation | 0.23% |

| | |
|---|---|
| 5V Load Regulation | 0.45% |
| 3.3V Load Regulation | 0.62% |
| 5VSB Load Regulation | 3.61% |
| Inrush Current | 68.210A |

## Hold-Up Time & PWR_OK Signal

| | |
|---|---|
| Hold-Up Time (ms) | 26.1 |
| AC Loss to PWR_OK Hold Up Time (ms) | 22 |
| PWR_OK Inactive to DC Loss Delay (ms) | 4.1 |

# Vampire Power

## Graphs 115V



## Efficiency Graph

### 115V




### INFO

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations

# Noise Graph

## 115V




## INFO

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

## Indicative Performance

### Efficiency under high ambient temperature




**INFO**

The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

## 5VSB Efficiency




### INFO

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

### 5VSB Efficiency (ERP LOT 3/6 & CEC) 115V

| Test # | 5VSB | DC/AC (Watts) | Efficiency | PF/AC Volts |
|---|---|---|---|---|
| 1 | 0.045A | 0.232 | 65.909% | 0.036 |
| | 5.159V | 0.352 | | 115.15V |

| | | | | |
|---|---|---|---|---|
| 2 | 0.090A | 0.464 | 72.613% | 0.064 |
| | 5.157V | 0.639 | | 115.15V |
| 3 | 0.550A | 2.829 | 80.805% | 0.266 |
| | 5.144V | 3.501 | | 115.17V |
| 4 | 1.000A | 5.129 | 80.886% | 0.361 |
| | 5.130V | 6.341 | | 115.16V |
| 5 | 1.500A | 7.671 | 80.815% | 0.415 |
| | 5.114V | 9.492 | | 115.16V |
| 6 | 2.999A | 15.189 | 79.015% | 0.493 |
| | 5.065V | 19.223 | | 115.15V |

## Supplementary Tests (For Reference)

### Typical Load Tests 115V

| Test # | 12V | 5V | 3.3V | 5VSB | DC/AC (Watts) | Efficiency | Fan Speed (RPM) | PSU Noise (dB[A]) | Temps (In/Out) | PF/AC Volts |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 6.444A | 1.956A | 1.963A | 0.975A | 99.978 | 86.345% | 0 | <6.0 | 45.69°C | 0.973 |
| | 12.165V | 5.106V | 3.363V | 5.126V | 115.789 | | | | 40.63°C | 115.15V |
| 2 | 13.904A | 2.939A | 2.945A | 1.174A | 199.997 | 90.337% | 0 | <6.0 | 46.76°C | 0.983 |
| | 12.162V | 5.104V | 3.360V | 5.111V | 221.389 | | | | 41.07°C | 115.15V |
| 3 | 21.704A | 3.432A | 3.440A | 1.373A | 299.957 | 91.561% | 0 | <6.0 | 47.82°C | 0.981 |
| | 12.159V | 5.102V | 3.358V | 5.096V | 327.603 | | | | 41.60°C | 115.15V |
| 4 | 29.469A | 3.923A | 3.934A | 1.574A | 399.433 | 91.883% | 0 | <6.0 | 48.64°C | 0.986 |
| | 12.156V | 5.100V | 3.356V | 5.081V | 434.720 | | | | 41.77°C | 115.14V |
| 5 | 36.951A | 4.905A | 4.921A | 1.777A | 499.578 | 91.810% | 0 | <6.0 | 49.61°C | 0.990 |
| | 12.153V | 5.098V | 3.354V | 5.066V | 544.141 | | | | 42.29°C | 115.14V |
| 6 | 44.436A | 5.889A | 5.910A | 1.981A | 599.719 | 91.461% | 318 | <6.0 | 42.79°C | 0.992 |
| | 12.150V | 5.096V | 3.352V | 5.049V | 655.708 | | | | 50.73°C | 115.14V |
| 7 | 51.891A | 6.874A | 6.899A | 2.185A | 699.442 | 91.025% | 318 | <6.0 | 43.10°C | 0.993 |
| | 12.147V | 5.094V | 3.350V | 5.032V | 768.409 | | | | 51.59°C | 115.14V |
| 8 | 59.417A | 7.858A | 7.886A | 2.392A | 799.965 | 90.549% | 476 | <6.0 | 43.45°C | 0.994 |
| | 12.144V | 5.092V | 3.347V | 5.016V | 883.457 | | | | 52.25°C | 115.13V |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 9 | 67.273A | 8.349A | 8.365A | 2.396A | 899.235 | 89.969% | 873 | 23.4 | 45.40°C | 0.995 |
| | 12.141V | 5.090V | 3.345V | 5.007V | 999.490 | | | | 54.76°C | 115.13V |
| 10 | 74.968A | 8.845A | 8.881A | 3.016A | 999.654 | 89.267% | 1196 | 33.6 | 45.63°C | 0.995 |
| | 12.138V | 5.087V | 3.344V | 4.973V | 1119.850 | | | | 55.59°C | 115.12V |
| 11 | 83.229A | 8.848A | 8.885A | 3.022A | 1099.668 | 88.527% | 2010 | 47.9 | 46.55°C | 0.995 |
| | 12.135V | 5.085V | 3.342V | 4.963V | 1242.178 | | | | 57.27°C | 115.12V |
| CL1 | 0.117A | 15.000A | 14.997A | 0.000A | 128.252 | 83.328% | 0 | <6.0 | 48.66°C | 0.975 |
| | 12.160V | 5.102V | 3.355V | 5.144V | 153.912 | | | | 42.42°C | 115.18V |
| CL2 | 82.990A | 1.000A | 0.999A | 1.000A | 1020.821 | 89.577% | 1193 | 33.6 | 45.85°C | 0.995 |
| | 12.138V | 5.095V | 3.347V | 5.050V | 1139.602 | | | | 55.84°C | 115.12V |

The results above are not used in the certification process

## Light Load Tests 115V

| Test # | 12V | 5V | 3.3V | 5VSB | DC/AC (Watts) | Efficiency | Fan Speed (RPM) | PSU Noise (dB[A]) | PF/AC Volts |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1.219A | 0.489A | 0.492A | 0.194A | 19.979 | 64.109% | 0 | <6.0 | 0.838 |
| | 12.158V | 5.114V | 3.369V | 5.159V | 31.164 | | | | 115.16V |
| 2 | 2.439A | 0.978A | 0.980A | 0.388A | 39.967 | 76.403% | 0 | <6.0 | 0.914 |
| | 12.166V | 5.110V | 3.365V | 5.151V | 52.311 | | | | 115.16V |
| 3 | 3.662A | 1.468A | 1.472A | 0.583A | 60.000 | 81.614% | 0 | <6.0 | 0.938 |
| | 12.166V | 5.108V | 3.364V | 5.142V | 73.517 | | | | 115.16V |
| 4 | 4.880A | 1.957A | 1.962A | 0.779A | 79.951 | 84.281% | 0 | <6.0 | 0.955 |
| | 12.164V | 5.106V | 3.363V | 5.134V | 94.862 | | | | 115.15V |

The results above are not used in the certification process

## Ripple Measurements 115V

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 10% Load | 12.10mV | 8.30mV | 12.40mV | 17.70mV | Pass |
| 20% Load | 15.20mV | 8.10mV | 12.60mV | 16.90mV | Pass |
| 30% Load | 12.70mV | 8.80mV | 13.00mV | 18.00mV | Pass |
| 40% Load | 9.50mV | 9.10mV | 13.20mV | 18.50mV | Pass |

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 50% Load | 10.40mV | 8.30mV | 13.30mV | 19.50mV | Pass |
| 60% Load | 12.00mV | 8.90mV | 13.50mV | 22.10mV | Pass |
| 70% Load | 13.10mV | 8.80mV | 13.60mV | 21.50mV | Pass |
| 80% Load | 14.00mV | 8.80mV | 14.90mV | 23.30mV | Pass |
| 90% Load | 14.30mV | 10.50mV | 16.50mV | 24.70mV | Pass |
| 100% Load | 20.60mV | 11.50mV | 17.40mV | 28.80mV | Pass |
| 110% Load | 23.30mV | 12.50mV | 17.90mV | 31.20mV | Pass |
| Crossload1 | 16.40mV | 8.10mV | 13.00mV | 16.30mV | Pass |
| Crossload2 | 22.40mV | 9.80mV | 16.90mV | 26.10mV | Pass |

The results above are not used in the certification process

## ASUS ROG-THOR-1000P2-GAMING

Top side

Power specifications label

All data and graphs included in this test report can be used by any individual on the following conditions:
› It should be mentioned that the test results are provided by Cybenetics
› The link to the original test results document should be provided in any case

Cybenetics runs voluntary certification programs for power supplies - ETA for efficiency, LAMBDA for noise and SAFE for safety and correct operation - and for cooling products, with DELTA for chassis soundproofing and PHI for fan airflow and static pressure. THETA rates cooler performance on AMD AM5 and Intel LGA1851 outside ISO 17065 and accreditation scope

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus

www.cybenetics.com - info@cybenetics.com