



Thermaltake Toughpower GF1 1000W


Serial Number PSTPD1000FNFAGU1XU000245

Lab ID TT10001885

Certification ID 251885

Test Result Report ID: 21PS1885A

Certificate Issue Date: Aug 26, 2021



A handwritten signature in blue ink, appearing to read 'A. Bitziopoulos', is written over a faint circular stamp.

Aristeidis Bitziopoulos, Certification Body General Manager

General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	Thermaltake
Model	Toughpower GF1 1000W
OEM/ODM	Channel Well Technology
Serial Number	PSTPD1000FNFAGU1XU000245
Product Specifications	
Manufacturer-Provided Information	
Rated Voltage (Vrms)	100-240
Rated Current (Arms)	15
Rated Frequency (Hz)	50-60

Rated Power (W)	1000
Operating Temperature (Continuous Full Load) (°C)	
Type	ATX12V
Cable Design	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
Cooling	140mm Hydraulic Bearing Fan [TT-1425 (A1425L12S)]
Semi-Passive Operation	✓ (selectable)
Cybenetics Testing Information	
Lab ID	TT10001885
Date of receipt	Jul 19, 2021
Testing Date	Aug 24, 2021
Report Issued Date	Aug 26, 2021
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

Cables and Connectors(Non-accredited measurements)

Modular Cables				
Description	Cable Count	Connector Count (Total)	Gauge	In Cable Capacitors
ATX connector 20+4 pin (600mm)	1	1	16AWG	No
8 pin EPS12V (700mm)	1	1	16AWG	No
4+4 pin EPS12V (700mm)	1	1	16AWG	No
6+2 pin PCIe (500mm+150mm)	3	6	16-18AWG	No
SATA (500mm+150mm+150mm+150mm)	3	12	18AWG	No
4-pin Molex (500mm+150mm+150mm+150mm)	1	4	18AWG	No
FDD Adapter (150mm)	1	1	20AWG	No
AC Power Cord (1420mm) - C13 coupler	1	1	14AWG	-

Power Specifications

Rail		3.3V	5V	12V	5VSB	-12V
Max. Power	Amps	24	24	83.3	3	0.5
	Watts	120		1000	15	6
Total Max. Power (W)		1000				

Parts Description

General Data	-
Manufacturer (OEM)	CWT
PCB Type	Double Sided
Primary Side	-
Transient Filter	4x Y caps, 2x X caps, 2x CM chokes, 1x MOV, 1x CAP200DG (Discharge IC)
Inrush Protection	NTC Thermistor SCK-055 (5 Ohm) & Relay
Bridge Rectifier(s)	2x GBU1510 (1000V, 15A @ 100°C)
APFC MOSFETs	3x Infineon IPA50R140CP (500V, 15A @ 100°C, Rds(on): 0.14 Ohm)
APFC Boost Diode	1x Infineon IDH10G65C6 (650V, 10A @ 140°C)
Bulk Cap(s)	2x Nichicon (400V, 680uF & 470uF each or 1.150uF compined, 2,000h @ 105°C, GG)
Main Switchers	2x Infineon IPW60R125P6 (600V, 19A @ 100°C, Rds(on): 0.125Ohm)
APFC Controller	Champion CM6500UNX & Champion CM03X
Resonant Controller	Champion CM6901X
Topology	Primary side: APFC, Half-Bridge & LLC converter Secondary side: Synchronous Rectification & DC-DC converters
Secondary Side	-
+12V MOSFETs	8x International Rectifier IRFH7004PbF (40V, 164A @ 100°C, Rds(on): 1.4mOhm)
5V & 3.3V	DC-DC Converters: 4x UBIQ QM3054M6 (30V, 61A @ 100°C, Rds(on): 4.8mOhm) & 2x UBIQ QN3107M6N (30V, 70A @ 100°C, Rds(on): 2.6mOhm) PWM Controllers: UPI Semi uP3861P
Filtering Capacitors	Electrolytic: 10x Nippon Chemi-Con (4-10,000h @ 105°C, KY), 6x Nichicon (4-10,000h @ 105°C, HE), 1x Rubycon (6-10,000h @ 105°C, ZLH), 1x Rubycon (3-6,000h @ 105°C, YXG) Polymer: 10x FPCAP, 11x NIC, 5x Nippon Chemi-Con
Supervisor IC	IN1S429I (OCP, OVP, UVP, SCP, PG)
Fan Model	Thermaltake TT-1425 (Hong Sheng A1425L12S) (140mm, 12V, 0.30A, Hydraulic Bearing Fan)
5VSB Circuit	-

Rectifier	1x Galaxy Microelectronics D10PS45L SBR (45V, 10A) & IPS ISD04N65A FET
Standby PWM Controller	On-Bright OB5282

Test Results

Temperature & Compliance Info

Temperature Range (°C /°F)	28-32 / 82.4-89.6
ErP Lot 3/6 Ready	✓
(EU) No 617/2013 Compliance	✓
ALPM (Alternative Low Power Mode) compatible	✓

Performance Summary

115V

Accredited	
Average Efficiency (>1450 load combinations)	88.220%
Average Noise Output (>1450 Load Combinations)	35.61dBA
Average PF (>1450 Load Combinations)	0.976
Efficiency With 10W ($\leq$ 500W) or 2% (>500W) Load	63.714%
Standby Power Consumption	0.0438W
Non-Accredited	
12V Ripple (Full Load)	15.76mV
5V Ripple (Full Load)	16.16mV
3.3V Ripple (Full Load)	19.13mV
5VSB Ripple (Full Load)	7.30mV
12V Load Regulation	0.63%
5V Load Regulation	0.68%
3.3V Load Regulation	1.09%
5VSB Load Regulation	4.16%
Inrush Current	33.900A

230V

Accredited		
Average Efficiency (>1450 load combinations)	90.422%	
Average Noise Output (>1450 Load Combinations)	35.58dBA	
Average PF (>1450 Load Combinations)	0.931	
Efficiency With 10W (≤500W) or 2% (>500W) Load	-	
Standby Power Consumption	0.0624W	
Non-Accredited		
12V Ripple (Full Load)	15.04mV	
5V Ripple (Full Load)	16.87mV	
3.3V Ripple (Full Load)	19.56mV	
5VSB Ripple (Full Load)	7.39mV	
12V Load Regulation	0.61%	
5V Load Regulation	0.68%	
3.3V Load Regulation	1.06%	
5VSB Load Regulation	4.14%	
Inrush Current	66.480A	
Hold-Up Time & PWR_OK Signal	19.00ms	
AC Loss to PWR_OK Hold Up Time	17.40ms	
PWR_OK Inactive to DC Loss Delay	1.60ms	
PSU Timings: T1 (20% / 100%)	36.0ms	36.0ms
PSU Timings: T3 (20% / 100%)	134.0ms	134.0ms
OPP (29.73°C / 40.76°C)	131.54%	120.14%

Hold-Up Time & PWR_OK Signal


Hold-Up Time (ms)	19
AC Loss to PWR_OK Hold Up Time (ms)	17.4
PWR_OK Inactive to DC Loss Delay (ms)	1.6

Vampire Power

Graphs


115V

Power - PSTPD1000FNFAGU1XU000245 - 31/07/2021 - 12:59




230V

Power - PSTPD1000FNFAGU1XU000245 - 31/07/2021 - 12:59




Efficiency Graph

115V



INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations




INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


Noise Graph

115V



INFO

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails



INFO


The PSU's noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Indicative Performance

Efficiency under high ambient temperature

Efficiency: Thermaltake Toughpower GF1 1000W

Ambient: 37°C - 47°C (98.6°F - 116.6°F)




INFO

The PSU's efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5VSB Efficiency

5VSB Efficiency: Thermaltake Toughpower GF1 1000W

Ambient: 34°C - 36°C (93.2°F - 96.8°F)



INFO

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

5VSB Efficiency (ERP LOT 3/6 & CEC)

115V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.23W	69.871%	0.033
	5.117V	0.329W		115.13V
2	0.09A	0.461W	75.340%	0.061
	5.115V	0.612W		115.12V
3	0.55A	2.805W	79.553%	0.269
	5.099V	3.526W		115.13V
4	1A	5.084W	79.064%	0.364
	5.083V	6.43W		115.13V
5	1.5A	7.6W	78.650%	0.417
	5.066V	9.663W		115.13V
6	3.001A	15.039W	77.088%	0.479
	5.012V	19.509W		115.12V

230V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.23W	63.404%	0.011
	5.116V	0.363W		230.26V
2	0.09A	0.461W	70.486%	0.02
	5.115V	0.654W		230.26V
3	0.55A	2.805W	77.723%	0.103
	5.099V	3.609W		230.26V
4	1A	5.084W	78.656%	0.17
	5.083V	6.464W		230.26V
5	1.5A	7.599W	78.587%	0.229
	5.065V	9.67W		230.26V
6	3.001A	15.038W	77.446%	0.334
	5.012V	19.418W		230.26V

Supplementary Tests (For Reference)

Typical Load Tests

115V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
10%	6.476A	1.985A	1.972A	0.987A	100.032	84.851%	0	<6.0	46.19°C	0.963
	12.110V	5.038V	3.347V	5.069V	117.892				40.82°C	115.14V
20%	13.961A	2.98A	2.961A	1.188A	199.998	89.134%	0	<6.0	46.83°C	0.976
	12.112V	5.034V	3.344V	5.052V	224.379				40.97°C	115.14V
30%	21.792A	3.479A	3.457A	1.391A	300.071	90.708%	0	<6.0	47.73°C	0.976
	12.116V	5.031V	3.341V	5.034V	330.809				41.35°C	115.14V
40%	29.626A	3.978A	3.955A	1.595A	399.894	90.78%	0	<6.0	48.4°C	0.972
	12.107V	5.029V	3.338V	5.017V	440.509				41.65°C	115.14V
50%	37.162A	4.976A	4.949A	1.801A	499.627	90.238%	960	27.3	41.95°C	0.975
	12.085V	5.026V	3.335V	4.999V	553.68				49.2°C	115.13V
60%	44.792A	5.975A	5.947A	2A	600.119	89.698%	993	28.3	42.48°C	0.978
	12.063V	5.023V	3.33V	4.984V	669.041				50.26°C	115.13V
70%	52.300A	6.976A	6.945A	2.216A	699.853	88.86%	1266	35.6	42.87°C	0.98
	12.060V	5.019V	3.327V	4.965V	787.592				51.23°C	115.12V
80%	59.899A	7.979A	7.946A	2.324A	799.904	88.173%	1530	41.1	43.59°C	0.982
	12.053V	5.016V	3.323V	4.951V	907.2				52.32°C	115.12V
90%	67.824A	8.483A	8.436A	2.432A	899.71	87.305%	1751	45.0	44.54°C	0.984
	12.049V	5.012V	3.32V	4.936V	1030.542				53.83°C	115.12V
100%	75.572A	8.988A	8.957A	3.061A	999.721	86.393%	1745	44.6	45.97°C	0.985
	12.042V	5.009V	3.316V	4.902V	1157.18				55.8°C	115.11V
110%	83.271A	9.995A	10.055A	3.069A	1100.351	85.298%	1743	44.3	46.64°C	0.987
	12.033V	5.005V	3.312V	4.89V	1290.012				57.38°C	115.11V
CL1	0.116A	14.389A	14.31A	0A	121.346	82.461%	840	22.7	42.26°C	0.973
	12.083V	5.02V	3.333V	5.09V	147.156				49.4°C	115.15V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
CL2	0.116A	23.955A	0A	0A	121.452	80.603%	0	<6.0	51.45°C	0.973
	12.087V	5.011V	3.348V	5.096V	150.679				43.45°C	115.15V
CL3	0.116A	0A	23.801A	0A	80.6	74.691%	0	<6.0	53.87°C	0.962
	12.105V	5.035V	3.327V	5.094V	107.911				44.91°C	115.15V
CL4	83.012A	0A	0A	0A	1000.252	86.873%	1758	45.4	45.93°C	0.985
	12.049V	5.025V	3.329V	5.027V	1151.392				55.75°C	115.11V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
10%	6.474A	1.985A	1.972A	0.987A	100.026	85.89%	0	<6.0	45.29°C	0.822
	12.115V	5.038V	3.347V	5.069V	116.459				40.01°C	230.29V
20%	13.962A	2.98A	2.961A	1.188A	199.986	90.242%	0	<6.0	46.75°C	0.9
	12.109V	5.034V	3.344V	5.052V	221.61				40.95°C	230.29V
30%	21.798A	3.479A	3.457A	1.39A	300.052	92.232%	0	<6.0	47.86°C	0.929
	12.111V	5.031V	3.341V	5.035V	325.324				41.47°C	230.29V
40%	29.626A	3.978A	3.954A	1.595A	399.853	92.672%	0	<6.0	48.68°C	0.94
	12.105V	5.029V	3.338V	5.017V	431.471				41.87°C	230.28V
50%	37.188A	4.975A	4.949A	1.8A	499.599	92.447%	878	24.1	42.24°C	0.949
	12.076V	5.026V	3.334V	5.001V	540.415				49.62°C	230.28V
60%	44.751A	5.974A	5.945A	2A	600.066	92.192%	1126	32.0	42.88°C	0.953
	12.073V	5.023V	3.33V	4.983V	650.885				50.83°C	230.29V
70%	52.274A	6.975A	6.944A	2.216A	699.819	91.778%	1336	37.2	43.45°C	0.956
	12.065V	5.019V	3.327V	4.965V	762.513				51.84°C	230.29V
80%	59.883A	7.978A	7.945A	2.323A	799.84	91.356%	1547	41.2	43.88°C	0.959
	12.055V	5.016V	3.323V	4.952V	875.524				52.77°C	230.28V
90%	67.820A	8.482A	8.435A	2.431A	899.618	90.865%	1748	44.8	44.46°C	0.961
	12.048V	5.013V	3.32V	4.938V	990.056				53.79°C	230.29V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
100%	75.566A	8.987A	8.956A	3.06A	999.634	90.29%	1746	44.7	45.47°C	0.963
	12.042V	5.009V	3.316V	4.903V	1107.14				55.38°C	230.28V
110%	83.236A	9.993A	10.053A	3.066A	1100.212	89.779%	1747	44.7	46.54°C	0.965
	12.036V	5.005V	3.312V	4.893V	1225.474				57.33°C	230.28V
CL1	0.116A	14.386A	14.309A	0A	121.33	82.899%	840	22.7	42.43°C	0.854
	12.086V	5.021V	3.333V	5.091V	146.36				49.61°C	230.28V
CL2	0.116A	23.95A	0A	0A	121.438	81.305%	0	<6.0	51.65°C	0.856
	12.095V	5.012V	3.349V	5.096V	149.361				43.92°C	230.28V
CL3	0.116A	0A	23.798A	0A	80.591	75.471%	0	<6.0	53.21°C	0.803
	12.113V	5.034V	3.328V	5.094V	106.784				44.7°C	230.28V
CL4	82.980A	0A	0A	0A	1000.131	90.895%	1754	45.1	45.25°C	0.962
	12.053V	5.025V	3.329V	5.028V	1100.316				54.51°C	230.28V

The results above are not used in the certification process

Light Load Tests

115V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.226A	0.496A	0.492A	0.196A	20.012	59.778%	0	<6.0	40.23°C	0.847
	12.116V	5.043V	3.352V	5.106V	33.478				36.95°C	115.14V
40W	2.698A	0.694A	0.689A	0.294A	40.013	73.993%	0	<6.0	41.35°C	0.923
	12.116V	5.042V	3.351V	5.101V	54.077				37.65°C	115.14V
60W	4.172A	0.893A	0.887A	0.393A	60.014	80.979%	0	<6.0	42.42°C	0.938
	12.116V	5.042V	3.35V	5.095V	74.11				38.24°C	115.14V
80W	5.640A	1.091A	1.084A	0.491A	79.981	83.813%	0	<6.0	44.06°C	0.958
	12.117V	5.041V	3.35V	5.089V	95.428				39.34°C	115.14V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.226A	0.496A	0.492A	0.196A	20.011	59.026%	0	<6.0	39.89°C	0.53
	12.113V	5.043V	3.351V	5.106V	33.902				36.78°C	230.29V
40W	2.700A	0.694A	0.689A	0.294A	40.012	74.232%	0	<6.0	40.7°C	0.652
	12.114V	5.042V	3.351V	5.101V	53.9				37.17°C	230.29V
60W	4.172A	0.893A	0.887A	0.393A	60.012	80.984%	0	<6.0	42.82°C	0.727
	12.113V	5.041V	3.35V	5.095V	74.103				38.7°C	230.29V
80W	5.642A	1.091A	1.084A	0.491A	79.974	84.346%	0	<6.0	44.61°C	0.78
	12.113V	5.04V	3.349V	5.09V	94.816				39.87°C	230.29V

The results above are not used in the certification process

Ripple Measurements

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	8.03mV	12.67mV	14.37mV	4.25mV	Pass
20% Load	8.55mV	12.61mV	12.02mV	4.30mV	Pass
30% Load	12.67mV	13.43mV	12.17mV	4.86mV	Pass
40% Load	10.69mV	13.33mV	12.63mV	4.86mV	Pass
50% Load	9.93mV	13.64mV	15.90mV	5.17mV	Pass
60% Load	9.93mV	13.69mV	15.29mV	5.42mV	Pass
70% Load	9.82mV	14.51mV	15.34mV	5.53mV	Pass
80% Load	9.98mV	14.40mV	15.80mV	6.04mV	Pass
90% Load	10.03mV	15.68mV	17.44mV	6.50mV	Pass
100% Load	15.76mV	16.16mV	19.13mV	7.30mV	Pass
110% Load	15.57mV	16.86mV	19.75mV	7.84mV	Pass
Crossload1	8.61mV	13.42mV	13.64mV	8.47mV	Pass
Crossload2	9.31mV	12.62mV	14.01mV	8.09mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
Crossload3	9.21mV	12.56mV	12.78mV	7.93mV	Pass
Crossload4	15.16mV	16.33mV	19.18mV	10.58mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	7.68mV	12.36mV	11.35mV	4.40mV	Pass
20% Load	8.50mV	12.62mV	11.66mV	4.50mV	Pass
30% Load	12.31mV	13.59mV	14.98mV	4.71mV	Pass
40% Load	15.76mV	18.85mV	12.53mV	8.44mV	Pass
50% Load	9.41mV	14.45mV	14.16mV	5.48mV	Pass
60% Load	9.88mV	14.25mV	14.57mV	5.68mV	Pass
70% Load	9.82mV	14.86mV	15.50mV	5.88mV	Pass
80% Load	9.78mV	14.55mV	25.16mV	6.19mV	Pass
90% Load	9.77mV	15.02mV	16.41mV	6.24mV	Pass
100% Load	15.04mV	16.87mV	19.56mV	7.39mV	Pass
110% Load	15.22mV	17.09mV	19.87mV	7.50mV	Pass
Crossload1	8.25mV	13.97mV	13.48mV	8.00mV	Pass
Crossload2	8.85mV	12.51mV	12.17mV	8.29mV	Pass
Crossload3	8.80mV	13.07mV	12.63mV	7.93mV	Pass
Crossload4	14.15mV	16.81mV	18.26mV	10.34mV	Pass

The results above are not used in the certification process

Thermaltake Toughpower GF1 1000W



Top side



Power specifications label

All data and graphs included in this test report can be used by any individual on the following conditions:

- › It should be mentioned that the test results are provided by Cybenetics
- › The link to the original test results document should be provided in any case

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus

Cybenetics runs voluntary certification programs for power supplies - ETA for efficiency, LAMBDA for noise and SAFE for safety and correct operation - and for cooling products, with DELTA for chassis soundproofing and PHI for fan airflow and static pressure. THETA rates cooler performance on AMD AM5 and Intel LGA1851 outside ISO 17065 and accreditation scope

www.cybenetics.com - info@cybenetics.com