

NZXT

NZXT C850 Gold

Serial Number 52241Z06500003

Lab ID NZ85002451

Certification ID 252451

Test Result Report ID: 24PS2451A

Certificate Issue Date: May 22, 2024

Scheme: ETA-EMI PSU

115V



230V



115V



230V



Scheme: LAMBDA PSU



Outside Validation Scope



General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	NZXT
Model	C850 Gold
OEM/ODM	Channel Well Technology
Serial Number	52241Z06500003
Product Specifications	
Manufacturer-Provided Information	
Rated Voltage (Vrms)	100-240
Rated Current (Arms)	10

Rated Frequency (Hz)	50-60
Rated Power (W)	850
Operating Temperature (Continuous Full Load) (°C)	
Type	ATX12V
Cable Design	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
Cooling	135mm Fluid Dynamic Bearing Fan (HA13525H12SF-Z)
Semi-Passive Operation	✓ (selectable)
Cybenetics Testing Information	
Lab ID	NZ85002451
Date of receipt	May 7, 2024
Testing Date	May 21, 2024
Report Issued Date	May 22, 2024
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

Cables and Connectors(Non-accredited measurements)

Modular Cables				
Description	Cable Count	Connector Count (Total)	Gauge	In Cable Capacitors
ATX connector 20+4 pin (600mm)	1	1	16-20AWG	No
4+4 pin EPS12V (700mm)	1	1	16AWG	No
8 pin EPS12V (700mm)	1	1	16AWG	No
6+2 pin PCIe (650mm)	3	3	16-18AWG	No
12+4 pin PCIe (645mm) (600W)	1	1	16-24AWG	No
SATA (500mm+145mm+145mm+145mm)	3	12	18AWG	No
4-pin Molex (500mm+145mm+145mm+145mm)	1	4	18AWG	No

Modular Cables				
AC Power Cord (1415mm) - C13 coupler	1	1	14AWG	-

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✓

Power Specifications

Rail		3.3V	5V	12V	5VSB	-12V
Max. Power	Amps	22	22	70.83	3	0
	Watts	120		850	15	0
Total Max. Power (W)		850				

Test Results

Temperature & Compliance Info

Temperature Range (°C /°F)	28-32 / 82.4-89.6
ErP Lot 3/6 Ready	✓
(EU) No 617/2013 Compliance	✓
ALPM (Alternative Low Power Mode) compatible	✓
ATX v3.1 PSU Power Excursion	✓

Performance Summary

115V

Accredited	
Average Efficiency (>1450 load combinations)	88.749%
Average Noise Output (>1450 Load Combinations)	25.41dBA
Average PF (>1450 Load Combinations)	0.987
Efficiency With 10W ($\leq$ 500W) or 2% (>500W) Load	77.025%
Standby Power Consumption	0.0132W
Non-Accredited	
12V Ripple (Full Load)	18.63mV
5V Ripple (Full Load)	7.83mV
3.3V Ripple (Full Load)	8.71mV
5VSB Ripple (Full Load)	9.78mV
12V Load Regulation	0.91%
5V Load Regulation	0.34%
3.3V Load Regulation	0.78%
5VSB Load Regulation	1.57%
Inrush Current	35.610A

230V

Accredited	
Average Efficiency (>1450 load combinations)	90.910%
Average Noise Output (>1450 Load Combinations)	25.44dBA
Average PF (>1450 Load Combinations)	0.963
Efficiency With 10W ($\leq$ 500W) or 2% (>500W) Load	76.621%
Standby Power Consumption	0.0704W
Non-Accredited	
12V Ripple (Full Load)	18.61mV
5V Ripple (Full Load)	10.75mV
3.3V Ripple (Full Load)	8.98mV

5VSB Ripple (Full Load)	8.47mV	
12V Load Regulation	0.90%	
5V Load Regulation	0.34%	
3.3V Load Regulation	0.81%	
5VSB Load Regulation	1.57%	
Inrush Current	63.390A	
12V Transient Response (200%)	11.58V	
5V Transient Response (200%)	4.983V	
3.3V Transient Response (200%)	3.233V	
5VSB Transient Response (200%)	4.876V	
Hold-Up Time & PWR_OK Signal	25.60ms	
AC Loss to PWR_OK Hold Up Time	24.20ms	
PWR_OK Inactive to DC Loss Delay	1.40ms	
PSU Timings: T1 (20% / 100%)	63.0ms	60.0ms
PSU Timings: T3 (20% / 100%)	131.0ms	131.0ms
OPP (27.22°C / 42.84°C)	121.50%	121.14%

Hold-Up Time & PWR_OK Signal

Hold-Up Time (ms)	25.6
AC Loss to PWR_OK Hold Up Time (ms)	24.2
PWR_OK Inactive to DC Loss Delay (ms)	1.4

Vampire Power

Tables

115V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	115.18 V	115.14 V	113.85 V	115.18 V	116.15 V	PASS


Mains Frequency:	60.00 Hz	59.95 Hz	59.40 Hz	60.01 Hz	60.60 Hz	PASS
Mains Voltage CF:	1.415	1.415	1.340	1.416	1.490	PASS
Mains Voltage THD:	0.13 %	0.11 %	N/A	0.15 %	2.00 %	PASS
Real Power:	0.013 W	0.011 W	N/A	0.086 W	N/A	N/A
Apparent Power:	9.991 W	9.986 W	N/A	10.020 W	N/A	N/A
Power Factor:	0.001	N/A	N/A	N/A	N/A	N/A

230V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	230.38 V	230.34 V	227.70 V	230.40 V	232.30 V	PASS
Mains Frequency:	50.00 Hz	50.00 Hz	49.50 Hz	50.01 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.415	1.415	1.340	1.416	1.490	PASS
Mains Voltage THD:	0.14 %	0.13 %	N/A	0.16 %	2.00 %	PASS
Real Power:	0.070 W	0.061 W	N/A	0.084 W	N/A	N/A
Apparent Power:	33.435 W	33.422 W	N/A	33.445 W	N/A	N/A
Power Factor:	0.002	N/A	N/A	N/A	N/A	N/A


Efficiency Graph

115V



INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations




INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


Noise Graph

115V



INFO

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails



INFO


The PSU's noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Indicative Performance

Efficiency under high ambient temperature

Efficiency: NZXT C850 Gold

Ambient: 37°C - 47°C (98.6°F - 116.6°F)




INFO

The PSU's efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5VSB Efficiency

5VSB Efficiency: NZXT C850 Gold

Ambient: 34°C - 36°C (93.2°F - 96.8°F)



INFO

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

5VSB Efficiency (ERP LOT 3/6 & CEC)

115V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.227W	73.757%	0.031
	5.042V	0.308W		115.15V
2	0.09A	0.454W	78.223%	0.057
	5.041V	0.58W		115.15V
3	0.55A	2.771W	83.161%	0.263
	5.037V	3.332W		115.16V
4	1A	5.035W	82.835%	0.37
	5.034V	6.079W		115.16V
5	1.5A	7.548W	82.746%	0.428
	5.03V	9.121W		115.15V
6	3A	15.058W	80.417%	0.505
	5.019V	18.726W		115.14V

230V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.227W	62.437%	0.011
	5.047V	0.364W		230.37V
2	0.09A	0.454W	70.348%	0.019
	5.044V	0.646W		230.36V
3	0.55A	2.771W	80.141%	0.099
	5.038V	3.458W		230.35V
4	1A	5.036W	81.575%	0.166
	5.035V	6.173W		230.35V
5	1.5A	7.549W	81.741%	0.227
	5.032V	9.236W		230.35V
6	3A	15.059W	81.579%	0.34
	5.019V	18.459W		230.35V

Protection Features

Protection Features	
OCP (Cold @ 27°C)	12V: 85.4A (120.57%), 12.109V 5V: 27.6A (125.45%), 5.054V 3.3V: 28.6A (130%), 3.318V 5VSB: 5A (166.67%), 4.991V
OCP (Hot @ 44°C)	12V: 85A (120.01%), 12.121V 5V: 26.9A (122.27%), 5.063V 3.3V: 27.6A (125.45%), 3.317V 5VSB: 5A (166.67%), 4.993V
OPP (Cold @ 27°C)	1032.77W (121.5%)
OPP (Hot @ 43°C)	1029.73W (121.14%)
OTP	✓ (129°C @ secondary side)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓
PWR_OK	Proper operation
NLO	✓
Fan Failure Protection	✓
SIP	Surge: MOV Inrush: NTC Thermistor & Bypass relay

Supplementary Tests (For Reference)

Typical Load Tests

115V										
Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
	5.216A	1.97A	1.972A	0.992A	84.998	84.985%	0	<6.0	44.3°C	0.964
	12.153V	5.077V	3.346V	5.04V	100.016				40.03°C	115.12V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
	11.436A	2.956A	2.961A	1.192A	169.951	88.903%	0	<6.0	45.45°C	0.982
	12.159V	5.075V	3.343V	5.034V	191.166				40.83°C	115.09V
	18.007A	3.45A	3.458A	1.393A	254.97	90.416%	0	<6.0	46.4°C	0.986
	12.157V	5.074V	3.34V	5.028V	281.995				41.4°C	115.07V
	24.616A	3.943A	3.957A	1.593A	340.073	91.088%	0	<6.0	47.35°C	0.988
	12.141V	5.073V	3.337V	5.022V	373.349				41.79°C	115.05V
	30.870A	4.932A	4.949A	1.796A	425.097	90.903%	409	<6.0	42.1°C	0.99
	12.134V	5.071V	3.334V	5.014V	467.635				48.18°C	115.03V
	37.089A	5.921A	5.943A	1.998A	509.583	90.499%	412	<6.0	42.62°C	0.992
	12.126V	5.068V	3.332V	5.005V	563.078				49.12°C	115.01V
	43.373A	6.91A	6.94A	2.201A	594.867	89.906%	645	14.6	43.43°C	0.994
	12.121V	5.066V	3.329V	4.998V	661.659				50.45°C	114.98V
	49.676A	7.9A	7.937A	2.305A	679.703	89.247%	793	21.5	43.56°C	0.995
	12.115V	5.064V	3.326V	4.991V	761.594				51.59°C	114.96V
	56.370A	8.397A	8.424A	2.408A	765.174	88.541%	1031	29.9	44.57°C	0.995
	12.110V	5.062V	3.324V	4.983V	864.217				53.66°C	114.94V
	62.780A	8.894A	8.944A	3.018A	850.061	87.65%	1248	36.1	45.71°C	0.996
	12.112V	5.06V	3.321V	4.97V	969.831				55.74°C	114.92V
	69.061A	9.887A	10.037A	3.022A	934.604	86.852%	1459	40.2	46.74°C	0.996
	12.110V	5.058V	3.317V	4.964V	1076.079				57.68°C	114.89V
	0.115A	14.252A	14.32A	0A	121.305	82.342%	408	<6.0	40.74°C	0.976
	12.158V	5.066V	3.331V	5.04V	147.323				51.92°C	115.12V
	0.115A	21.705A	0A	0A	111.393	80.545%	407	<6.0	41.65°C	0.975
	12.162V	5.068V	3.334V	5.046V	138.303				50.93°C	115.13V
	0.115A	0A	21.895A	0A	73.995	74.772%	406	<6.0	41.18°C	0.965
	12.155V	5.081V	3.316V	5.04V	98.96				49.84°C	115.14V
	70.164A	0A	0A	0A	849.753	88.464%	1270	36.7	45.41°C	0.996
	12.111V	5.073V	3.32V	5.007V	960.571				51.83°C	114.93V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
	5.217A	1.972A	1.974A	0.992A	85.001	86.191%	0	<6.0	44.37°C	0.879
	12.152V	5.073V	3.344V	5.04V	98.617				40.11°C	230.35V
	11.438A	2.958A	2.963A	1.192A	169.961	90.159%	0	<6.0	45.37°C	0.943
	12.157V	5.072V	3.341V	5.034V	188.508				40.78°C	230.34V
	18.008A	3.452A	3.461A	1.393A	254.97	91.959%	0	<6.0	46.22°C	0.962
	12.156V	5.071V	3.338V	5.028V	277.264				41.05°C	230.33V
	24.619A	3.946A	3.959A	1.593A	340.062	92.793%	0	<6.0	47.32°C	0.971
	12.139V	5.07V	3.334V	5.022V	366.472				41.77°C	230.32V
	30.866A	4.935A	4.952A	1.796A	424.994	92.88%	413	<6.0	42.26°C	0.976
	12.133V	5.067V	3.332V	5.013V	457.573				48.31°C	230.31V
	37.091A	5.926A	5.946A	1.998A	509.521	92.708%	413	<6.0	42.85°C	0.979
	12.124V	5.064V	3.33V	5.005V	549.602				49.53°C	230.3V
	43.385A	6.916A	6.944A	2.201A	594.854	92.384%	592	11.9	43.32°C	0.982
	12.118V	5.062V	3.327V	4.997V	643.89				50.38°C	230.28V
	49.685A	7.906A	7.941A	2.305A	679.669	91.967%	777	20.8	43.7°C	0.984
	12.112V	5.06V	3.324V	4.99V	739.036				51.78°C	230.28V
	56.376A	8.403A	8.428A	2.409A	765.096	91.552%	1034	30.0	44.23°C	0.986
	12.107V	5.058V	3.322V	4.983V	835.655				53.23°C	230.26V
	62.784A	8.901A	8.947A	3.018A	849.921	91.073%	1249	36.1	45.55°C	0.988
	12.109V	5.056V	3.319V	4.97V	933.232				55.58°C	230.25V
	69.063A	9.887A	10.037A	3.022A	934.486	90.558%	1459	40.2	46.62°C	0.988
	12.108V	5.057V	3.317V	4.964V	1031.914				57.48°C	230.24V
	0.115A	14.252A	14.32A	0A	121.291	83.479%	409	<6.0	41.38°C	0.924
	12.156V	5.066V	3.331V	5.04V	145.296				48.33°C	230.35V
	0.115A	21.707A	0A	0A	111.385	81.527%	408	<6.0	40.44°C	0.919
	12.161V	5.067V	3.334V	5.045V	136.624				47.53°C	230.35V
	0.115A	0A	21.889A	0A	73.985	75.817%	407	<6.0	40.87°C	0.879
	12.153V	5.081V	3.316V	5.04V	97.583				47.47°C	230.35V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
	70.161A	0A	0A	0A	849.607	91.838%	1273	36.7	45.05°C	0.987
	12.110V	5.072V	3.32V	5.007V	925.114				48.91°C	230.25V

The results above are not used in the certification process

Light Load Tests

115V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.232A	0.493A	0.494A	0.198A	20.003	77.248%	0	<6.0	39.68°C	0.875
	12.049V	5.073V	3.341V	5.048V	25.894				36.61°C	115.15V
40W	2.712A	0.69A	0.691A	0.297A	39.999	83.354%	0	<6.0	40.92°C	0.935
	12.053V	5.072V	3.344V	5.047V	47.984				37.62°C	115.14V
60W	4.159A	0.887A	0.887A	0.396A	59.996	83.07%	0	<6.0	42.16°C	0.953
	12.149V	5.073V	3.347V	5.046V	72.215				38.51°C	115.13V
80W	5.622A	1.084A	1.084A	0.496A	79.946	85.084%	0	<6.0	43.43°C	0.963
	12.152V	5.077V	3.347V	5.045V	93.962				39.51°C	115.11V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.232A	0.493A	0.494A	0.198A	20.001	77.898%	0	<6.0	39.63°C	0.519
	12.048V	5.073V	3.341V	5.048V	25.674				36.57°C	230.36V
40W	2.712A	0.69A	0.691A	0.297A	39.998	83.843%	0	<6.0	41.09°C	0.72
	12.051V	5.073V	3.343V	5.047V	47.707				37.73°C	230.36V
60W	4.160A	0.887A	0.888A	0.397A	59.997	83.466%	0	<6.0	41.74°C	0.825
	12.144V	5.073V	3.346V	5.046V	71.882				38.07°C	230.36V
80W	5.624A	1.084A	1.085A	0.496A	79.955	86.305%	0	<6.0	42.83°C	0.869
	12.149V	5.073V	3.345V	5.044V	92.643				39.03°C	230.35V

The results above are not used in the certification process

Ripple Measurements

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	6.97mV	5.26mV	3.61mV	5.04mV	Pass
20% Load	7.38mV	5.82mV	3.51mV	5.15mV	Pass
30% Load	8.70mV	5.51mV	3.66mV	5.45mV	Pass
40% Load	10.65mV	5.81mV	4.68mV	5.30mV	Pass
50% Load	10.13mV	6.94mV	4.83mV	5.50mV	Pass
60% Load	11.50mV	15.35mV	14.80mV	5.86mV	Pass
70% Load	10.58mV	6.17mV	5.04mV	5.91mV	Pass
80% Load	11.80mV	7.75mV	7.83mV	6.06mV	Pass
90% Load	12.67mV	9.54mV	8.49mV	6.78mV	Pass
100% Load	18.63mV	7.83mV	8.71mV	9.78mV	Pass
110% Load	17.76mV	13.80mV	10.23mV	10.04mV	Pass
Crossload1	8.92mV	7.02mV	9.16mV	7.27mV	Pass
Crossload2	9.26mV	6.12mV	3.97mV	6.47mV	Pass
Crossload3	8.24mV	6.33mV	9.82mV	6.52mV	Pass
Crossload4	16.98mV	6.65mV	5.19mV	7.36mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	6.87mV	5.41mV	3.51mV	4.89mV	Pass
20% Load	7.02mV	5.36mV	3.66mV	5.35mV	Pass
30% Load	8.75mV	5.20mV	3.51mV	5.09mV	Pass
40% Load	11.58mV	5.97mV	4.78mV	6.16mV	Pass
50% Load	10.80mV	6.48mV	4.63mV	5.66mV	Pass
60% Load	10.19mV	15.56mV	13.83mV	5.66mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
70% Load	10.43mV	6.68mV	5.24mV	5.91mV	Pass
80% Load	11.04mV	7.50mV	7.73mV	5.60mV	Pass
90% Load	12.06mV	9.23mV	8.24mV	6.73mV	Pass
100% Load	18.61mV	10.75mV	8.98mV	8.47mV	Pass
110% Load	18.85mV	13.79mV	9.99mV	12.12mV	Pass
Crossload1	8.88mV	7.41mV	9.24mV	7.41mV	Pass
Crossload2	9.21mV	6.12mV	3.86mV	7.08mV	Pass
Crossload3	8.09mV	6.63mV	10.02mV	6.88mV	Pass
Crossload4	17.69mV	8.73mV	5.67mV	7.12mV	Pass

The results above are not used in the certification process

NZXT C850 Gold



Top side

All data and graphs included in this test report can be used by any individual on the following conditions:

- › It should be mentioned that the test results are provided by Cybenetics
- › The link to the original test results document should be provided in any case

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus

NZXT				
PRODUCT TYPE 产品名称, 產品類別, 제 품 명	Switching Power Supply 交換式電源供應器 , 交換式電源供應器 , 컴퓨터용 전원공급장치			
MODEL NO. 型号, 型號, 모델명	PS-2302			
AC INPUT RATING 交流輸入, 交流輸入, 정격입력	100V-240V- 10A-5A 50Hz-60Hz			
DC OUTPUT RATING 直流輸出, 直流輸出, 정격출력	+3.3V	+5V	+12V	+5Vsb
	22A	22A	70.83A	3A
	120W		850W	15W
	850W			
⚠ CAUTION! ⚠ HAZARDOUS! ITE Power Supply Do not remove this cover! Trained service people only! No serviceable components inside! ATTENTION! DANGEREUX! Ne retirez pas cette couverture! Personne de service qualifié seulement! Aucun composant réparable à l'intérieur! VORSICHT! GEFAHRLICH! Entfernen Sie diese Abdeckung nicht! Nur ausgebildete Serviceleute! Keine wartbaren Komponenten im Inneren! 警告! 危險! 請勿打開上蓋! 僅能由專業合格人員進行維修! 內部無任何可維修物件! 警告! 危險! 請勿打開上蓋! 僅能由專業合格人員進行維修! 內部無任何可維修物件! ©2024 NZXT, Inc. Visit nzxt.com for more information. Made in China. 中國製造. 中國製造. Manufacturer. 製造商. 製造商: NZXT, Inc.				

Power specifications label

Cybenetics runs voluntary certification programs for power supplies - ETA for efficiency, LAMBDA for noise and SAFE for safety and correct operation - and for cooling products, with DELTA for chassis soundproofing and PHI for fan airflow and static pressure. THETA rates cooler performance on AMD AM5 and Intel LGA1851 outside ISO 17065 and accreditation scope

www.cybenetics.com - info@cybenetics.com