Sharkoon Rebel P10 850

Lab ID SK85002586

Certification ID 252586

Test Result Report ID: 24PS2586A

Certificate Issue Date: Nov 15, 2024

Scheme: ETA-EMI PSU

115V



230V



Scheme: LAMBDA PSU

115V



230V





Outside Validation Scope




General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	Sharkoon
Model	Rebel P10 850
OEM/ODM	Andyson
Serial Number	
Product Specifications	
Manufacturer-Provided Information	
□□□□ (Vrms)	100-240
□□□□ (Arms)	10-5

□□□□ (Hz)	50-60
□□□□ (W)	850
Operating Temperature (Continuous Full Load) (°C)	
□□	ATX12V
□□□□	Fixed cables
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
□□	120mm Sleeve Bearing Fan (S1202512M)
□□□□□	✗
Cybenetics Testing Information	
Lab ID	SK85002586
Date of receipt	Oct 29, 2024
Testing Date	Nov 8, 2024
Report Issued Date	Nov 15, 2024
□□□□□	Excessive noise at 989RPM
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

□□□□ (Non-accredited measurements)

□□□□				
□□	□□□□	□□□□□□	**Gauge**	In Cable Capacitors
ATX □□ 20+4 pin (545mm)	1	1	18-22AWG	□
4+4 pin EPS 12V □□ (620mm)	2	2	18AWG	□
6+2pin PCIe□□ (575mm+150mm)	2	4	18AWG	□
SATA□□ (465mm+120mm+120mm)	1	3	18AWG	□
SATA□□ (460mm+120mm) / 4-pin Molex (+120mm)	1	2 / 1	18AWG	□

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✗

□□□□

□		3.3V	5V	12V	5VSB	-12V
□□□□	□□	18	18	70.8	3	0.3
	□	100		850	15	3.6
□□□□□ (W)		850				

Test Results

Temperature & Compliance Info

□□□□ (°C /°F)	28-32 / 82.4-89.6
□□ ErP Lot3/6□□	✓
□□ (EU) No 617/2013□□	✓
ALPM (Alternative Low Power Mode) compatible	✓
ATX v3.1 PSU Power Excursion	✓

Performance Summary

115V

Accredited	
□□□□ (>1450 load combinations)	85.183%

Average Noise Output (>1450 Load Combinations)	37.03dBA
PF□□□ (>1450 Load Combinations)	0.988
Efficiency With 10W (≤500W) or 2% (>500W) Load	66.879%
□□□□□□	0.0678W
Non-Accredited	
12V Ripple (Full Load)	44.65mV
5V Ripple (Full Load)	30.81mV
3.3V Ripple (Full Load)	28.66mV
5VSB Ripple (Full Load)	30.02mV
12V Load Regulation	0.87%
5V Load Regulation	1.99%
3.3V Load Regulation	4.31%
5VSB Load Regulation	4.33%
Inrush Current	32.600A

230V

Accredited	
□□□□ (>1450 load combinations)	87.644%
Average Noise Output (>1450 Load Combinations)	36.95dBA
PF□□□ (>1450 Load Combinations)	0.961
Efficiency With 10W (≤500W) or 2% (>500W) Load	-
□□□□□□	0.1719W
Non-Accredited	
12V Ripple (Full Load)	44.11mV
5V Ripple (Full Load)	28.48mV
3.3V Ripple (Full Load)	26.53mV
5VSB Ripple (Full Load)	26.88mV
12V Load Regulation	0.83%
5V Load Regulation	2.01%
3.3V Load Regulation	4.25%
5VSB Load Regulation	4.31%
Inrush Current	65.300A

12V Transient Response (150%)		11.58V
5V Transient Response (150%)		4.954V
3.3V Transient Response (150%)		3.197V
5VSB Transient Response (150%)		4.912V
□□□□ & PG□□		18.00ms
AC Loss to PWR_OK Hold Up Time		14.60ms
PWR_OK Inactive to DC Loss Delay		3.40ms
PSU Timings: T1 (20% / 100%)	28.0ms	27.0ms
PSU Timings: T3 (20% / 100%)	119.0ms	119.0ms
12V OCP (28.2°C / 44.8°C)	92.20A (130.23%), 12.035V	86.40A (122.03%), 12.027V
5V OCP (28.2°C / 44.8°C)	22.7A (126.11%), 5.08V	21.7A (120.56%), 5.085V*
3.3V OCP (28.2°C / 44.8°C)	22.4A (124.44%), 3.341V	
5VSB OCP (28.2°C / 44.8°C)	4.7A (156.67%), 4.965V*	21.2A (117.78%), 3.342V
OPP (29.37°C / 44.73°C)	135.61%	115.61%

□□□□ & PG□□

Hold-Up Time (ms)	18
AC Loss to PWR_OK Hold Up Time (ms)	14.6
PWR_OK Inactive to DC Loss Delay (ms)	3.4

□□□□

Tables

115V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	114.88 V	114.82 V	113.85 V	114.93 V	116.15 V	PASS
Mains Frequency:	60.00 Hz	59.98 Hz	59.40 Hz	60.01 Hz	60.60 Hz	PASS
Mains Voltage CF:	1.419	1.417	1.340	1.422	1.490	PASS


Mains Voltage THD:	0.15 %	0.09 %	N/A	0.30 %	2.00 %	PASS
Real Power:	0.068 W	0.020 W	N/A	0.099 W	N/A	N/A
Apparent Power:	7.803 W	7.789 W	N/A	7.822 W	N/A	N/A
Power Factor:	0.011	N/A	N/A	N/A	N/A	N/A

230V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	229.98 V	229.90 V	227.70 V	230.03 V	232.30 V	PASS
Mains Frequency:	50.00 Hz	49.99 Hz	49.50 Hz	50.01 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.417	1.415	1.340	1.419	1.490	PASS
Mains Voltage THD:	0.14 %	0.08 %	N/A	0.21 %	2.00 %	PASS
Real Power:	0.172 W	0.137 W	N/A	0.228 W	N/A	N/A
Apparent Power:	26.680 W	26.645 W	N/A	26.730 W	N/A	N/A
Power Factor:	0.007	N/A	N/A	N/A	N/A	N/A

□□□□□□


115V



□□

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


230V



This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations

□□□□□


115V



□□

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

230V



The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Noise under high ambient temperature (indicative)

115V

Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	910 RPM · 22.7 dB(A) · 29.7 °C	969 RPM · 24.8 dB(A) · 40.1 °C	**+2.1 dB(A)**
20%	926 RPM · 23.2 dB(A) · 30.1 °C	1119 RPM · 27.9 dB(A) · 40.6 °C	**+4.7 dB(A)**
50%	1358 RPM · 35.1 dB(A) · 30.7 °C	1722 RPM · 39.1 dB(A) · 42.1 °C	**+4.0 dB(A)**
100%	2164 RPM · 44.6 dB(A) · 30.5 °C	2314 RPM · 46.5 dB(A) · 45.2 °C	**+1.9 dB(A)**

230V


Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	907 RPM · 22.3 dB(A) · 30.2 °C	989 RPM · 30.0 dB(A) · 40.5 °C	**+7.7 dB(A)**
20%	919 RPM · 22.9 dB(A) · 30.5 °C	1145 RPM · 28.2 dB(A) · 40.7 °C	**+5.3 dB(A)**
50%	1291 RPM · 32.9 dB(A) · 30.8 °C	1718 RPM · 39.0 dB(A) · 42.1 °C	**+6.1 dB(A)**
100%	2103 RPM · 43.8 dB(A) · 30.7 °C	2310 RPM · 46.4 dB(A) · 45.5 °C	**+2.6 dB(A)**

INFO

Fan speed, noise and the measured intake temperature at 10, 20, 50 and 100 % load, from the two load regulation tests: at normal ambient (about 30-32 °C) and at high ambient (about 40-47 °C). These are stabilized readings at fixed loads, not averages over the certification sweep, so they are indicative of how the fan behaves when it is hot. "<6.0" is the floor of our sound meter, with the fan stopped; with the fan stopped, the intake sensor can read higher than the chamber air.


Informational. Not part of the ETA or LAMBDA rating.

Indicative Performance



The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5Vsb□□□□



□□

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

□□□□ □□ 5Vsb □□ (ErP Lot3/6 & CEC)

115V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.23W	61.981%	0.047
	5.111V	0.371W		114.87V
2	**0.09A**	0.46W	70.135%	0.081
	5.11V	0.656W		114.87V
3	**0.55A**	2.804W	77.525%	0.292
	5.098V	3.618W		114.87V
4	**1A**	5.088W	78.238%	0.346
	5.087V	6.504W		114.87V
5	**1.5A**	7.612W	79.091%	0.387
	5.074V	9.625W		114.86V
6	**3.001A**	15.109W	77.674%	0.444
	5.035V	19.452W		114.87V

230V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.23W	52.516%	0.017
	5.111V	0.438W		229.98V
2	**0.09A**	0.46W	60.502%	0.028
	5.11V	0.762W		229.97V
3	**0.55A**	2.804W	74.839%	0.129
	5.099V	3.748W		229.95V
4	**1A**	5.089W	76.259%	0.203
	5.088V	6.673W		229.95V
5	**1.5A**	7.615W	77.05%	0.236
	5.076V	9.883W		229.95V
6	**3A**	15.119W	77.491%	0.329
	5.039V	19.511W		229.94V

Protection Features

OCP (Normal @ 28.2°C)	12V: 92.20A (130.23%), 12.035V 5V: 22.7A (126.11%), 5.08V 3.3V: 22.4A (124.44%), 3.341V 5VSB: 4.7A (156.67%), 4.965V* *High Ripple (52.8mV)
OCP (Hot @ 44.8°C)	12V: 86.40A (122.03%), 12.027V 5V: 21.7A (120.56%), 5.085V* *High Ripple (52.34mV) 3.3V: 21.2A (117.78%), 3.342V 5VSB: 4.6A (153.33%), 4.957V
OPP (Normal @ 29.4°C)	1152.65W (135.61%)
OPP (Hot @ 44.7°C)	982.66W (115.61%)
OTP	✓ (145°C @ Secondary Side)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓ -12V to Earth: ✓
PWR_OK	Proper Operation
NLO	✓
Fan Failure Protection	✗
SIP	Surge: MOV Inrush: NTC & Bypass Relay

Supplementary Tests (For Reference)

10-110%□□□□

115V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
10%	**5.242A**	**1.958A**	**1.956A**	**0.986A**	85.012	83.322%	969	24.8	40.14°C	0.958
	12.096V	5.107V	3.375V	5.073V	102.028				42.76°C	114.85V
20%	**11.506A**	**2.944A**	**2.946A**	**1.187A**	169.966	87.05%	1119	27.9	40.63°C	0.979
	12.086V	5.097V	3.361V	5.054V	195.252				43.7°C	114.82V
30%	**18.127A**	**3.441A**	**3.449A**	**1.39A**	254.981	87.788%	1332	33.9	41.4°C	0.987
	12.078V	5.087V	3.349V	5.036V	290.452				44.25°C	114.79V
40%	**24.764A**	**3.94A**	**3.956A**	**1.595A**	340.079	87.722%	1511	36.7	41.8°C	0.992
	12.069V	5.077V	3.337V	5.018V	387.678				44.89°C	114.76V
50%	**31.051A**	**4.935A**	**4.967A**	**1.801A**	424.976	87.099%	1722	39.1	42.09°C	0.994
	12.059V	5.067V	3.322V	4.999V	487.923				46.19°C	114.73V
60%	**37.317A**	**5.935A**	**5.987A**	**2A**	509.453	86.329%	1891	41.4	42.73°C	0.995
	12.050V	5.056V	3.308V	4.979V	590.127				47.21°C	114.69V
70%	**43.662A**	**6.94A**	**7.017A**	**2.219A**	594.807	85.338%	2054	43.5	43.3°C	0.996
	12.040V	5.045V	3.293V	4.958V	696.999				48.71°C	114.66V
80%	**50.024A**	**7.946A**	**8.056A**	**2.329A**	679.625	84.176%	2235	45.5	43.53°C	0.997
	12.029V	5.034V	3.277V	4.94V	807.386				50.8°C	114.63V
90%	**56.792A**	**8.46A**	**8.58A**	**2.438A**	765.023	82.971%	2310	46.4	44.2°C	0.997
	12.017V	5.024V	3.263V	4.923V	922.038				53.48°C	114.59V
100%	**63.316A**	**8.974A**	**9.143A**	**3.067A**	849.795	81.487%	2314	46.5	45.21°C	0.997
	12.005V	5.015V	3.248V	4.892V	1042.859				57.17°C	114.55V
110%	**69.676A**	**9.996A**	**10.294A**	**3.075A**	934.26	80.169%	2320	46.5	46.01°C	0.998
	11.999V	5.002V	3.234V	4.879V	1165.377				58.72°C	114.52V
CL1	**0.115A**	**11.825A**	**11.895A**	**0A**	101.297	78.297%	1697	38.8	41.94°C	0.97
	12.084V	5.091V	3.337V	5.076V	129.378				47.07°C	114.83V

CL2	**0.115A**	**17.665A**	**0A**	**0.001A**	91.393	77.635%	1362	35.2	40.66°C	0.964
	12.095V	5.095V	3.357V	5.087V	117.723				44.44°C	114.84V
CL3	**0.115A**	**0A**	**17.728A**	**0A**	60.783	72.318%	1202	29.8	41.2°C	0.948
	12.093V	5.096V	3.35V	5.084V	84.051				43.86°C	114.85V
CL4	**70.683A**	**0A**	**0A**	**0.001A**	849.496	82.706%	2321	46.5	45.28°C	0.997
	12.019V	5.037V	3.29V	4.993V	1027.152				55.33°C	114.57V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
10%	**5.242A**	**1.958A**	**1.955A**	**0.985A**	85.006	84.987%	989	30	40.47°C	0.859
	12.096V	5.108V	3.376V	5.074V	100.018				43.13°C	229.94V
20%	**11.504A**	**2.943A**	**2.945A**	**1.187A**	169.95	88.754%	1145	28.2	40.73°C	0.935
	12.086V	5.097V	3.362V	5.055V	191.484				43.27°C	229.93V
30%	**18.125A**	**3.441A**	**3.449A**	**1.39A**	254.965	89.628%	1339	34	41.05°C	0.96
	12.078V	5.088V	3.349V	5.037V	284.476				43.82°C	229.91V
40%	**24.762A**	**3.94A**	**3.956A**	**1.594A**	340.063	89.68%	1550	37.6	41.67°C	0.972
	12.069V	5.078V	3.337V	5.019V	379.195				44.91°C	229.89V
50%	**31.046A**	**4.935A**	**4.967A**	**1.8A**	424.927	89.315%	1718	39	42.13°C	0.978
	12.060V	5.067V	3.322V	5V	475.764				45.34°C	229.88V
60%	**37.308A**	**5.935A**	**5.986A**	**2A**	509.379	88.81%	1892	41.4	42.79°C	0.983
	12.051V	5.056V	3.308V	4.98V	573.56				46.75°C	229.87V
70%	**43.648A**	**6.939A**	**7.015A**	**2.218A**	594.712	88.18%	2043	43.2	43.03°C	0.986
	12.042V	5.046V	3.294V	4.96V	674.431				47.54°C	229.85V
80%	**50.002A**	**7.945A**	**8.052A**	**2.327A**	679.518	87.488%	2209	45.3	43.88°C	0.988
	12.032V	5.034V	3.278V	4.942V	776.694				49.19°C	229.84V
90%	**56.767A**	**8.459A**	**8.575A**	**2.437A**	764.926	86.714%	2301	46.4	44.67°C	0.989
	12.022V	5.024V	3.265V	4.925V	882.128				50.75°C	229.82V
100%	**63.285A**	**8.974A**	**9.138A**	**3.065A**	849.736	85.732%	2310	46.4	45.5°C	0.991
	12.010V	5.014V	3.25V	4.894V	991.156				53.08°C	229.81V

110%	**69.688A**	**9.993A**	**10.299A**	**3.076A**	934.322	84.687%	2309	46.4	46.45°C	0.992
	11.997V	5.003V	3.233V	4.877V	1103.265				55.56°C	229.79V
CL1	**0.116A**	**11.825A**	**11.895A**	**0A**	101.296	79.936%	1685	38.7	40.24°C	0.895
	12.086V	5.091V	3.337V	5.076V	126.723				45.12°C	229.94V
CL2	**0.115A**	**17.665A**	**0A**	**0.001A**	91.392	79.36%	1335	33.9	40.24°C	0.881
	12.096V	5.095V	3.357V	5.087V	115.162				43.77°C	229.94V
CL3	**0.114A**	**0A**	**17.727A**	**0A**	60.782	73.373%	1184	29.1	40.78°C	0.828
	12.094V	5.096V	3.351V	5.084V	82.84				43.37°C	229.94V
CL4	**70.667A**	**0A**	**0A**	**0.001A**	849.486	86.692%	2316	46.5	46.97°C	0.99
	12.021V	5.036V	3.291V	4.994V	979.896				52.43°C	229.81V

The results above are not used in the certification process

20-80□□□□□

115V

□□	**12V**	**5V**	**3.3V**	**5VSB**	**DC/AC (□)**	□□	□□□□ **(RPM)**	□□□□□□□□ **(dB[A])**	□□ **(□□ /□□)**	**PF/AC □□**
20W	**1.227A**	**0.489A**	**0.487A**	**0.196A**	20.008	66.781%	921	23.2	36.74°C	0.872
	12.109V	5.115V	3.388V	5.104V	29.961				39.02°C	114.87V
40W	**2.701A**	**0.685A**	**0.682A**	**0.294A**	40.007	78.172%	930	23.1	37.59°C	0.921
	12.105V	5.113V	3.385V	5.099V	51.174				39.71°C	114.87V
60W	**4.176A**	**0.881A**	**0.878A**	**0.393A**	60.007	81.18%	941	22.8	38.71°C	0.941
	12.101V	5.111V	3.382V	5.093V	73.92				41.3°C	114.86V
80W	**5.648A**	**1.077A**	**1.074A**	**0.491A**	79.96	83.762%	954	23.1	39.66°C	0.955
	12.099V	5.109V	3.379V	5.088V	95.463				42.1°C	114.85V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
20W	**1.226A**	**0.489A**	**0.487A**	**0.196A**	19.998	67.038%	936	22.8	36.19°C	0.565
	12.110V	5.115V	3.388V	5.105V	29.831				38.57°C	229.95V
40W	**2.700A**	**0.685A**	**0.682A**	**0.294A**	39.998	78.744%	934	23	37.35°C	0.72
	12.106V	5.113V	3.386V	5.1V	50.792				39.29°C	229.95V
60W	**4.175A**	**0.88A**	**0.878A**	**0.393A**	59.998	82.668%	939	22.8	38.21°C	0.804
	12.103V	5.111V	3.383V	5.094V	72.577				40.35°C	229.95V
80W	**5.645A**	**1.076A**	**1.074A**	**0.491A**	79.938	85.242%	950	22.6	39.08°C	0.848
	12.100V	5.11V	3.38V	5.089V	93.775				41.27°C	229.94V

The results above are not used in the certification process

□□□□

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	11.6 mV	17.2 mV	14.0 mV	20.7 mV	Pass
20% Load	13.5 mV	17.9 mV	14.3 mV	22.3 mV	Pass
30% Load	14.8 mV	17.8 mV	14.8 mV	22.3 mV	Pass
40% Load	15.9 mV	17.9 mV	15.8 mV	22.0 mV	Pass
50% Load	17.8 mV	21.0 mV	16.5 mV	22.6 mV	Pass
60% Load	20.7 mV	19.9 mV	18.4 mV	22.1 mV	Pass
70% Load	25.5 mV	21.6 mV	21.3 mV	22.5 mV	Pass
80% Load	30.0 mV	24.5 mV	25.4 mV	24.3 mV	Pass
90% Load	34.7 mV	26.6 mV	25.6 mV	25.9 mV	Pass
100% Load	44.7 mV	30.8 mV	28.7 mV	30.0 mV	Pass
110% Load	49.7 mV	31.1 mV	31.4 mV	29.4 mV	Pass
Crossload 1	18.7 mV	29.4 mV	25.3 mV	20.9 mV	Pass
Crossload 2	16.7 mV	30.2 mV	18.8 mV	20.5 mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
Crossload 3	15.0 mV	18.7 mV	22.1 mV	15.4 mV	Pass
Crossload 4	40.6 mV	20.2 mV	24.9 mV	28.7 mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	10.8 mV	16.4 mV	13.8 mV	19.7 mV	Pass
20% Load	12.7 mV	16.9 mV	13.8 mV	21.2 mV	Pass
30% Load	13.2 mV	17.5 mV	14.1 mV	19.8 mV	Pass
40% Load	14.8 mV	17.8 mV	14.9 mV	19.3 mV	Pass
50% Load	18.7 mV	19.6 mV	16.6 mV	19.9 mV	Pass
60% Load	20.9 mV	19.5 mV	18.4 mV	19.6 mV	Pass
70% Load	25.0 mV	20.0 mV	19.7 mV	20.8 mV	Pass
80% Load	30.7 mV	24.0 mV	22.9 mV	21.1 mV	Pass
90% Load	34.5 mV	25.1 mV	25.1 mV	22.3 mV	Pass
100% Load	44.1 mV	28.5 mV	26.5 mV	26.9 mV	Pass
110% Load	48.0 mV	30.9 mV	30.1 mV	26.9 mV	Pass
Crossload 1	18.5 mV	27.2 mV	23.9 mV	19.9 mV	Pass
Crossload 2	16.5 mV	30.5 mV	19.0 mV	20.5 mV	Pass
Crossload 3	14.9 mV	18.4 mV	21.2 mV	14.5 mV	Pass
Crossload 4	39.4 mV	17.0 mV	21.4 mV	22.8 mV	Pass

The results above are not used in the certification process

Sharkoon Rebel P10 850



Top side



Power specifications label

Cybenetics

Cybenetics ETA LAMBDA SAFE DELTA PHI