Cougar GLE 850W

NBD08GL85000054

Lab ID CG85002593

Certification ID 252593

Test Result Report ID: 24PS2593A

Certificate Issue Date: Oct 8, 2024

Scheme: ETA-EMI PSU

115V 230V

Scheme: LAMBDA PSU

115V 230V

Outside Validation Scope

General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	Cougar
Model	GLE 850W
OEM/ODM	CE-Link
Serial Number	NBD08GL85000054
Product Specifications	
Manufacturer-Provided Information	
□□□□ (Vrms)	100-240
□□□□ (Arms)	12-6

□□□□ (Hz)	50-60
□□□□ (W)	850
Operating Temperature (Continuous Full Load) (°C)	
□□	ATX12V
□□□□	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
□□	135mm Hydro Dynamic Bearing Fan (RL4Z S1352512H)
□□□□□	✗
Cybenetics Testing Information	
Lab ID	CG85002593
Date of receipt	Sep 16, 2024
Testing Date	Oct 4, 2024
Report Issued Date	Oct 8, 2024
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

□□□□ (Non-accredited measurements)

□□□□				
□□	□□□□	□□□□□	**Gauge**	In Cable Capacitors
ATX □□ 24 pin (605mm)	1	1	16-22AWG	□
4+4 pin EPS 12V □□ (650mm)	1	1	16AWG	□
8 pin EPS 12V □□ (650mm)	1	1	16AWG	□
6+2pin PCIe□□ (600mm+160mm)	1	2	16-18AWG	□
6+2pin PCIe□□ (600mm)	2	2	16AWG	□
12+2 pin PCIe (650mm) (600W)	1	1	16-24AWG	□
SATA□□ (405mm+150mm+150mm+150mm)	3	12	18AWG	□

4-pin Molex (405mm+105mm+105mm+105mm)	1	4	18AWG	□
AC Power Cord (1850mm) - C13 coupler	1	1	14AWG	-

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✗

□□□□

□		3.3V	5V	12V	5VSB	-12V
□□□□	□□	20	20	70.8	3	0.3
	□	120		850	15	3.6
□□□□□ (W)		850				

Test Results

Temperature & Compliance Info

□□□□ (°C /°F)	28-32 / 82.4-89.6
□□ ErP Lot3/6□□	✓
□□ (EU) No 617/2013□□	✓
ALPM (Alternative Low Power Mode) compatible	✓
ATX v3.1 PSU Power Excursion	✓

Performance Summary

115V

Accredited	
□□□□ (>1450 load combinations)	88.107%
Average Noise Output (>1450 Load Combinations)	27.37dBA
PF□□□ (>1450 Load Combinations)	0.994
Efficiency With 10W (≤500W) or 2% (>500W) Load	70.250%
□□□□□□	0.0610W
Non-Accredited	
12V Ripple (Full Load)	21.17mV
5V Ripple (Full Load)	19.17mV
3.3V Ripple (Full Load)	20.61mV
5VSB Ripple (Full Load)	17.11mV
12V Load Regulation	1.47%
5V Load Regulation	0.70%
3.3V Load Regulation	0.67%
5VSB Load Regulation	3.02%
Inrush Current	34.900A

230V

Accredited	
□□□□ (>1450 load combinations)	90.195%
Average Noise Output (>1450 Load Combinations)	27.03dBA
PF□□□ (>1450 Load Combinations)	0.965
Efficiency With 10W (≤500W) or 2% (>500W) Load	-
□□□□□□	0.1371W
Non-Accredited	
12V Ripple (Full Load)	20.26mV
5V Ripple (Full Load)	19.67mV
3.3V Ripple (Full Load)	20.12mV

5VSB Ripple (Full Load)		16.24mV
12V Load Regulation		1.47%
5V Load Regulation		0.70%
3.3V Load Regulation		0.67%
5VSB Load Regulation		3.04%
Inrush Current		66.800A
12V Transient Response (200%)		11.34V
5V Transient Response (200%)		4.938V
3.3V Transient Response (200%)		3.207V
5VSB Transient Response (200%)		4.988V
□□□□ & PG□□		18.00ms
AC Loss to PWR_OK Hold Up Time		15.00ms
PWR_OK Inactive to DC Loss Delay		3.00ms
PSU Timings: T1 (20% / 100%)	109.0ms	54.0ms
PSU Timings: T3 (20% / 100%)	124.0ms	124.0ms
12V OCP (30.8°C / 41.7°C)	90.00A (127.12%), 11.839V	90.20A (127.40%), 11.844V
5V OCP (30.8°C / 41.7°C)	28.3A (141.50%), 4.997V	27.6A (138.00%), 4.995V
3.3V OCP (30.8°C / 41.7°C)	28.5A (142.50%), 3.289V	27.6A (138.00%), 3.288V
5VSB OCP (30.8°C / 41.7°C)	5.4A (180.00%), 4.995V	5.2A (173.33%), 4.99V
OPP (31.05°C / 42.25°C)	123.85%	123.85%

□□□□ & PG□□

Hold-Up Time (ms)	18
AC Loss to PWR_OK Hold Up Time (ms)	15
PWR_OK Inactive to DC Loss Delay (ms)	3

Tables

115V


Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	115.07 V	115.03 V	113.85 V	115.11 V	116.15 V	PASS
Mains Frequency:	60.00 Hz	59.95 Hz	59.40 Hz	60.01 Hz	60.60 Hz	PASS
Mains Voltage CF:	1.416	1.415	1.340	1.418	1.490	PASS
Mains Voltage THD:	0.13 %	0.09 %	N/A	0.18 %	2.00 %	PASS
Real Power:	0.061 W	0.019 W	N/A	0.099 W	N/A	N/A
Apparent Power:	7.049 W	6.938 W	N/A	7.141 W	N/A	N/A
Power Factor:	0.010	N/A	N/A	N/A	N/A	N/A

230V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	231.01 V	230.93 V	227.70 V	231.08 V	232.30 V	PASS
Mains Frequency:	50.00 Hz	49.99 Hz	49.50 Hz	50.01 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.417	1.416	1.340	1.419	1.490	PASS
Mains Voltage THD:	0.17 %	0.14 %	N/A	0.24 %	2.00 %	PASS
Real Power:	0.137 W	0.097 W	N/A	0.199 W	N/A	N/A
Apparent Power:	23.973 W	23.715 W	N/A	24.233 W	N/A	N/A
Power Factor:	0.005	N/A	N/A	N/A	N/A	N/A

□□□□□□


115V



□□

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


230V



This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations

□□□□□


115V



□□

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

230V



The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Noise under high ambient temperature (indicative)

115V

Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	678 RPM · 16.3 dB(A) · 30.8 °C	689 RPM · 17.2 dB(A) · 40.1 °C	**+0.9 dB(A)**
20%	679 RPM · 16.3 dB(A) · 30.6 °C	688 RPM · 17.1 dB(A) · 40.5 °C	**+0.8 dB(A)**
50%	675 RPM · 16.3 dB(A) · 30.9 °C	1033 RPM · 30.3 dB(A) · 42.2 °C	**+14.0 dB(A)**
100%	1299 RPM · 36.8 dB(A) · 30.7 °C	1526 RPM · 41.2 dB(A) · 45.2 °C	**+4.4 dB(A)**

230V


Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	678 RPM · 16.3 dB(A) · 30.2 °C	690 RPM · 17.2 dB(A) · 40.0 °C	**+0.9 dB(A)**
20%	678 RPM · 16.3 dB(A) · 30.2 °C	690 RPM · 17.2 dB(A) · 40.5 °C	**+0.9 dB(A)**
50%	675 RPM · 16.3 dB(A) · 30.2 °C	1027 RPM · 30.2 dB(A) · 42.2 °C	**+13.9 dB(A)**
100%	1289 RPM · 36.5 dB(A) · 30.1 °C	1529 RPM · 41.3 dB(A) · 45.7 °C	**+4.8 dB(A)**

INFO

Fan speed, noise and the measured intake temperature at 10, 20, 50 and 100 % load, from the two load regulation tests: at normal ambient (about 30-32 °C) and at high ambient (about 40-47 °C). These are stabilized readings at fixed loads, not averages over the certification sweep, so they are indicative of how the fan behaves when it is hot. "<6.0" is the floor of our sound meter, with the fan stopped; with the fan stopped, the intake sensor can read higher than the chamber air.


Informational. Not part of the ETA or LAMBDA rating.

Indicative Performance



The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5Vsb□□□□



□□

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

□□□□ □□ 5Vsb □□ (ErP Lot3/6 & CEC)

115V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.231W	71.377%	0.046
	5.122V	0.324W		114.93V
2	**0.09A**	0.461W	78.211%	0.081
	5.121V	0.589W		114.93V
3	**0.55A**	2.811W	84.548%	0.311
	5.111V	3.325W		114.92V
4	**1A**	5.101W	84.63%	0.398
	5.101V	6.028W		114.91V
5	**1.5A**	7.635W	84.736%	0.436
	5.089V	9.011W		114.91V
6	**3A**	15.165W	83.472%	0.492
	5.055V	18.168W		114.91V

230V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.231W	64.868%	0.015
	5.121V	0.357W		229.9V
2	**0.09A**	0.461W	73.558%	0.026
	5.121V	0.626W		229.89V
3	**0.55A**	2.811W	83.282%	0.131
	5.11V	3.376W		229.88V
4	**1A**	5.101W	84.24%	0.21
	5.1V	6.056W		229.88V
5	**1.5A**	7.635W	84.683%	0.272
	5.089V	9.017W		229.88V
6	**3A**	15.165W	84.054%	0.364
	5.055V	18.042W		229.88V

Protection Features

OCP (Normal @ 30.8°C)	12V: 90.00A (127.12%), 11.839V 5V: 28.3A (141.50%), 4.997V 3.3V: 28.5A (142.50%), 3.289V 5VSB: 5.4A (180.00%), 4.995V
OCP (Hot @ 41.7°C)	12V: 90.20A (127.40%), 11.844V 5V: 27.6A (138.00%), 4.995V 3.3V: 27.6A (138.00%), 3.288V 5VSB: 5.2A (173.33%), 4.99V
OPP (Normal @ 31.1°C)	1052.70W (123.85%)
OPP (Hot @ 42.3°C)	1052.75W (123.85%)
OTP	✓ (155°C @ Heat Sink)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓ -12V to Earth: ✓
PWR_OK	Proper Operation
NLO	✓
Fan Failure Protection	✗
SIP	Surge: MOV Inrush: NTC & Bypass Relay

Supplementary Tests (For Reference)

10-110%□□□□

115V

□□	**12V**	**5V**	**3.3V**	**5VSB**	**DC/AC (□)**	□□	□□□□ **(RPM)**	□□□□□□□ **(dB[A])**	□□ **(□□ /□□)**	**PF/AC □□**
10%	**5.268A**	**1.98A**	**1.991A**	**0.983A**	85.006	83.579%	689	17.2	40.14°C	0.974
	12.036V	5.05V	3.315V	5.088V	101.71				39.75°C	114.87V

20%	**11.568A**	**2.973A**	**2.988A**	**1.182A**	169.949	89.575%	688	17.1	40.52°C	0.986
	12.020V	5.046V	3.313V	5.075V	189.746				40.5°C	114.86V
30%	**18.265A**	**3.47A**	**3.488A**	**1.383A**	254.956	90.861%	689	17.2	41.47°C	0.997
	11.985V	5.044V	3.311V	5.062V	280.592				41.3°C	114.82V
40%	**24.972A**	**3.968A**	**3.989A**	**1.585A**	340.049	90.739%	846	23.9	41.75°C	0.997
	11.967V	5.041V	3.31V	5.049V	374.753				41.87°C	114.8V
50%	**31.330A**	**4.963A**	**4.989A**	**1.787A**	424.886	90.321%	1033	30.3	42.19°C	0.998
	11.950V	5.037V	3.307V	5.036V	470.437				41.94°C	114.76V
60%	**37.678A**	**5.961A**	**5.992A**	**1.991A**	509.395	89.823%	1208	34.9	42.74°C	0.998
	11.933V	5.033V	3.305V	5.023V	567.157				42.12°C	114.73V
70%	**44.112A**	**6.96A**	**6.995A**	**2.196A**	594.719	89.197%	1340	37.8	43.04°C	0.998
	11.915V	5.029V	3.303V	5.009V	666.737				42.39°C	114.7V
80%	**50.563A**	**7.958A**	**7.999A**	**2.301A**	679.538	88.465%	1469	40.1	43.59°C	0.998
	11.898V	5.025V	3.3V	4.998V	768.198				43.13°C	114.66V
90%	**57.434A**	**8.46A**	**8.488A**	**2.406A**	764.935	87.774%	1525	41.2	44.57°C	0.999
	11.882V	5.023V	3.299V	4.987V	871.482				44.31°C	114.63V
100%	**64.054A**	**8.963A**	**9.01A**	**3.022A**	849.752	86.998%	1526	41.2	45.16°C	0.998
	11.866V	5.02V	3.296V	4.963V	976.818				45.19°C	114.59V
110%	**70.557A**	**9.967A**	**10.111A**	**3.029A**	934.349	86.086%	1526	41.2	46.3°C	0.996
	11.850V	5.016V	3.294V	4.953V	1085.314				46.49°C	114.56V
CL1	**0.117A**	**14.389A**	**14.459A**	**0A**	121.294	80.401%	1138	33	40.7°C	0.985
	12.028V	5.017V	3.299V	5.09V	150.867				45.82°C	114.86V
CL2	**0.115A**	**19.941A**	**0A**	**0A**	101.348	79.158%	945	27.5	40.53°C	0.978
	12.034V	5.013V	3.311V	5.1V	128.027				44.5°C	114.87V
CL3	**0.115A**	**0A**	**20.017A**	**0A**	67.398	73.419%	829	23.2	41.12°C	0.969
	12.035V	5.046V	3.298V	5.099V	91.8				44.58°C	114.88V
CL4	**71.595A**	**0A**	**0A**	**0A**	849.524	87.71%	1528	41.3	45.85°C	0.999
	11.866V	5.046V	3.307V	5.044V	968.546				56.39°C	114.6V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
10%	**5.268A**	**1.98A**	**1.991A**	**0.983A**	85.003	84.171%	690	17.2	40.03°C	0.851
	12.036V	5.05V	3.315V	5.088V	100.988				42.46°C	229.87V
20%	**11.567A**	**2.973A**	**2.988A**	**1.182A**	169.946	90.303%	690	17.2	40.51°C	0.928
	12.021V	5.046V	3.313V	5.075V	188.195				43.32°C	229.86V
30%	**18.263A**	**3.47A**	**3.488A**	**1.383A**	254.95	91.949%	689	17.2	41.44°C	0.957
	11.985V	5.043V	3.311V	5.063V	277.274				44.29°C	229.85V
40%	**24.971A**	**3.968A**	**3.989A**	**1.584A**	340.043	92.493%	795	21.7	41.56°C	0.971
	11.967V	5.041V	3.31V	5.05V	367.61				45.52°C	229.83V
50%	**31.332A**	**4.964A**	**4.99A**	**1.787A**	424.908	92.257%	1027	30.2	42.21°C	0.98
	11.950V	5.037V	3.307V	5.036V	460.62				46.45°C	229.82V
60%	**37.683A**	**5.962A**	**5.992A**	**1.991A**	509.454	91.986%	1211	34.9	42.92°C	0.987
	11.932V	5.033V	3.305V	5.023V	553.943				47.34°C	229.8V
70%	**44.118A**	**6.962A**	**6.996A**	**2.196A**	594.799	91.511%	1364	38.4	43.42°C	0.99
	11.915V	5.029V	3.302V	5.009V	649.95				47.86°C	229.79V
80%	**50.576A**	**7.96A**	**8.001A**	**2.302A**	679.641	91.123%	1475	40.3	43.68°C	0.993
	11.898V	5.024V	3.3V	4.997V	745.891				48.12°C	229.77V
90%	**57.447A**	**8.462A**	**8.491A**	**2.407A**	765.029	90.741%	1529	41.3	44.36°C	0.996
	11.881V	5.022V	3.298V	4.986V	843.139				49.23°C	229.75V
100%	**64.060A**	**8.964A**	**9.012A**	**3.022A**	849.807	90.236%	1529	41.3	45.69°C	0.997
	11.866V	5.019V	3.296V	4.963V	941.708				51.49°C	229.73V
110%	**70.561A**	**9.968A**	**10.112A**	**3.029A**	934.378	89.619%	1528	41.3	46.4°C	0.998
	11.849V	5.015V	3.293V	4.953V	1042.649				53.4°C	229.72V
CL1	**0.117A**	**14.39A**	**14.46A**	**0A**	121.296	81.15%	1187	34.2	41.29°C	0.91
	12.028V	5.016V	3.299V	5.09V	149.466				44.57°C	229.86V
CL2	**0.115A**	**19.942A**	**0A**	**0A**	101.349	79.811%	967	28	41.6°C	0.886
	12.034V	5.012V	3.311V	5.099V	126.994				43.54°C	229.87V
CL3	**0.115A**	**0A**	**20.019A**	**0A**	67.399	74.035%	843	23.8	40.78°C	0.826
	12.035V	5.045V	3.297V	5.099V	91.056				42.76°C	229.87V

CL4	**71.607A**	**0A**	**0A**	**0A**	849.539	90.942%	1535	41.4	45.77°C	0.997
	11.864V	5.046V	3.307V	5.045V	934.225				48.87°C	229.74V

The results above are not used in the certification process

20-80□□□□□

115V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
20W	**1.236A**	**0.495A**	**0.497A**	**0.196A**	20.008	72.822%	679	16.3	36.65°C	0.851
	12.017V	5.055V	3.318V	5.113V	27.481				36.77°C	114.9V
40W	**2.716A**	**0.693A**	**0.696A**	**0.294A**	40.004	73.828%	685	16.9	37.04°C	0.941
	12.040V	5.054V	3.317V	5.109V	54.192				37.01°C	114.89V
60W	**4.198A**	**0.891A**	**0.895A**	**0.392A**	60.002	80.511%	686	16.9	38.13°C	0.961
	12.039V	5.053V	3.317V	5.105V	74.533				38.16°C	114.88V
80W	**5.676A**	**1.089A**	**1.095A**	**0.49A**	79.953	83.287%	687	17	39.39°C	0.971
	12.036V	5.052V	3.317V	5.1V	96.009				38.84°C	114.88V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
20W	**1.236A**	**0.495A**	**0.497A**	**0.196A**	20.004	74.217%	679	16.3	36.1°C	0.504
	12.014V	5.054V	3.318V	5.114V	26.957				37.76°C	229.88V
40W	**2.715A**	**0.693A**	**0.696A**	**0.294A**	40.001	74.263%	686	16.9	37.73°C	0.692
	12.041V	5.053V	3.317V	5.109V	53.868				39.13°C	229.88V
60W	**4.198A**	**0.891A**	**0.895A**	**0.392A**	59.999	81.037%	687	17	38.02°C	0.781
	12.039V	5.053V	3.317V	5.105V	74.048				39.99°C	229.87V
80W	**5.676A**	**1.089A**	**1.094A**	**0.49A**	79.949	83.958%	688	17.1	39.08°C	0.838
	12.036V	5.052V	3.317V	5.101V	95.229				40.66°C	229.87V

The results above are not used in the certification process

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	14.4 mV	12.8 mV	14.1 mV	13.5 mV	Pass
20% Load	17.9 mV	14.3 mV	14.4 mV	14.1 mV	Pass
30% Load	15.4 mV	14.4 mV	16.2 mV	14.9 mV	Pass
40% Load	14.4 mV	14.2 mV	14.5 mV	14.0 mV	Pass
50% Load	14.3 mV	20.0 mV	25.6 mV	14.1 mV	Pass
60% Load	14.3 mV	15.2 mV	16.5 mV	15.8 mV	Pass
70% Load	14.4 mV	15.3 mV	17.0 mV	18.0 mV	Pass
80% Load	14.1 mV	17.2 mV	19.2 mV	14.9 mV	Pass
90% Load	16.3 mV	17.6 mV	18.3 mV	15.8 mV	Pass
100% Load	21.2 mV	19.2 mV	20.6 mV	17.1 mV	Pass
110% Load	22.8 mV	19.0 mV	21.1 mV	17.1 mV	Pass
Crossload 1	13.6 mV	15.6 mV	17.8 mV	13.9 mV	Pass
Crossload 2	13.5 mV	21.6 mV	16.4 mV	13.7 mV	Pass
Crossload 3	13.8 mV	13.4 mV	17.3 mV	14.2 mV	Pass
Crossload 4	19.6 mV	18.0 mV	19.2 mV	19.4 mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	14.1 mV	12.7 mV	13.3 mV	12.7 mV	Pass
20% Load	17.2 mV	14.0 mV	14.8 mV	13.5 mV	Pass
30% Load	13.5 mV	14.9 mV	14.4 mV	13.1 mV	Pass
40% Load	13.2 mV	13.9 mV	15.1 mV	13.1 mV	Pass
50% Load	13.4 mV	16.5 mV	28.8 mV	14.1 mV	Pass
60% Load	13.8 mV	15.4 mV	15.5 mV	15.0 mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
70% Load	14.3 mV	15.7 mV	16.6 mV	14.0 mV	Pass
80% Load	15.0 mV	16.1 mV	18.5 mV	14.3 mV	Pass
90% Load	14.6 mV	16.5 mV	18.6 mV	14.9 mV	Pass
100% Load	20.3 mV	19.7 mV	20.1 mV	16.2 mV	Pass
110% Load	20.5 mV	18.6 mV	21.3 mV	16.1 mV	Pass
Crossload 1	13.7 mV	15.4 mV	19.3 mV	14.0 mV	Pass
Crossload 2	14.1 mV	19.9 mV	15.8 mV	14.0 mV	Pass
Crossload 3	14.1 mV	13.6 mV	18.1 mV	13.8 mV	Pass
Crossload 4	19.8 mV	15.9 mV	19.5 mV	17.4 mV	Pass

The results above are not used in the certification process

Cougar GLE 850W



Top side



Power specifications label