ASRock Phantom Gaming PG-1300G (ATX v3.1)

S4311030004

Lab ID AR13002621

Certification ID 252621

Test Result Report ID: 24PS2621A

Certificate Issue Date: Oct 30, 2024

Scheme: ETA-EMI PSU

115V 230V

Scheme: LAMBDA PSU

115V 230V

Outside Validation Scope

General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	ASRock
Model	Phantom Gaming PG-1300G (ATX v3.1)
OEM/ODM	FSP
Serial Number	S4311030004
Product Specifications	
Manufacturer-Provided Information	
□□□□ (Vrms)	100-240
□□□□ (Arms)	8-15

□□□□ (Hz)	50-60
□□□□ (W)	1300
Operating Temperature (Continuous Full Load) (°C)	
□□	ATX12V
□□□□	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
□□	135mm Hydro Dynamic Bearing Fan (PLA13525S12M)
□□□□□	✓ (selectable)
Cybenetics Testing Information	
Lab ID	AR13002621
Date of receipt	Oct 4, 2024
Testing Date	Oct 25, 2024
Report Issued Date	Oct 30, 2024
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

□□□□ (Non-accredited measurements)

□□□□				
□□	□□□□	□□□□□	**Gauge**	In Cable Capacitors
ATX □□ 24 pin (600mm)	1	1	16-22AWG	□
4+4 pin EPS 12V □□ (650mm)	2	2	16AWG	□
6+2pin PCIe□□ (675mm)	4	4	16-18AWG	□
6+2pin PCIe□□ (675mm+75mm)	2	4	16-18AWG	□
12+4 pin PCIe (710mm) (600W)	1	1	16-24AWG	□
SATA□□ (450mm+100mm+100mm)	3	9	18AWG	□

4-pin Molex (450mm+100mm+100mm)	1	3	18AWG	□

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✗

□□□□

□		3.3V	5V	12V	5VSB	-12V
□□□□	□□	25	25	108.3	3	0.3
	□	130		1300	15	3.6
□□□□□ (W)		1300				

Test Results

Temperature & Compliance Info

□□□□ (°C /°F)	28-32 / 82.4-89.6
□□ ErP Lot3/6□□	✓
□□ (EU) No 617/2013□□	✓
ALPM (Alternative Low Power Mode) compatible	✓
ATX v3.1 PSU Power Excursion	✓

Performance Summary

115V

Accredited	
□□□□ (>1450 load combinations)	90.106%
Average Noise Output (>1450 Load Combinations)	23.39dBA
PF□□□ (>1450 Load Combinations)	0.995
Efficiency With 10W (≤500W) or 2% (>500W) Load	65.665%
□□□□□□	0.0753W
Non-Accredited	
12V Ripple (Full Load)	24.75mV
5V Ripple (Full Load)	16.32mV
3.3V Ripple (Full Load)	14.43mV
5VSB Ripple (Full Load)	18.14mV
12V Load Regulation	0.71%
5V Load Regulation	0.66%
3.3V Load Regulation	1.21%
5VSB Load Regulation	2.41%
Inrush Current	46.880A

230V

Accredited	
□□□□ (>1450 load combinations)	92.090%
Average Noise Output (>1450 Load Combinations)	23.20dBA
PF□□□ (>1450 Load Combinations)	0.973
Efficiency With 10W (≤500W) or 2% (>500W) Load	67.765%
□□□□□□	0.1283W
Non-Accredited	
12V Ripple (Full Load)	28.98mV
5V Ripple (Full Load)	20.36mV
3.3V Ripple (Full Load)	20.70mV

5VSB Ripple (Full Load)		19.15mV
12V Load Regulation		0.64%
5V Load Regulation		0.60%
3.3V Load Regulation		1.06%
5VSB Load Regulation		2.35%
Inrush Current		81.170A
12V Transient Response (200%)		11.38V
5V Transient Response (200%)		4.934V
3.3V Transient Response (200%)		3.192V
5VSB Transient Response (200%)		4.865V
□□□□ & PG□□		24.20ms
AC Loss to PWR_OK Hold Up Time		22.20ms
PWR_OK Inactive to DC Loss Delay		2.00ms
PSU Timings: T1 (20% / 100%)	48.0ms	51.0ms
PSU Timings: T3 (20% / 100%)	128.0ms	125.0ms
12V OCP (28.1°C / 43.0°C)	131.80A (121.70%), 12.032V	127.20A (117.45%), 12.052V
5V OCP (28.1°C / 43.0°C)	27.8A (111.20%), 5.019V	26.3A (105.20%), 5.024V
3.3V OCP (28.1°C / 43.0°C)	30A (120.00%), 3.314V	27.7A (110.80%), 3.325V
5VSB OCP (28.1°C / 43.0°C)	4.2A (140.00%), 4.982V	4.1A (136.67%), 4.983V
OPP (28.42°C / 43.36°C)	125.85%	123.21%

□□□□ & PG□□

Hold-Up Time (ms)	24.2
AC Loss to PWR_OK Hold Up Time (ms)	22.2
PWR_OK Inactive to DC Loss Delay (ms)	2

Tables

115V


Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	115.06 V	115.03 V	113.85 V	115.10 V	116.15 V	PASS
Mains Frequency:	60.00 Hz	59.99 Hz	59.40 Hz	60.01 Hz	60.60 Hz	PASS
Mains Voltage CF:	1.416	1.415	1.340	1.418	1.490	PASS
Mains Voltage THD:	0.13 %	0.09 %	N/A	0.18 %	2.00 %	PASS
Real Power:	0.075 W	0.053 W	N/A	0.109 W	N/A	N/A
Apparent Power:	10.077 W	9.969 W	N/A	10.177 W	N/A	N/A
Power Factor:	0.006	N/A	N/A	N/A	N/A	N/A

230V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	231.02 V	230.92 V	227.70 V	231.08 V	232.30 V	PASS
Mains Frequency:	50.00 Hz	49.99 Hz	49.50 Hz	50.01 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.417	1.416	1.340	1.418	1.490	PASS
Mains Voltage THD:	0.17 %	0.15 %	N/A	0.25 %	2.00 %	PASS
Real Power:	0.128 W	0.080 W	N/A	0.230 W	N/A	N/A
Apparent Power:	34.271 W	33.986 W	N/A	34.598 W	N/A	N/A
Power Factor:	0.004	N/A	N/A	N/A	N/A	N/A

□□□□□□


115V



□□

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


230V



This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations

□□□□□


115V



□□

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

230V



The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Noise under high ambient temperature (indicative)

115V

Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	0 RPM · <6.0 dB(A) · 34.7 °C	0 RPM · <6.0 dB(A) · 51.5 °C	fan off in both
20%	0 RPM · <6.0 dB(A) · 41.6 °C	0 RPM · <6.0 dB(A) · 53.4 °C	fan off in both
50%	473 RPM · 11.1 dB(A) · 30.3 °C	957 RPM · 24.6 dB(A) · 42.2 °C	**+13.5 dB(A)**
100%	1229 RPM · 31.1 dB(A) · 30.8 °C	1593 RPM · 39.1 dB(A) · 45.1 °C	**+8.0 dB(A)**

230V


Load	Normal ambient fan · noise · intake	High ambient fan · noise · intake	Noise change
10%	0 RPM · <6.0 dB(A) · 34.9 °C	0 RPM · <6.0 dB(A) · 50.7 °C	fan off in both
20%	0 RPM · <6.0 dB(A) · 39.2 °C	0 RPM · <6.0 dB(A) · 51.9 °C	fan off in both
50%	472 RPM · 11.1 dB(A) · 30.8 °C	883 RPM · 23.3 dB(A) · 42.3 °C	**+12.2 dB(A)**
100%	0 RPM · <6.0 dB(A) · 30.8 °C	1576 RPM · 38.6 dB(A) · 45.1 °C	fan starts (<6.0 → 38.6)

INFO

Fan speed, noise and the measured intake temperature at 10, 20, 50 and 100 % load, from the two load regulation tests: at normal ambient (about 30-32 °C) and at high ambient (about 40-47 °C). These are stabilized readings at fixed loads, not averages over the certification sweep, so they are indicative of how the fan behaves when it is hot. "<6.0" is the floor of our sound meter, with the fan stopped; with the fan stopped, the intake sensor can read higher than the chamber air.


Informational. Not part of the ETA or LAMBDA rating.

Indicative Performance



The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5Vsb□□□□



□□

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

□□□□ □□ 5Vsb □□ (ErP Lot3/6 & CEC)

115V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.227W	61.973%	0.036
	5.05V	0.367W		114.88V
2	**0.09A**	0.455W	69.537%	0.064
	5.049V	0.654W		114.88V
3	**0.55A**	2.773W	81.351%	0.263
	5.042V	3.409W		114.87V
4	**1A**	5.035W	81.867%	0.346
	5.035V	6.15W		114.87V
5	**1.5A**	7.542W	81.379%	0.408
	5.027V	9.268W		114.87V
6	**3.001A**	15.012W	78.946%	0.488
	5.003V	19.015W		114.87V

230V

□□ #	5VSB	DC/AC (□)	□□	PF/AC □□
1	**0.045A**	0.227W	54.334%	0.012
	5.05V	0.418W		229.94V
2	**0.09A**	0.455W	64.929%	0.02
	5.049V	0.701W		229.94V
3	**0.55A**	2.773W	79.223%	0.098
	5.042V	3.501W		229.94V
4	**1A**	5.036W	80.413%	0.165
	5.035V	6.263W		229.94V
5	**1.5A**	7.542W	80.863%	0.203
	5.027V	9.327W		229.94V
6	**3.001A**	15.012W	79.945%	0.317
	5.003V	18.779W		229.94V

Protection Features

OCP (Normal @ 28.1°C)	12V: 131.80A (121.70%), 12.032V 5V: 27.8A (111.20%), 5.019V 3.3V: 30A (120.00%), 3.314V 5VSB: 4.2A (140.00%), 4.982V
OCP (Hot @ 43.0°C)	12V: 127.20A (117.45%), 12.052V 5V: 26.3A (105.20%), 5.024V 3.3V: 27.7A (110.80%), 3.325V 5VSB: 4.1A (136.67%), 4.983V
OPP (Normal @ 28.4°C)	1636.05W (125.85%)
OPP (Hot @ 43.4°C)	1601.67W (123.21%)
OTP	✓ (150°C @ Heat Sink)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓ -12V to Earth: ✓
PWR_OK	Proper Operation
NLO	✓
Fan Failure Protection	✗
SIP	Surge: MOV Inrush: NTC & Bypass Relay

Supplementary Tests (For Reference)

10-110%□□□□

115V

□□	**12V**	**5V**	**3.3V**	**5VSB**	**DC/AC (□)**	□□	□□□□ **(RPM)**	□□□□□□□ **(dB[A])**	□□ **(□□ /□□)**	**PF/AC □□**
10%	**8.946A**	**1.976A**	**1.978A**	**0.995A**	130.015	87.369%	0	<6.0	51.53°C	0.987
	12.118V	5.062V	3.337V	5.028V	148.809				40.21°C	114.83V

20%	**18.916A**	**2.966A**	**2.97A**	**1.196A**	259.987	91.062%	0	<6.0	53.44°C	0.995
	12.110V	5.059V	3.333V	5.017V	285.503				40.83°C	114.79V
30%	**29.219A**	**3.462A**	**3.469A**	**1.398A**	389.697	92.087%	0	<6.0	54.59°C	0.997
	12.103V	5.056V	3.33V	5.006V	423.182				41.21°C	114.75V
40%	**39.550A**	**3.958A**	**3.968A**	**1.602A**	519.658	92.204%	0	<6.0	57.29°C	0.997
	12.097V	5.054V	3.327V	4.996V	563.601				41.98°C	114.7V
50%	**49.585A**	**4.952A**	**4.968A**	**1.806A**	649.797	91.867%	957	24.6	42.15°C	0.997
	12.086V	5.049V	3.322V	4.985V	707.326				54.47°C	114.65V
60%	**59.637A**	**5.948A**	**5.971A**	**2A**	779.857	91.6%	1003	26.5	42.69°C	0.997
	12.075V	5.045V	3.316V	4.975V	851.38				56.34°C	114.61V
70%	**69.698A**	**6.945A**	**6.975A**	**2.217A**	909.98	91.146%	1127	29.3	43.28°C	0.997
	12.065V	5.041V	3.312V	4.963V	998.37				58.03°C	114.56V
80%	**79.772A**	**7.941A**	**7.98A**	**2.322A**	1039.571	90.586%	1277	33.8	43.68°C	0.997
	12.056V	5.038V	3.308V	4.954V	1147.614				60.16°C	114.51V
90%	**90.253A**	**8.442A**	**8.474A**	**2.427A**	1169.797	89.964%	1434	36.3	44.23°C	0.996
	12.047V	5.035V	3.304V	4.945V	1300.303				62.04°C	114.46V
100%	**100.487A**	**8.944A**	**8.999A**	**3.045A**	1299.395	89.242%	1593	39.1	45.09°C	0.996
	12.038V	5.032V	3.3V	4.928V	1456.033				65.09°C	114.4V
110%	**110.669A**	**9.945A**	**10.102A**	**3.05A**	1429.586	88.421%	1762	40.8	46.31°C	0.996
	12.029V	5.028V	3.296V	4.92V	1616.789				68.18°C	114.35V
CL1	**0.116A**	**15.542A**	**15.482A**	**0A**	131.308	82.325%	0	<6.0	51.67°C	0.99
	12.120V	5.038V	3.333V	5.036V	159.5				42.85°C	114.83V
CL2	**0.114A**	**24.856A**	**0A**	**0A**	126.263	80.221%	0	<6.0	52.03°C	0.99
	12.122V	5.024V	3.346V	5.041V	157.38				40.29°C	114.84V
CL3	**0.114A**	**0A**	**24.78A**	**0A**	83.885	74.966%	0	<6.0	53.29°C	0.98
	12.118V	5.064V	3.329V	5.037V	111.893				40.12°C	114.85V
CL4	**107.928A**	**0A**	**0A**	**0A**	1299.937	89.885%	1589	39.1	45.38°C	0.996
	12.044V	5.051V	3.31V	4.983V	1446.229				69.17°C	114.41V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
10%	**8.946A**	**1.976A**	**1.978A**	**0.994A**	129.987	88.59%	0	<6.0	50.7°C	0.907
	12.116V	5.062V	3.337V	5.028V	146.728				40.01°C	229.93V
20%	**18.916A**	**2.965A**	**2.97A**	**1.196A**	259.944	92.441%	0	<6.0	51.88°C	0.965
	12.109V	5.059V	3.333V	5.018V	281.199				40.84°C	229.91V
30%	**29.211A**	**3.461A**	**3.468A**	**1.398A**	389.551	93.611%	0	<6.0	52.86°C	0.981
	12.102V	5.057V	3.33V	5.008V	416.139				41.25°C	229.89V
40%	**39.544A**	**3.957A**	**3.967A**	**1.601A**	519.516	93.875%	0	<6.0	54.72°C	0.988
	12.096V	5.054V	3.327V	4.998V	553.411				41.96°C	229.87V
50%	**49.573A**	**4.951A**	**4.967A**	**1.805A**	649.654	93.813%	883	23.3	42.25°C	0.99
	12.086V	5.05V	3.322V	4.987V	692.5				52.86°C	229.85V
60%	**59.623A**	**5.946A**	**5.969A**	**2A**	779.726	93.763%	961	25	42.61°C	0.99
	12.076V	5.046V	3.317V	4.977V	831.593				53.37°C	229.83V
70%	**69.682A**	**6.942A**	**6.973A**	**2.215A**	909.873	93.57%	1078	29	43.09°C	0.989
	12.066V	5.042V	3.313V	4.966V	972.405				53.89°C	229.81V
80%	**79.754A**	**7.938A**	**7.977A**	**2.32A**	1039.458	93.294%	1243	31.6	43.84°C	0.989
	12.057V	5.039V	3.309V	4.957V	1114.171				54.81°C	229.79V
90%	**90.236A**	**8.439A**	**8.47A**	**2.425A**	1169.707	92.991%	1414	35.6	44.44°C	0.989
	12.048V	5.036V	3.305V	4.948V	1257.864				56.22°C	229.77V
100%	**100.461A**	**8.94A**	**8.994A**	**3.042A**	1299.34	92.638%	1576	38.6	45.14°C	0.989
	12.041V	5.033V	3.302V	4.931V	1402.609				57.07°C	229.74V
110%	**110.647A**	**9.941A**	**10.097A**	**3.047A**	1429.543	92.219%	1727	39.9	46.29°C	0.988
	12.031V	5.03V	3.298V	4.923V	1550.171				58.21°C	229.72V
CL1	**0.115A**	**15.536A**	**15.486A**	**0A**	131.292	83.506%	0	<6.0	53.86°C	0.917
	12.119V	5.04V	3.332V	5.037V	157.224				40.81°C	229.94V
CL2	**0.114A**	**24.842A**	**0A**	**0A**	126.258	81.271%	0	<6.0	54.03°C	0.916
	12.124V	5.026V	3.346V	5.042V	155.354				40.19°C	229.93V
CL3	**0.114A**	**0A**	**24.769A**	**0A**	83.881	75.557%	0	<6.0	54.36°C	0.864
	12.119V	5.065V	3.331V	5.038V	111.027				40.71°C	229.94V

CL4	**107.899A**	**0A**	**0A**	**0A**	1299.899	93.116%	1600	39	45.6°C	0.989
	12.047V	5.052V	3.312V	4.985V	1395.992				56.74°C	229.74V

The results above are not used in the certification process

20-80□□□□□

115V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
20W	**1.226A**	**0.494A**	**0.494A**	**0.198A**	20.01	59.755%	0	<6.0	45.78°C	0.877
	12.123V	5.065V	3.34V	5.047V	33.487				36.15°C	114.87V
40W	**2.697A**	**0.691A**	**0.692A**	**0.297A**	40.008	73.776%	0	<6.0	47.57°C	0.939
	12.123V	5.064V	3.339V	5.044V	54.23				37.23°C	114.86V
60W	**4.168A**	**0.889A**	**0.889A**	**0.397A**	60.007	79.841%	0	<6.0	48.92°C	0.962
	12.122V	5.064V	3.339V	5.041V	75.157				38.08°C	114.85V
80W	**5.637A**	**1.086A**	**1.087A**	**0.496A**	79.96	83.179%	0	<6.0	50.27°C	0.971
	12.121V	5.064V	3.339V	5.039V	96.131				39.36°C	114.85V

The results above are not used in the certification process

230V

□□	12V	5V	3.3V	5VSB	DC/AC (□)	□□	□□□□ (RPM)	□□□□□□□ (dB[A])	□□ (□□ /□□)	PF/AC □□
20W	**1.226A**	**0.494A**	**0.494A**	**0.198A**	20.004	60.277%	0	<6.0	42.44°C	0.498
	12.116V	5.063V	3.337V	5.047V	33.19				36.25°C	229.95V
40W	**2.698A**	**0.691A**	**0.692A**	**0.297A**	40.005	74.504%	0	<6.0	46°C	0.67
	12.116V	5.063V	3.337V	5.044V	53.698				37.13°C	229.94V
60W	**4.170A**	**0.889A**	**0.89A**	**0.397A**	60.002	80.732%	0	<6.0	48.34°C	0.772
	12.117V	5.063V	3.337V	5.041V	74.322				38.88°C	229.94V
80W	**5.638A**	**1.086A**	**1.088A**	**0.496A**	79.943	84.326%	0	<6.0	48.78°C	0.83
	12.117V	5.063V	3.337V	5.039V	94.803				39.13°C	229.93V

The results above are not used in the certification process

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	11.3 mV	11.6 mV	11.5 mV	9.3 mV	Pass
20% Load	12.8 mV	11.1 mV	11.1 mV	9.2 mV	Pass
30% Load	14.9 mV	12.0 mV	11.9 mV	10.3 mV	Pass
40% Load	19.9 mV	12.8 mV	12.0 mV	11.6 mV	Pass
50% Load	16.5 mV	14.5 mV	12.8 mV	12.5 mV	Pass
60% Load	15.9 mV	13.8 mV	11.4 mV	12.7 mV	Pass
70% Load	15.8 mV	12.7 mV	12.1 mV	14.0 mV	Pass
80% Load	15.8 mV	14.5 mV	12.3 mV	15.7 mV	Pass
90% Load	16.6 mV	13.3 mV	11.5 mV	15.6 mV	Pass
100% Load	24.8 mV	16.3 mV	14.4 mV	18.1 mV	Pass
110% Load	25.6 mV	19.2 mV	15.5 mV	21.8 mV	Pass
Crossload 1	14.4 mV	11.2 mV	13.0 mV	16.6 mV	Pass
Crossload 2	12.2 mV	19.6 mV	11.2 mV	10.2 mV	Pass
Crossload 3	11.1 mV	12.4 mV	13.5 mV	17.1 mV	Pass
Crossload 4	25.5 mV	14.4 mV	14.0 mV	26.1 mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	10.9 mV	10.8 mV	10.8 mV	8.6 mV	Pass
20% Load	12.4 mV	11.1 mV	11.9 mV	9.4 mV	Pass
30% Load	14.5 mV	11.6 mV	11.1 mV	9.4 mV	Pass
40% Load	21.0 mV	12.5 mV	11.6 mV	11.2 mV	Pass
50% Load	20.9 mV	12.9 mV	11.8 mV	11.9 mV	Pass
60% Load	17.5 mV	13.3 mV	12.0 mV	13.2 mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
70% Load	19.0 mV	14.4 mV	12.5 mV	13.6 mV	Pass
80% Load	20.6 mV	14.5 mV	13.7 mV	14.3 mV	Pass
90% Load	19.7 mV	14.3 mV	12.6 mV	14.7 mV	Pass
100% Load	29.0 mV	20.4 mV	20.7 mV	19.2 mV	Pass
110% Load	30.3 mV	22.4 mV	21.8 mV	20.0 mV	Pass
Crossload 1	18.0 mV	16.7 mV	17.6 mV	19.0 mV	Pass
Crossload 2	13.6 mV	17.5 mV	11.9 mV	15.9 mV	Pass
Crossload 3	12.4 mV	12.9 mV	14.7 mV	17.1 mV	Pass
Crossload 4	30.3 mV	22.7 mV	21.2 mV	25.0 mV	Pass

The results above are not used in the certification process

ASRock Phantom Gaming PG-1300G (ATX v3.1)



Top side



Power specifications label