



be quiet! Dark Power 14 1200W



Serial Number 021EUL52200001000

Lab ID BQ12002952

Certification ID 252952

Test Result Report ID: 25PS2952A

Certificate Issue Date: Sep 2, 2025



Outside Validation Scope

General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	be quiet!
Model	Dark Power 14 1200W
OEM/ODM	CWT
Serial Number	021EUL52200001000
Product Specifications	
Manufacturer-Provided Information	
Rated Voltage (Vrms)	100-240
Rated Current (Arms)	7-15

Rated Frequency (Hz)	50-60
Rated Power (W)	1200
Operating Temperature (Continuous Full Load) (°C)	
Type	ATX12V
Cable Design	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
Cooling	135mm Fluid Dynamic Bearing (BQ SIW4-13525-MF)
Semi-Passive Operation	✓ (selectable)
Cybenetics Testing Information	
Lab ID	BQ12002952
Date of receipt	Aug 22, 2025
Testing Date	Aug 28, 2025
Report Issued Date	Sep 2, 2025
Engineer Name	Georgios Theodoros Sarimpalas
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

Cables and Connectors(Non-accredited measurements)

Modular Cables				
Description	Cable Count	Connector Count (Total)	Gauge	Cable Type
ATX connector 20+4 pin (600mm)	1	1	16-18AWG	Tinned Copper
8 pin ATX12V (700mm)	1	1	16AWG	Tinned Copper
4+4 pin ATX12V (700mm)	1	1	16AWG	Tinned Copper
2x 6+2 pin PCIe (750mm)	4	4	18AWG	Tinned Copper
12+4 pin PCIe PCIe (600mm)	2	2	16-24AWG	Tinned Copper
SATA (600mm+155mm+155mm+155mm)	2	8	18AWG	Tinned Copper
SATA (600mm+155mm+155mm)	1	3	18AWG	Tinned Copper

SATA (605mm+155mm) / 4-pin Molex (+155mm+150mm)	1	2 / 2	18AWG	Tinned Copper
AC Power Cord (1380mm)	1	1	18AWG	-

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✗

Power Specifications

Rail		3.3V	5V	12V(1)	12V(2)	12V(3)	12V(4)	5VSB	-12V
Max. Power	Amps	25	24	33	33	45	45	3	0.5
	Watts	120		1200				15	6
Total Max. Power (W)		1200							

Parts Description

General Data	
Manufacturer (OEM)	CWT
PCB Type	Double-Sided
Primary Side	
Transient Filter	6x Y caps, 2x X caps, 2x CM chokes, 1x MOV
Inrush Protection	NTC Thermistor SCK-0510 (5 Ohm @ 25°C) & Relay
Rectifier MOSFETs	4x
APFC MOSFETs	3x Infineon IPA60R099P7 (650V, 20A @ 100°C, Rds(on): 0.099Ohm)
APFC Boost Diode	Infineon IDH16G65C6 (650V, 16A @ 135°C)
Bulk Cap(s)	2x Toshin Kogyo (420V, 680uF each or 1360uF combined, 2000h @ 105°C, LFW)
Main Switchers	4x Alpha & Omega AOTF29S50 (600V, 18A @ 100°C, Rds(on): 0.15Ohm)

APFC Controller	Champion CM6500UNX & Sync Power SPN5003 (reducing no load consumption)
Resonant Controller	Champion CM6901T2X
IC Driver	2x Novosense NSI6602BD
Topology	Primary side: Bridgeless PFC, Full-Bridge & LLC Resonant Converter Secondary side: [12V] Synchronous Rectification & [Minor Rails] DC-DC converters
Secondary Side	
+12V MOSFETs	8x Infineon BSC010N04LS (40V, 206A @ 100°C, Rds(on): 1.0mOhm)
5V & 3.3V	DC-DC Converters: 4x UBIQ Semi QN3107M6N (30V, 70A @ 100°C, Rds(on): 2.6mOhm) PWM Controller(s): UPI-Semi uP3861P
Filtering Capacitors	Electrolytic: 6x Nippon Chemi-con (@ 105°C, W) 3x Rubycon (4-10,000 @ 105°C, YXJ) Rubycon (3-6,000 @ 105°C, YXS) Rubycon (10,000 @ 105°C, YXM) Nichicon (4-10,000 @ 105°C, HE(M)) Polymer: 23x Nippon Chemi-con, 19x FPCAP
Supervisor IC	Weltrend WT7518 (OVP, UVP, OCP, PG)
MCU / Fan Controller	Nuvoton MS51FB9AE
Fan Model	BQ SIW4-13525-MF (135mm, 12V, 0.4A, Fluid Dynamic Bearing Fan)
5VSB Circuit	
Rectifier (High Side)	1x Dongke DK5V45R10V (45V, 10mOhm)
Standby PWM Controller	On-Bright OB2365T

Test Results

Temperature & Compliance Info

Temperature Range (°C /°F)	28-32 / 82.4-89.6
ErP Lot 3/6 Ready	✓
(EU) No 617/2013 Compliance	✓
ALPM (Alternative Low Power Mode) compatible	✓

ATX v3.1 PSU Power Excursion	✓
------------------------------	---

Performance Summary

115V

Accredited	
Average Efficiency (>1450 load combinations)	91.492%
Average Noise Output (>1450 Load Combinations)	15.78dBA
Average PF (>1450 Load Combinations)	0.991
Efficiency With 10W ($\leq$ 500W) or 2% (>500W) Load	74.258%
Standby Power Consumption	0.0900W
Non-Accredited	
12V Ripple (Full Load)	16.12mV
5V Ripple (Full Load)	14.23mV
3.3V Ripple (Full Load)	14.35mV
5VSB Ripple (Full Load)	15.10mV
12V Load Regulation	0.66%
5V Load Regulation	0.80%
3.3V Load Regulation	1.48%
5VSB Load Regulation	3.53%
Inrush Current	35.720A

230V

Accredited	
Average Efficiency (>1450 load combinations)	93.385%
Average Noise Output (>1450 Load Combinations)	14.79dBA
Average PF (>1450 Load Combinations)	0.964
Efficiency With 10W ($\leq$ 500W) or 2% (>500W) Load	75.306%
Standby Power Consumption	0.1400W
Non-Accredited	
12V Ripple (Full Load)	15.69mV

5V Ripple (Full Load)	12.63mV	
3.3V Ripple (Full Load)	12.82mV	
5VSB Ripple (Full Load)	13.81mV	
12V Load Regulation	0.64%	
5V Load Regulation	0.60%	
3.3V Load Regulation	1.57%	
5VSB Load Regulation	3.47%	
Inrush Current	67.550A	
12V Transient Response (200%)	11.32V	
5V Transient Response (200%)	4.918V	
3.3V Transient Response (200%)	3.153V	
5VSB Transient Response (200%)	4.919V	
Hold-Up Time & PWR_OK Signal	17.00ms	
AC Loss to PWR_OK Hold Up Time	15.00ms	
PWR_OK Inactive to DC Loss Delay	2.00ms	
PSU Timings: T1 (20% / 100%)	52.0ms	52.0ms
PSU Timings: T3 (20% / 100%)	127.0ms	127.0ms
OPP (31.10°C / 45.15°C)	128.92%	120.17%

Hold-Up Time & PWR_OK Signal

Hold-Up Time (ms)	17
AC Loss to PWR_OK Hold Up Time (ms)	15
PWR_OK Inactive to DC Loss Delay (ms)	2

Stromverbrauch im Ruhezustand

Tables

115V


Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	115.06 V	115.04 V	113.85 V	115.10 V	116.15 V	PASS
Mains Frequency:	60.00 Hz	60.00 Hz	59.40 Hz	60.01 Hz	60.60 Hz	PASS
Mains Voltage CF:	1.416	1.415	1.340	1.416	1.490	PASS
Mains Voltage THD:	0.13 %	0.10 %	N/A	0.15 %	2.00 %	PASS
Real Power:	0.090 W	0.074 W	N/A	0.107 W	N/A	N/A
Apparent Power:	9.976 W	9.962 W	N/A	10.017 W	N/A	N/A
Power Factor:	0.009	N/A	N/A	N/A	N/A	N/A

230V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	230.27 V	230.25 V	227.70 V	230.33 V	232.30 V	PASS
Mains Frequency:	50.00 Hz	50.00 Hz	49.50 Hz	50.00 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.416	1.415	1.340	1.416	1.490	PASS
Mains Voltage THD:	0.14 %	0.13 %	N/A	0.16 %	2.00 %	PASS
Real Power:	0.140 W	0.111 W	N/A	0.244 W	N/A	N/A
Apparent Power:	32.843 W	32.820 W	N/A	32.857 W	N/A	N/A
Power Factor:	0.004	N/A	N/A	N/A	N/A	N/A


Efficiency Graph

115V



INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations




INFO

This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


Noise Graph

115V



INFO


The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails




INFO

The PSU's noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Conducted Emissions EN 55032 & CISPR 32



NEUTRAL




PHASE

Indicative Performance

Efficiency under high ambient temperature

Efficiency: be quiet! Dark Power 14 1200W

Ambient: 36°C - 47°C (96.8°F - 116.6°F)




INFO

The PSU's efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5VSB Efficiency

5VSB Efficiency: be quiet! Dark Power 14 1200W

Ambient: 34°C - 36°C (93.2°F - 96.8°F)



INFO

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

5VSB Efficiency (ERP LOT 3/6 & CEC)

115V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.228W	61.896%	0.037
	5.068V	0.369W		115.08V
2	0.09A	0.456W	70.909%	0.064
	5.066V	0.644W		115.08V
3	0.55A	2.778W	82.675%	0.263
	5.052V	3.361W		115.08V
4	1A	5.038W	83.05%	0.363
	5.038V	6.066W		115.08V
5	1.5A	7.534W	83.675%	0.414
	5.023V	9.004W		115.08V
6	3A	14.928W	82.051%	0.483
	4.976V	18.194W		115.07V

230V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.045A	0.228W	51.615%	0.014
	5.067V	0.447W		230.28V
2	0.09A	0.456W	62.539%	0.022
	5.066V	0.73W		230.28V
3	0.55A	2.778W	79.749%	0.101
	5.052V	3.482W		230.27V
4	1A	5.038W	81.937%	0.167
	5.038V	6.151W		230.27V
5	1.5A	7.534W	82.6%	0.226
	5.022V	9.123W		230.27V
6	3A	14.928W	83.508%	0.328
	4.976V	17.876W		230.28V

Protection Features

OCP (Normal @ 27.1°C)	12V1: 42.60A (129.09%), 11.889V 12V2: 43.80A (132.73%), 11.773V 12V3: 63.847A (141.88%), 11.75V 12V4: 63.851A (141.89%), 11.744V 5V: 30.5A (127.08%), 4.958V 3.3V: 31.1A (124.40%), 3.195V 5VSB: 5A (166.67%), 4.933V
OCP (Hot @ 44.8°C)	12V1: 42.30A (128.18%), 11.911V 12V2: 43.40A (131.52%), 11.783V 12V3: 58.65A (130.78%), 11.779V 12V4: 58.852A (130.78%), 11.771V 5V: 30.6A (127.50%), 4.95V 3.3V: 30.198A (120.79%), 3.18V 5VSB: 4.9A (163.33%), 4.932V
OPP (Normal @ 31.1°C)	1547.07W (128.92%)
OPP (Hot @ 45.1°C)	1442.06W (120.17%)
OTP	✓ (120°C @ Heat Sink)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓ -12V to Earth: ✓
PWR_OK	Proper Operation
UVP (Full Load @ 90V)	✓
UVP (No Damage @ 80V)	✓
Conducted Emissions EN55032 & CISPR 32	✓
NLO	✓
Fan Failure Protection	✗
SIP	Surge: MOV Inrush: NTC & Bypass Relay

Supplementary Tests (For Reference)

Typical Load Tests

115V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
10%	8.198A	1.986A	2.006A	0.993A	119.979	90.97%	0	<6.0	48.1°C	0.962
	12.001V	5.035V	3.289V	5.035V	131.889				40.03°C	115.05V
20%	17.427A	2.982A	3.015A	1.195A	239.932	93.652%	0	<6.0	48.59°C	0.984
	11.994V	5.031V	3.284V	5.02V	256.198				40.53°C	115.01V
30%	26.951A	3.481A	3.522A	1.399A	359.112	94.097%	0	<6.0	49.63°C	0.991
	11.987V	5.028V	3.28V	5.005V	381.645				41.04°C	114.97V
40%	36.583A	3.981A	4.03A	1.603A	479.492	93.953%	0	<6.0	51.99°C	0.994
	11.980V	5.025V	3.275V	4.99V	510.351				41.92°C	114.93V
50%	45.829A	4.98A	5.047A	1.809A	599.25	93.457%	0	<6.0	53.11°C	0.996
	11.974V	5.021V	3.269V	4.975V	641.211				42.46°C	114.89V
60%	55.179A	5.981A	6.057A	2A	719.706	92.594%	954	20	42.63°C	0.997
	11.961V	5.017V	3.269V	4.962V	777.296				54.25°C	114.85V
70%	64.449A	6.989A	7.082A	2.225A	839.487	91.811%	478	6.6	43.23°C	0.997
	11.953V	5.009V	3.262V	4.945V	914.366				68.18°C	114.81V
80%	73.806A	7.989A	8.103A	2.331A	959.456	90.884%	677	10.3	43.55°C	0.997
	11.944V	5.007V	3.258V	4.933V	1055.702				60.11°C	114.77V
90%	83.503A	8.494A	8.606A	2.439A	1079.261	89.982%	1093	24	44.41°C	0.997
	11.937V	5.003V	3.253V	4.921V	1199.431				67.53°C	114.72V
100%	93.025A	8.993A	9.138A	3.065A	1199.302	88.963%	1654	35.4	45.57°C	0.997
	11.928V	5.004V	3.25V	4.894V	1348.1				65.16°C	114.68V
110%	102.494A	10.001A	10.259A	3.071A	1319.897	88.093%	1973	40.7	46.37°C	0.996
	11.919V	4.999V	3.246V	4.884V	1498.303				62.99°C	114.64V
CL1	0.116A	14.464A	14.679A	0A	121.293	84.86%	584	7.9	40.93°C	0.965
	11.998V	4.992V	3.249V	5.045V	142.934				48.81°C	115.03V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
CL2	0.115A	24.173A	0A	0A	121.275	83.641%	1343	30.1	41.77°C	0.965
	12.002V	4.96V	3.286V	5.052V	144.995				46.79°C	115.03V
CL3	0.115A	0A	25.633A	0A	83.881	75.954%	1577	34.3	41.49°C	0.959
	11.997V	5.029V	3.218V	5.047V	110.437				45.05°C	115.05V
CL4	100.566A	0A	0A	0A	1199.881	89.762%	1081	23.7	44.01°C	0.997
	11.931V	5.028V	3.274V	4.99V	1336.756				62.57°C	114.68V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
10%	8.196A	1.988A	2.008A	0.993A	119.983	91.833%	0	<6.0	41.27°C	0.888
	12.003V	5.031V	3.286V	5.034V	130.654				40.49°C	230.25V
20%	17.426A	2.984A	3.017A	1.195A	239.937	94.563%	0	<6.0	42.76°C	0.946
	11.996V	5.028V	3.281V	5.019V	253.736				40.64°C	230.23V
30%	26.945A	3.483A	3.524A	1.399A	359.092	95.17%	0	<6.0	44.62°C	0.966
	11.989V	5.026V	3.277V	5.004V	377.319				41.32°C	230.21V
40%	36.578A	3.982A	4.033A	1.603A	479.49	95.328%	0	<6.0	42.36°C	0.974
	11.982V	5.023V	3.273V	4.99V	502.987				41.65°C	230.19V
50%	45.823A	4.982A	5.05A	1.809A	599.243	95.164%	0	<6.0	42.74°C	0.98
	11.975V	5.02V	3.267V	4.975V	629.698				42.23°C	230.17V
60%	55.144A	5.984A	6.073A	2A	719.7	94.512%	0	<6.0	44.39°C	0.984
	11.968V	5.015V	3.261V	4.96V	761.488				42.52°C	230.15V
70%	64.417A	6.986A	7.098A	2.224A	839.494	94.125%	482	6.6	43.23°C	0.987
	11.959V	5.011V	3.255V	4.945V	891.894				46.47°C	230.14V
80%	73.770A	7.984A	8.124A	2.331A	959.455	93.643%	307	<6.0	43.76°C	0.989
	11.950V	5.01V	3.249V	4.934V	1024.594				44.04°C	230.12V
90%	83.473A	8.48A	8.612A	2.438A	1079.266	93.138%	894	18.1	44.43°C	0.991
	11.941V	5.012V	3.251V	4.923V	1158.769				47.39°C	230.09V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
100%	92.980A	8.986A	9.155A	3.064A	1199.303	92.64%	1476	32.5	45.13°C	0.992
	11.933V	5.008V	3.244V	4.896V	1294.591				48.86°C	230.07V
110%	102.439A	9.99A	10.29A	3.071A	1319.912	91.997%	1974	40.7	46.48°C	0.993
	11.925V	5.005V	3.236V	4.885V	1434.744				49.38°C	230.05V
CL1	0.116A	14.444A	14.741A	0A	121.292	86.063%	580	7.8	40.16°C	0.896
	11.997V	4.999V	3.236V	5.046V	140.938				41.1°C	230.24V
CL2	0.116A	24.102A	0A	0A	121.283	84.588%	1340	30	40.27°C	0.897
	12.000V	4.975V	3.288V	5.053V	143.384				42.13°C	230.24V
CL3	0.115A	0A	25.637A	0A	83.881	76.82%	1613	34.9	40.56°C	0.86
	11.995V	5.032V	3.218V	5.048V	109.188				42.11°C	230.25V
CL4	100.515A	0A	0A	0A	1199.875	93.239%	1084	23.8	45.44°C	0.992
	11.937V	5.031V	3.277V	4.991V	1286.883				48.41°C	230.07V

The results above are not used in the certification process

Light Load Tests

115V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.237A	0.496A	0.5A	0.197A	19.993	69.931%	0	<6.0	47.27°C	0.884
	12.005V	5.043V	3.298V	5.067V	28.589				36.14°C	115.08V
40W	2.723A	0.694A	0.701A	0.296A	39.994	81.375%	0	<6.0	51.39°C	0.94
	12.005V	5.041V	3.296V	5.062V	49.146				37.68°C	115.07V
60W	4.209A	0.893A	0.901A	0.395A	59.995	86.433%	0	<6.0	45°C	0.963
	12.004V	5.04V	3.294V	5.058V	69.416				38.78°C	115.06V
80W	5.690A	1.092A	1.102A	0.495A	79.93	88.653%	0	<6.0	50.94°C	0.96
	12.003V	5.038V	3.293V	5.053V	90.158				39.31°C	115.06V

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
20W	1.236A	0.496A	0.501A	0.197A	19.996	71.949%	0	<6.0	37.31°C	0.48
	12.008V	5.038V	3.295V	5.066V	27.794				36.85°C	230.26V
40W	2.722A	0.695A	0.701A	0.296A	39.996	82.487%	0	<6.0	37.8°C	0.669
	12.007V	5.037V	3.294V	5.062V	48.491				37.63°C	230.26V
60W	4.208A	0.894A	0.902A	0.395A	59.997	87.063%	0	<6.0	38.14°C	0.774
	12.007V	5.036V	3.292V	5.057V	68.918				38.06°C	230.25V
80W	5.689A	1.093A	1.103A	0.495A	79.935	89.597%	0	<6.0	40.92°C	0.83
	12.006V	5.035V	3.291V	5.052V	89.219				39.28°C	230.25V

The results above are not used in the certification process

Ripple Measurements

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	14.39mV	9.99mV	10.08mV	8.15mV	Pass
20% Load	14.59mV	10.46mV	10.24mV	8.67mV	Pass
30% Load	15.78mV	10.97mV	11.17mV	9.08mV	Pass
40% Load	16.55mV	10.97mV	10.96mV	10.01mV	Pass
50% Load	17.27mV	11.18mV	11.12mV	10.01mV	Pass
60% Load	14.08mV	11.13mV	10.91mV	11.20mV	Pass
70% Load	14.80mV	12.73mV	12.72mV	14.14mV	Pass
80% Load	15.72mV	13.70mV	13.75mV	14.61mV	Pass
90% Load	16.60mV	14.06mV	14.64mV	14.81mV	Pass
100% Load	16.12mV	14.23mV	14.35mV	15.10mV	Pass
110% Load	16.30mV	15.08mV	15.11mV	15.90mV	Pass
Crossload1	14.15mV	10.47mV	10.93mV	7.92mV	Pass
Crossload2	15.05mV	16.85mV	11.17mV	8.10mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
Crossload3	14.13mV	10.35mV	12.98mV	8.05mV	Pass
Crossload4	15.94mV	13.44mV	13.56mV	13.27mV	Pass

The results above are not used in the certification process

230V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	14.49mV	9.99mV	10.19mV	8.31mV	Pass
20% Load	14.59mV	10.10mV	10.08mV	8.67mV	Pass
30% Load	16.03mV	10.92mV	10.75mV	9.45mV	Pass
40% Load	17.22mV	11.59mV	11.58mV	10.43mV	Pass
50% Load	17.58mV	10.97mV	11.12mV	10.12mV	Pass
60% Load	14.64mV	12.00mV	12.05mV	11.82mV	Pass
70% Load	15.41mV	12.26mV	12.00mV	13.52mV	Pass
80% Load	15.67mV	12.73mV	12.88mV	14.20mV	Pass
90% Load	15.67mV	12.88mV	13.39mV	13.78mV	Pass
100% Load	15.69mV	12.63mV	12.82mV	13.81mV	Pass
110% Load	16.15mV	12.64mV	13.34mV	14.22mV	Pass
Crossload1	14.22mV	10.81mV	10.86mV	7.70mV	Pass
Crossload2	15.36mV	14.37mV	10.24mV	8.36mV	Pass
Crossload3	14.44mV	9.99mV	12.20mV	8.05mV	Pass
Crossload4	16.99mV	11.88mV	12.47mV	11.87mV	Pass

The results above are not used in the certification process

be quiet! Dark Power 14 1200W




Top side

Model • Modèle 型號 型号 제품명 : P14 - 1200W ATX 3.1 Switching Power Supply • Alimentation à découpage 交換式電源供應器 开关电源供应器									
AC INPUT • ENTRÉE CA 交流輸入 交流輸入	100 - 240Vac		15 - 7A		50 - 60Hz		(Not for EU/China/Korea • Not applicable to U.S. & China et la Corée • 不适用于中国地区)		
	200 - 240Vac		7A		50 - 60Hz		(Only for EU/China/Korea/Argentina • Seulement pour l'UE/la Chine/la Corée/l'Argentine • 适用于中国地区)		
DC OUTPUT • SORTIE CC == 直流輸出 直流輸出	3.3V	5V	12V1	12V2	12V3	12V4	-12V	5VSB	
	25A	24A	33A	33A	45A	45A	0.5A	3A	
MAX. COMBINED POWER MAX. PUISSANCE COMBINÉE 最大總功率 最大总功率	120W				1200W		6W		15W
1200W									
Product conception, design and quality control in Germany Conception, design et contrôle qualité des produits en Allemagne									
UK Authorised Representative (for authorities only) ProductIP (UK) Ltd. 8, Northumberland Av. London WC2N 5BY 製造商: Listan GmbH Wilhelm-Bergner-Straße 11c 21509 Glinde Germany • Allemagne									
Made in China Fabriqué en Chine 中國製造 中国制造									
 S/N: 021EUL5220000100									

Power specifications label



Fan



PSU Internals

Cybenetics bietet freiwillige Zertifizierungsprogramme für Netzteile - ETA für Effizienz, LAMBDA für Lautstärke und SAFE für Sicherheit und korrekten Betrieb - sowie für Kühlprodukte mit DELTA für die Schalldämmung von Gehäusen und PHI für Luftstrom und statischen Druck von Lüftern

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus

www.cybenetics.com - info@cybenetics.com