

GIGABYTE™

Gigabyte GP-UD1000GM PG5 V2 / ICE

□□ -

Lab ID GB10003071

Certification ID 253071

Test Result Report ID: 25PS3071A

Certificate Issue Date: Jan 9, 2026

115V

230V

Scheme: ETA-EMI PSU

CYBENETICS

PLATINUM

CYBENETICS

SILVER

230v

115V

230V

Scheme: LAMBDA PSU

CYBENETICS

STANDARD++

CYBENETICS

STANDARD++

230v

CYBENETICS

ATX 3.1

PASS

Outside Validation Scope



General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details		
Brand	Gigabyte	
Model	GP-UD1000GM PG5 V2 / ICE	
OEM/ODM	Guangzhou Pansheng Electronic Technology Co., Ltd	
Serial Number	-	
Product Specifications		
Manufacturer-Provided Information		
Vrms	100-240	
Arms	6.5-12	

□□□□ (Hz)	50-60
□□□□ (W)	1000
Operating Temperature (Continuous Full Load) (°C)	0 - 50
□□	ATX12V
□□□□	Fully Modular
Warranty	No info
Cybenetics Measurements	
Dimensions (W x H x D)	150 x 85 x 140mm
Weight	1.40 kg (3.09lb)
□□	120mm Fluid Dynamic Bearing Fan (BK BDH12025S)
□□□□	✓
Cybenetics Testing Information	
Lab ID	GB10003071
Date of receipt	Nov 17, 2025
Testing Date	Dec 29, 2025
Report Issued Date	Jan 9, 2026
□□□□	• The results apply to both the black and white (ICE) models. • The vampire power consumption is too high for the Gold ETA rating at 230V (0.2127W). • PF @ 230V is lower than the Platinum ETA level's requirements.
Engineer Name	Ioannis Kalyviotis
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

□□□□ (Non-accredited measurements)

□□□□				
□□	□□□□	□□□□□	Gauge	Cable Type
ATX □□ 20+4 pin (600mm)	1	1	18AWG	Tinned Copper
4+4 pin EPS 12V □□ (650mm+200mm)	1	2	18AWG	Tinned Copper
6+2pin PCIe□□ (600mm+145mm)	2	4	18AWG	Tinned Copper
12+4 pin PCIe (700mm) (600W)	1	1	16-24AWG	Tinned Copper

SATA□□ (600mm+150mm+150mm+150mm)	2	8	18AWG	Tinned Copper
4-pin Molex (500mm+150mm+150mm) / FDD (+150mm)	1	3 / 1	18AWG	Tinned Copper

Protection Features(Manufacturer)

Over Power Protection	✓
Over Current (+12V) Protection	✓
Over Temperature Protection	✓
Short Circuit Protection	✓
Surge Protection	✓
Inrush Current Protection	✓
Fan Failure Protection	✗

□□□□

□		3.3V	5V	12V	5VSB	-12V
□□□□	□□	25	25	83.3	3	0.3
	□	125		1000	15	3.6
□□□□ (W)		1000				

Parts Description

General Data	
Manufacturer (OEM)	Guangzhou Pansheng Electronic Technology Co., Ltd
PCB Type	Double-Sided
Primary Side	
Transient Filter	4x Y caps, 3x X caps, 2x CM chokes, 1x MOV
Inrush Protection	NTC Thermistor MF72-10D15 (10 Ohm @ 25°C) & Relay
Bridge Rectifier	2x GBU2510 (1000V, 25A @ 100°C)
APFC MOSFETs	2x Wuhan Xinyuan Semiconductor CWH65R038AZ (650V, 30A @ 25°C, Rds(on): 38mOhm)
APFC Boost Diode	1x CR Micro CRXF10D065G2 (650V, 10A @ 125°C)
Bulk Cap(s)	2x Toshin Kogyo (420V, 390μF, 2000h @ 105°C, LW)
Main Switchers	2x Wuhan Xinyuan Semiconductor CWS60R099BZ (600V, 25A @ 100°C, Rds(on): 99mOhm)

APFC Controller	Champion CM6500UNX
Resonant Controller	Champion CU6901T6X
Topology	Primary side: APFC, Half-Bridge & LLC Resonant Converter Secondary side: [12V] Synchronous Rectification & [Minor Rails] DC-DC converters
Secondary Side	
+12V MOSFETs	6x Nexperia PSMN1R0-40YLD (40V, 280A @ 25°C, Rds(on): 1.1mOhm)
5V & 3.3V	DC-DC Converters: 4x InPower Semiconductor FTG022N03S (30V, 120A @ 100°C, Rds(on): 2.2mOhm) PWM Controller(s): 2x ANPEC APW7164
Filtering Capacitors	Electrolytic: 10x Toshin Kogyo (@ 105°C, AZ series) 6x Toshin Kogyo (@ 105°C, HZ series) Polymer: 7x Teapo (470µF, 16V) 9x Teapo (820µF, 6.3V)
Supervisor IC	Grenergy GR8329E (OVP, UVP, OCP, PGO, FPO)
MCU / Fan Controller	Anpec APW9010
Fan Model	BOK BDH12025S (120mm, 12V, 0.18A, Fluid Dynamic Bearing)
5VSB Circuit	
Rectifier	Dongke Semiconductor DK5V60R20H Synchronous Rectifier (60V, 35A, Rds(on): 20mOhm)
Standby PWM Controller	Excelliance MOS Corporation EM8564A

Test Results

Temperature & Compliance Info

□□□ (°C / °F)	28-32 / 82.4-89.6
□□ ErP Lot3/6□□	✓
□□ (EU) No 617/2013□□	✓
ALPM (Alternative Low Power Mode) compatible	✓
ATX v3.1 PSU Power Excursion	✓

Performance Summary 115V

Accredited	
THD (%) (>1450 load combinations)	89.270%
Average Noise Output (>1450 Load Combinations)	31.48dBA
PF (%) (>1450 Load Combinations)	0.982
Efficiency With 10W (≤500W) or 2% (>500W) Load	69.884%
THD (%)	0.0712W
Non-Accredited	
12V Ripple (Full Load)	32.46mV
5V Ripple (Full Load)	27.75mV
3.3V Ripple (Full Load)	26.18mV
5VSB Ripple (Full Load)	28.43mV
12V Load Regulation	0.49%
5V Load Regulation	0.70%
3.3V Load Regulation	0.52%
5VSB Load Regulation	1.93%
Inrush Current	19.760A

THD (%) & PFC (%)

Hold-Up Time (ms)	25.8
AC Loss to PWR_OK Hold Up Time (ms)	21.4
PWR_OK Inactive to DC Loss Delay (ms)	4.4

THD (%)


Tables 115V

Detailed Results						
	Average	Min	Limit Min	Max	Limit Max	Result
Mains Voltage RMS:	230.07 V	230.06 V	227.70 V	230.10 V	232.30 V	PASS

Mains Frequency:	50.00 Hz	50.00 Hz	49.50 Hz	50.01 Hz	50.50 Hz	PASS
Mains Voltage CF:	1.415	1.415	1.340	1.416	1.490	PASS
Mains Voltage THD:	0.15 %	0.13 %	N/A	0.16 %	2.00 %	PASS
Real Power:	0.213 W	0.170 W	N/A	0.280 W	N/A	N/A
Apparent Power:	67.211 W	67.180 W	N/A	67.241 W	N/A	N/A
Power Factor:	0.003	N/A	N/A	N/A	N/A	N/A




115V



This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations




115V




The PSU's noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

Conducted Emissions EN 55032 & CISPR 32


Gigabyte Ultra durable Gold 1000W (GB10003071) Neutral



Gigabyte Ultra durable Gold 1000W (GB10003071) Phase




Indicative Performance



Efficiency: Gigabyte Ultra Durable Gold 1000W

Ambient: 37°C - 47°C (98.6°F - 116.6°F)




The PSU's efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

5Vsb

5VSB Efficiency: Gigabyte Ultra Durable Gold 1000W

Ambient: 25°C - 30°C (77°F - 86°F)



This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

5Vsb (ErP Lot3/6 & CEC) 115V

#	5VSB	DC/AC ()		PF/AC
1	0.045A	0.226W	60.044%	0.019
	5.025V	0.376W		115.04V

2	0.09A	0.452W	70.053%	0.032
	5.024V	0.645W		115.04V
3	0.55A	2.756W	80.436%	0.154
	5.012V	3.426W		115.04V
4	1A	4.999W	81.761%	0.237
	5V	6.114W		115.04V
5	1.5A	7.48W	80.02%	0.298
	4.986V	9.348W		115.04V
6	3A	14.838W	73.288%	0.377
	4.947V	20.246W		115.03V

Protection Features

OCP (Normal @ 28.7°C)	12V: 100.80A (121.01%), 11.845V 5V: 29.2A (116.80%), 5.115V 3.3V: 31.004A (124.02%), 3.249V 5VSB: 3.8A (126.67%), 4.922V
OCP (Hot @ 44.8°C)	12V: 96.80A (116.21%), 11.850V 5V: 28.7A (114.80%), 5.108V 3.3V: 31.1A (124.40%), 3.248V 5VSB: 3.7A (123.33%), 4.924V
OPP (Normal @ 31.4°C)	1273.083W (127.31%)
OPP (Hot @ 44.6°C)	1225.062W (122.51%)
OTP	✓ (128°C @ 12V Heatsink)
SCP	12V to Earth: ✓ 5V to Earth: ✓ 3.3V to Earth: ✓ 5VSB to Earth: ✓ -12V to Earth: ✓
PWR_OK	Proper Operation
UVP (Full Load @ 90V)	✓
UVP (No Damage @ 80V)	✓
Conducted Emissions EN55032 & CISPR 32	✓
NLO	✓

Fan Failure Protection	X
SIP	Surge: MOV Inrush: NTC & Bypass Relay

Supplementary Tests (For Reference)

10-110% 115V

	12V	5V	3.3V	5VSB	DC/AC ()		(RPM)	(dB[A])	(/)	PF/AC
10%	6.614A	1.977A	2.007A	1A	100.009	88.09%	739	21.1	40.43°C	0.965
	11.855V	5.059V	3.288V	4.999V	113.531				42.3°C	115.01V
20%	14.268A	2.966A	3.012A	1.202A	199.962	91.039%	778	22.5	40.56°C	0.966
	11.849V	5.057V	3.287V	4.992V	219.644				43.04°C	114.97V
30%	22.287A	3.465A	3.516A	1.404A	300.022	91.138%	875	26.3	41.15°C	0.979
	11.844V	5.051V	3.285V	4.985V	329.189				45.88°C	114.94V
40%	30.273A	3.964A	4.02A	1.607A	399.598	91.207%	962	29.2	41.92°C	0.985
	11.839V	5.046V	3.284V	4.978V	438.12				46.62°C	114.9V
50%	37.929A	4.957A	5.028A	1.811A	499.324	90.985%	1042	31.5	42.32°C	0.989
	11.833V	5.044V	3.282V	4.97V	548.796				49.75°C	114.86V
60%	45.662A	5.95A	6.038A	2A	599.789	90.467%	1434	39.4	42.8°C	0.991
	11.827V	5.043V	3.28V	4.963V	662.995				50.94°C	114.83V
70%	53.336A	6.944A	7.048A	2.22A	699.582	89.84%	1735	43	43.27°C	0.993
	11.821V	5.041V	3.278V	4.956V	778.702				51.08°C	114.79V
80%	61.086A	7.937A	8.059A	2.323A	799.582	89.176%	1896	44.5	43.88°C	0.994
	11.814V	5.039V	3.276V	4.951V	896.636				51.7°C	114.75V
90%	69.180A	8.444A	8.55A	2.426A	899.347	88.485%	1900	44.6	44.24°C	0.995
	11.808V	5.032V	3.275V	4.947V	1016.383				53.84°C	114.71V
100%	77.079A	8.954A	9.073A	3.045A	999.366	87.547%	1904	44.7	45.14°C	0.996
	11.802V	5.024V	3.274V	4.927V	1141.515				56.35°C	114.66V
110%	84.905A	9.956A	10.18A	3.046A	1099.947	86.515%	1908	44.7	47.09°C	0.997
	11.798V	5.021V	3.271V	4.925V	1271.396				59.83°C	114.62V

CL1	0.118A	14.574A	15.173A	0A	126.297	82.72%	1868	44.3	40.14°C	0.963
	11.867V	5.166V	3.269V	5.027V	152.678				43.82°C	114.99V
CL2	0.118A	23.872A	0A	0A	126.26	82.978%	925	28	40.69°C	0.962
	11.864V	5.231V	3.29V	5.027V	152.156				43.46°C	114.99V
CL3	0.117A	0A	25.331A	0A	83.898	74.883%	943	28.5	40.19°C	0.965
	11.864V	5.018V	3.257V	5.028V	112.038				44.23°C	115V
CL4	84.754A	0A	0A	0.001A	999.931	88.296%	1908	44.7	45.85°C	0.995
	11.798V	4.948V	3.287V	5.012V	1132.488				54.7°C	114.67V

The results above are not used in the certification process

20-80 115V

	12V	5V	3.3V	5VSB	DC/AC ()		(RPM)	(dB[A])	(/)	PF/AC
20W	1.253A	0.495A	0.501A	0.199A	20.01	68.813%	685	18.4	36.72°C	0.748
	11.860V	5.054V	3.291V	5.022V	29.079				39.27°C	115.03V
40W	2.758A	0.693A	0.702A	0.299A	40.005	80.421%	688	18.5	37.4°C	0.871
	11.857V	5.054V	3.29V	5.019V	49.748				39.62°C	115.02V
60W	4.262A	0.89A	0.903A	0.399A	60.003	84.043%	696	19.4	38.69°C	0.931
	11.857V	5.054V	3.29V	5.016V	71.399				40.82°C	115.02V
80W	5.763A	1.088A	1.104A	0.499A	79.954	86.827%	710	19.9	39.42°C	0.954
	11.856V	5.053V	3.289V	5.013V	92.09				41.4°C	115.01V

The results above are not used in the certification process

115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	29.06mV	24.83mV	24.81mV	23.02mV	Pass
20% Load	28.45mV	23.86mV	23.94mV	22.61mV	Pass
30% Load	30.70mV	23.45mV	23.43mV	22.61mV	Pass
40% Load	30.44mV	24.01mV	26.34mV	22.56mV	Pass
50% Load	30.49mV	28.00mV	26.45mV	23.73mV	Pass
60% Load	30.29mV	26.67mV	29.57mV	25.57mV	Pass

