# ASUS TUF Gaming 650W Gold EVO

2Q014131925

Lab ID AS65003264

Certification ID 263264

Test Result Report ID: 26PS3264A

Certificate Issue Date: Apr 28, 2026

Scheme: ETA-EMI PSU

115V 230V







Scheme: LAMBDA PSU

115V 230V










Outside Validation Scope



# General Information

## Test Equipment

| | |
|---|---|
| Electronic Loads | Chroma 63601-5 x2<br>Chroma 63600-2<br>Chroma 63640-80-80 x10<br>Chroma 63610-80-20 |
| AC Sources | Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500 |
| Power Analyzers | Rohde & Schwarz HMC8015 & NPA701 |
| Oscilloscopes | Picoscope 4444, Siglent SDS2104X PLUS |
| Sound Analyzer | Bruel & Kjaer 2270 G4 |
| Microphone | Bruel & Kjaer Type 4955-A |
| Temperature Logger | Picoscope TC-08 |
| Tachometer | UNI-T UT372 |
| Multimeters | Keysight 34465A |
| EMI Analyzer | TekBox TBMR-110M-EU |
| Isolation Transformer | 4kVA |
| UPS | FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA |
| Testing Methodology | Cybenetics PSU Test Protocol |

## DUT Information
## (Non-accredited measurements)

| | |
|---|---|
| Product Identification Details | |
| Brand | ASUS |
| Model | TUF Gaming 650W Gold EVO |
| OEM/ODM | Great Wall |
| Serial Number | 2Q014131925 |
| Product Specifications | |
| Manufacturer-Provided Information | |
| □□□□ (Vrms) | 100-240 |

| | |
|---|---|
| □□□□ (Arms) | 6-10 |
| □□□□ (Hz) | 47-63 |
| □□□□ (W) | 650 |
| Operating Temperature (Continuous Full Load) (°C) | 0 - 40 |
| □□ | ATX12V |
| □□□□ | Fully Modular |
| Warranty | 8 years |
| Cybenetics Measurements | |
| Dimensions (W x H x D) | 150 x 85 x 140mm |
| Weight | 1.29 kg (2.84 lb) |
| □□ | 135mm Ball Bearing Fan (HA13525M12B-Z) |
| □□□□□ | ✗ |
| Cybenetics Testing Information | |
| Lab ID | AS65003264 |
| Date of receipt | Apr 8, 2026 |
| Testing Date | Apr 24, 2026 |
| Report Issued Date | Apr 28, 2026 |
| Engineer Name | Ioannis Kalyviotis |
| Authorized By the Laboratory Technical Manager | Aristeidis Bitziopoulos |
| Signature |  |

## □□□□□
## (Non-accredited measurements)

| ????? | | | | |
|---|---|---|---|---|
| □□ | □□□□ | □□□□□□ | **Gauge** | **Cable Type** |
| ATX □□ 20+4 pin (500mm) | 1 | 1 | 18AWG | Tinned Copper |
| 4+4 pin EPS 12V □□ (650mm+100mm) | 1 | 2 | 18AWG | Tinned Copper |
| 6+2pin PCIe□□ (500mm) | 1 | 1 | 18AWG | Tinned Copper |
| 12+4 pin PCIe (500mm) (600W) | 1 | 1 | 16-24AWG | Tinned Copper |
| SATA□□ (400mm+115mm) / 4-pin Molex (+115mm) | 2 | 4 / 2 | 18AWG | Tinned Copper |

## Protection Features

| | |
|---|---|
| Under Voltage Protection | ✓ |
| Over Power Protection | ✓ |
| Over Current (+12V) Protection | ✓ |
| Over Temperature Protection | ✓ |
| Short Circuit Protection | ✓ |
| Surge Protection | ✓ |
| Inrush Current Protection | ✓ |
| Fan Failure Protection | ✗ |

## □□□□

| □ | | 3.3V | 5V | 12V | 5VSB | -12V |
|---|---|---|---|---|---|---|
| □□□□ | □□ | 20 | 20 | 54.16 | 3 | 0.3 |
| | □ | 110 | | 650 | 15 | 3.6 |
| □□□□□ (W) | | 650 | | | | |

## Parts Description

| | |
|---|---|
| **General Data** | |
| Manufacturer (OEM) | Great Wall |
| PCB Type | Double-Sided |
| **Primary Side** | |
| Transient Filter | 4x Y caps, 3x X caps, 2x CM chokes, 1x MOV |
| Inrush Protection | 1x NTC Thermistor SCK-056 (5 Ohm @ 20°C) & Relay |
| Bridge Rectifier | 1x ( @ 100°C) |
| APFC MOSFETs | 1x CRMicro CRJQ69N60G2 (600V, 25A @ 100°C, Rds(on): 0.073 Ohm) |
| APFC Boost Diode | 1x SMC S3D06065A (650V, 6A @ 150°C) |
| Bulk Cap(s) | 1x Samxon (420V, 390uF, 2,000h @ 105°C, HP ) |
| Main Switchers | 2x ST STF24N60DM2 (600V, 11A @ 100°C, Rds(on): 0.2 Ohm) |
| PFC/PWM Combo Controller | MPS HR1280 |

| | |
|---|---|
| Topology | Primary side: APFC, Half-Bridge & LLC converter<br>Secondary side: Synchronous Rectification & DC-DC converters |
| **Secondary Side** | |
| +12V MOSFETs | 4x ONSEMI NTMFS5C430NL (40V, 140A @ 100°C, Rds(on): 1.4 mOhm) |
| 5V & 3.3V | DC-DC Converters: 4x AP4024GEMT-HF (30V, 60A @ 25°C, Rds(on): 4.5 mOhm)<br>PWM Controller(s): ANPEC APW7159C |
| Filtering Capacitors | Electrolytic:<br>4x Elite (5000 @ 105°C, EJ )<br>3x Elite (4000 @ 105°C, EK )<br>1x Elite (4000 @ 105°C, ED )<br>1x Elite (4000 @ 105°C, EY )<br>1x Lelon (1000 @ 105°C, RA )<br>Polymer:<br>3x Nichicon FPCAP, 2x Elite, 4x Nippon Chemi-con |
| Supervisor IC | NDP NDP5201KC |
| Fan Controller | BCD AS358M |
| Fan Model | Hong Hua HA13525M12B-Z (135mm, 12V, 0.36A, Dual Ball Bearing Fan) |
| **5VSB Circuit** | |
| Rectifier | DIODES SDT8A60VP5 (60V,8A) |
| Standby PWM Controller | Lendtrend LD5537E1 |

# Test Results

## Temperature & Compliance Info

| | |
|---|---|
| □□□□ (°C /°F) | 28-32 / 82.4-89.6 |
| □□ ErP Lot3/6□□ | ✓ |
| □□ (EU) No 617/2013□□ | ✓ |
| ALPM (Alternative Low Power Mode) compatible | ✓ |
| ATX v3.1 PSU Power Excursion | ✓ |

## Performance Summary

### 115V

| | |
|---|---|
| Accredited | |
| □□□□ (>1450 load combinations) | 88.561% |
| Average Noise Output (>1450 Load Combinations) | 22.89dBA |
| PF□□□ (>1450 Load Combinations) | 0.966 |
| Efficiency With 10W (≤500W) or 2% (>500W) Load | 71.500% |
| □□□□□□ | 0.0449W |
| Non-Accredited | |
| 12V Ripple (Full Load) | 64.44mV |
| 5V Ripple (Full Load) | 29.82mV |
| 3.3V Ripple (Full Load) | 27.40mV |
| 5VSB Ripple (Full Load) | 17.44mV |
| 12V Load Regulation | 1.04% |
| 5V Load Regulation | 1.55% |
| 3.3V Load Regulation | 3.42% |
| 5VSB Load Regulation | 2.66% |
| Inrush Current | 32.780A |

### 230V

| | |
|---|---|
| Accredited | |
| □□□□ (>1450 load combinations) | 91.045% |
| Average Noise Output (>1450 Load Combinations) | 22.24dBA |
| PF□□□ (>1450 Load Combinations) | 0.960 |
| Efficiency With 10W (≤500W) or 2% (>500W) Load | 74.115% |
| □□□□□□ | 0.1309W |
| Non-Accredited | |
| 12V Ripple (Full Load) | 58.92mV |
| 5V Ripple (Full Load) | 33.51mV |
| 3.3V Ripple (Full Load) | 31.40mV |

| | | |
|---|---|---|
| 5VSB Ripple (Full Load) | | 18.93mV |
| 12V Load Regulation | | 1.06% |
| 5V Load Regulation | | 1.55% |
| 3.3V Load Regulation | | 3.71% |
| 5VSB Load Regulation | | 2.68% |
| Inrush Current | | 74.660A |
| 12V Transient Response (200%) | | 11.42V |
| 5V Transient Response (200%) | | 4.967V |
| 3.3V Transient Response (200%) | | 3.169V |
| 5VSB Transient Response (200%) | | 5.071V |
| □□□□ & PG□□ | | 20.10ms |
| AC Loss to PWR_OK Hold Up Time | | 18.10ms |
| PWR_OK Inactive to DC Loss Delay | | 2.00ms |
| PSU Timings: T1 (20% / 100%) | 53.0ms | 53.0ms |
| PSU Timings: T3 (20% / 100%) | 123.0ms | 126.0ms |
| 12V OCP (29.3°C / 41.2°C) | 68.40A (126.29%), 11.955V | 68.00A (125.55%), 11.957V |
| 5V OCP (29.3°C / 41.2°C) | 27.6A (138.00%), 5.065V *High Ripple (53.27mV) | 27.4A (137.00%), 5.065V |
| 3.3V OCP (29.3°C / 41.2°C) | 27.1A (135.50%), 3.206V | 26.9A (134.50%), 3.202V |
| 5VSB OCP (29.3°C / 41.2°C) | 4.2A (140.00%), 5.071V | 4.2A (140.00%), 5.072V |
| OPP (28.69°C / 41.74°C) | 124.72% | 123.94% |

## □□□□ & PG□□

| | |
|---|---|
| Hold-Up Time (ms) | 20.1 |
| AC Loss to PWR_OK Hold Up Time (ms) | 18.1 |
| PWR_OK Inactive to DC Loss Delay (ms) | 2 |

## Tables

### 115V


| Detailed Results | | | | | | |
|---|---|---|---|---|---|---|
| | Average | Min | Limit Min | Max | Limit Max | Result |
| Mains Voltage RMS: | 115.03 V | 115.02 V | 113.85 V | 115.06 V | 116.15 V | PASS |
| Mains Frequency: | 60.00 Hz | 59.94 Hz | 59.40 Hz | 60.01 Hz | 60.60 Hz | PASS |
| Mains Voltage CF: | 1.416 | 1.415 | 1.340 | 1.417 | 1.490 | PASS |
| Mains Voltage THD: | 0.13 % | 0.11 % | N/A | 0.16 % | 2.00 % | PASS |
| Real Power: | 0.045 W | 0.013 W | N/A | 0.075 W | N/A | N/A |
| Apparent Power: | 13.279 W | 13.259 W | N/A | 13.303 W | N/A | N/A |
| Power Factor: | 0.003 | N/A | N/A | N/A | N/A | N/A |

### 230V

| Detailed Results | | | | | | |
|---|---|---|---|---|---|---|
| | Average | Min | Limit Min | Max | Limit Max | Result |
| Mains Voltage RMS: | 230.05 V | 230.03 V | 227.70 V | 230.12 V | 232.30 V | PASS |
| Mains Frequency: | 50.00 Hz | 50.00 Hz | 49.50 Hz | 50.00 Hz | 50.50 Hz | PASS |
| Mains Voltage CF: | 1.415 | 1.415 | 1.340 | 1.416 | 1.490 | PASS |
| Mains Voltage THD: | 0.14 % | 0.13 % | N/A | 0.16 % | 2.00 % | PASS |
| Real Power: | 0.131 W | 0.093 W | N/A | 0.177 W | N/A | N/A |
| Apparent Power: | 43.830 W | 43.780 W | N/A | 43.884 W | N/A | N/A |
| Power Factor: | 0.004 | N/A | N/A | N/A | N/A | N/A |

## □□□□□□


**115V**




□□

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations


## 230V




This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations

## □□□□□


**115V**




□□

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

## 230V




The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

## Noise under high ambient temperature (indicative)

### 115V

| Load | Normal ambient<br>fan · noise · intake | High ambient<br>fan · noise · intake | Noise change |
|---|---|---|---|
| 10% | 329 RPM · <6.0 dB(A) · 30.9 °C | 396 RPM · <6.0 dB(A) · 40.2 °C | <6.0 in both |
| 20% | 352 RPM · <6.0 dB(A) · 31.1 °C | 470 RPM · 9.3 dB(A) · 41.0 °C | <6.0 → 9.3 dB(A) |
| 50% | 401 RPM · <6.0 dB(A) · 30.2 °C | 673 RPM · 20.1 dB(A) · 42.4 °C | <6.0 → 20.1 dB(A) |
| 100% | 903 RPM · 29.1 dB(A) · 30.9 °C | 1450 RPM · 43.3 dB(A) · 45.7 °C | **+14.2 dB(A)** |

### 230V


| Load | Normal ambient<br>fan · noise · intake | High ambient<br>fan · noise · intake | Noise change |
|---|---|---|---|
| 10% | 317 RPM · <6.0 dB(A) · 30.7 °C | 432 RPM · 7.5 dB(A) · 40.1 °C | <6.0 → 7.5 dB(A) |
| 20% | 321 RPM · <6.0 dB(A) · 31.0 °C | 493 RPM · 9.7 dB(A) · 40.8 °C | <6.0 → 9.7 dB(A) |
| 50% | 323 RPM · <6.0 dB(A) · 30.7 °C | 653 RPM · 19.3 dB(A) · 42.3 °C | <6.0 → 19.3 dB(A) |
| 100% | 821 RPM · 26.6 dB(A) · 30.5 °C | 1422 RPM · 42.8 dB(A) · 45.6 °C | **+16.2 dB(A)** |

### INFO


Fan speed, noise and the measured intake temperature at 10, 20, 50 and 100 % load, from the two load regulation tests: at normal ambient (about 30-32 °C) and at high ambient (about 40-47 °C). These are stabilized readings at fixed loads, not averages over the certification sweep, so they are indicative of how the fan behaves when it is hot. "<6.0" is the floor of our sound meter: the fan is stopped or too quiet to measure (the fan speed column says which); with the fan stopped, the intake sensor can read higher than the chamber air.

*Informational. Not part of the ETA or LAMBDA rating.*

## Conducted Emissions EN 55032 & CISPR 32





NEUTRAL





PHASE

## Indicative Performance




The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

## 5Vsb□□□□




□□

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

## □□□□ □□ 5Vsb □□ (ErP Lot3/6 & CEC)

### 115V

| □□ # | 5VSB | DC/AC (□ ) | □□ | PF/AC □□ |
|---|---|---|---|---|
| **1** | **0.045A** | 0.233W | 66.08% | 0.027 |
| | 5.181V | 0.353W | | 114.9V |
| **2** | **0.09A** | 0.466W | 72.253% | 0.048 |
| | 5.179V | 0.645W | | 114.9V |
| **3** | **0.55A** | 2.842W | 80.206% | 0.225 |
| | 5.167V | 3.543W | | 114.89V |
| **4** | **1A** | 5.157W | 80.438% | 0.33 |
| | 5.156V | 6.411W | | 114.89V |
| **5** | **1.5A** | 7.716W | 80.128% | 0.392 |
| | 5.143V | 9.63W | | 114.89V |
| **6** | **3A** | 15.315W | 77.818% | 0.484 |
| | 5.105V | 19.681W | | 114.89V |

### 230V

| □□ # | 5VSB | DC/AC (□ ) | □□ | PF/AC □□ |
|---|---|---|---|---|
| **1** | **0.045A** | 0.233W | 54.125% | 0.01 |
| | 5.183V | 0.433W | | 229.89V |
| **2** | **0.09A** | 0.466W | 66.963% | 0.015 |
| | 5.181V | 0.697W | | 229.89V |
| **3** | **0.55A** | 2.843W | 78.569% | 0.077 |
| | 5.169V | 3.62W | | 229.88V |
| **4** | **1A** | 5.158W | 79.573% | 0.133 |
| | 5.157V | 6.483W | | 229.89V |
| **5** | **1.5A** | 7.717W | 80.003% | 0.185 |
| | 5.144V | 9.646W | | 229.89V |
| **6** | **3A** | 15.317W | 79.439% | 0.298 |
| | 5.105V | 19.28W | | 229.89V |

## Protection Features

| | |
|---|---|
| OCP (Normal @ 29.3°C) | 12V: 68.4A (126.29%), 11.955V<br>5V: 27.6A (138%), 5.065V *High Ripple (53.27mV)<br>3.3V: 27.1A (135.5%), 3.206V<br>5VSB: 4.2A (140%), 5.071V |
| OCP (Hot @ 41.2°C) | 12V: 68A (125.55%), 11.957V<br>5V: 27.4A (137%), 5.065V<br>3.3V: 26.9A (134.5%), 3.202V<br>5VSB: 4.2A (140%), 5.072V |
| OPP (Normal @ 28.7°C) | 810.66W (124.72%) |
| OPP (Hot @ 41.7°C) | 805.61W (123.94%) |
| OTP | ✓ (110°C @ 12V Heatsink) |
| SCP | 12V to Earth: ✓<br>5V to Earth: ✓<br>3.3V to Earth: ✓<br>5VSB to Earth: ✓<br>-12V to Earth: ✓ |
| PWR_OK | Proper Operation |
| UVP (Full Load @ 90V) | ✓ |
| UVP (No Damage @ 80V) | ✓ |
| Conducted Emissions EN55032 & CISPR 32 | ✓ |
| NLO | ✓ |
| Fan Failure Protection | ✗ |
| SIP | Surge: MOV<br>Inrush: NTC & Bypass Relay |

## Supplementary Tests (For Reference)

### 10-110%□□□□

#### 115V

| □□ | 12V | 5V | 3.3V | 5VSB | DC/AC (□ ) | □□ | □□□□ (RPM) | □□□□□□□ (dB[A]) | □□ (□□ /□□ ) | PF/AC □□ |
|---|---|---|---|---|---|---|---|---|---|---|
| **10%** | **3.584A** | **1.966A** | **1.992A** | **0.971A** | 65.002 | 84.897% | 396 | <6.0 | 40.16°C | 0.866 |
| | 12.108V | 5.087V | 3.314V | 5.152V | 76.574 | | | | 43.59°C | 114.86V |
| **20%** | **8.188A** | **2.953A** | **2.998A** | **1.167A** | 129.932 | 86.82% | 470 | 9.3 | 40.95°C | 0.908 |
| | 12.095V | 5.079V | 3.302V | 5.141V | 149.547 | | | | 45.86°C | 114.76V |
| **30%** | **13.150A** | **3.45A** | **3.507A** | **1.365A** | 194.935 | 89.2% | 505 | 11 | 41.28°C | 0.932 |
| | 12.082V | 5.072V | 3.293V | 5.13V | 218.122 | | | | 47.01°C | 114.75V |
| **40%** | **18.132A** | **3.949A** | **4.02A** | **1.563A** | 260.022 | 90.284% | 565 | 13.9 | 41.52°C | 0.968 |
| | 12.068V | 5.065V | 3.284V | 5.119V | 288.02 | | | | 47.88°C | 114.8V |
| **50%** | **22.770A** | **4.944A** | **5.043A** | **1.762A** | 325.021 | 90.748% | 673 | 20.1 | 42.37°C | 0.987 |
| | 12.056V | 5.057V | 3.272V | 5.107V | 358.179 | | | | 48.78°C | 114.77V |
| **60%** | **27.368A** | **5.942A** | **6.075A** | **1.963A** | 389.37 | 90.492% | 771 | 23.9 | 42.73°C | 0.995 |
| | 12.041V | 5.049V | 3.26V | 5.096V | 430.272 | | | | 49.3°C | 114.75V |
| **70%** | **32.051A** | **6.944A** | **7.115A** | **2.164A** | 454.689 | 89.938% | 922 | 29.7 | 43.08°C | 0.996 |
| | 12.030V | 5.041V | 3.247V | 5.084V | 505.58 | | | | 50.94°C | 114.73V |
| **80%** | **36.749A** | **7.947A** | **8.161A** | **2.267A** | 519.483 | 89.271% | 1084 | 34.8 | 43.75°C | 0.997 |
| | 12.016V | 5.032V | 3.235V | 5.074V | 581.924 | | | | 51.93°C | 114.7V |
| **90%** | **41.859A** | **8.457A** | **8.679A** | **2.369A** | 584.905 | 88.521% | 1278 | 40 | 44.53°C | 0.998 |
| | 12.002V | 5.025V | 3.226V | 5.066V | 660.812 | | | | 53.4°C | 114.68V |
| **100%** | **46.716A** | **8.968A** | **9.231A** | **2.975A** | 649.749 | 87.572% | 1450 | 43.3 | 45.73°C | 0.998 |
| | 11.989V | 5.017V | 3.217V | 5.043V | 741.915 | | | | 55.46°C | 114.64V |
| **110%** | **51.452A** | **9.982A** | **10.391A** | **2.979A** | 714.374 | 86.73% | 1590 | 46.5 | 46.59°C | 0.999 |
| | 11.974V | 5.009V | 3.204V | 5.036V | 823.665 | | | | 58.25°C | 114.61V |
| **CL1** | **0.116A** | **13.088A** | **13.491A** | **0A** | 111.295 | 81.667% | 968 | 31.4 | 41.51°C | 0.901 |
| | 12.104V | 5.058V | 3.239V | 5.164V | 135.926 | | | | 51.11°C | 114.59V |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **CL2** | **0.116A** | **19.699A** | **0A** | **0A** | 101.353 | 80.654% | 797 | 25.3 | 40.05°C | 0.897 |
| | 12.108V | 5.074V | 3.303V | 5.168V | 125.657 | | | | 49.34°C | 114.84V |
| **CL3** | **0.114A** | **0A** | **20.479A** | **0A** | 67.382 | 74.327% | 698 | 21.2 | 41.56°C | 0.877 |
| | 12.107V | 5.062V | 3.222V | 5.168V | 90.651 | | | | 49.79°C | 114.86V |
| **CL4** | **54.210A** | **0A** | **0A** | **0A** | 649.562 | 88.782% | 1317 | 40.4 | 45.71°C | 0.998 |
| | 11.982V | 5.041V | 3.278V | 5.131V | 731.583 | | | | 53.87°C | 114.64V |

The results above are not used in the certification process

## 230V

| □□ | **12V** | **5V** | **3.3V** | **5VSB** | **DC/AC (□ )** | □□ | **□□□□ (RPM)** | **□□□□□□□ (dB[A])** | **□□ (□□ /□□ )** | **PF/AC □□** |
|---|---|---|---|---|---|---|---|---|---|---|
| **10%** | **3.586A** | **1.966A** | **1.992A** | **0.971A** | 65.009 | 86.562% | 432 | 7.5 | 40.07°C | 0.809 |
| | 12.107V | 5.087V | 3.313V | 5.152V | 75.065 | | | | 44.24°C | 229.88V |
| **20%** | **8.189A** | **2.954A** | **3A** | **1.167A** | 129.949 | 89.396% | 493 | 9.7 | 40.81°C | 0.927 |
| | 12.094V | 5.079V | 3.3V | 5.141V | 145.348 | | | | 45.26°C | 229.86V |
| **30%** | **13.153A** | **3.451A** | **3.51A** | **1.365A** | 194.954 | 92.472% | 493 | 9.7 | 41.17°C | 0.956 |
| | 12.080V | 5.072V | 3.291V | 5.13V | 210.824 | | | | 45.81°C | 229.86V |
| **40%** | **18.135A** | **3.949A** | **4.023A** | **1.563A** | 260.049 | 92.879% | 558 | 13.8 | 41.65°C | 0.973 |
| | 12.067V | 5.065V | 3.282V | 5.119V | 279.976 | | | | 46.71°C | 229.84V |
| **50%** | **22.776A** | **4.945A** | **5.049A** | **1.763A** | 325.048 | 92.84% | 653 | 19.3 | 42.25°C | 0.979 |
| | 12.053V | 5.057V | 3.269V | 5.107V | 350.125 | | | | 47.35°C | 229.83V |
| **60%** | **27.375A** | **5.943A** | **6.083A** | **1.963A** | 389.427 | 92.58% | 763 | 23.7 | 42.87°C | 0.984 |
| | 12.040V | 5.049V | 3.255V | 5.095V | 420.618 | | | | 48.37°C | 229.82V |
| **70%** | **32.061A** | **6.945A** | **7.126A** | **2.164A** | 454.752 | 92.237% | 912 | 29.5 | 43.29°C | 0.986 |
| | 12.028V | 5.041V | 3.242V | 5.083V | 493.059 | | | | 49.55°C | 229.82V |
| **80%** | **36.759A** | **7.948A** | **8.175A** | **2.267A** | 519.542 | 91.776% | 1089 | 34.8 | 43.71°C | 0.989 |
| | 12.015V | 5.032V | 3.229V | 5.073V | 566.078 | | | | 50.89°C | 229.79V |
| **90%** | **41.869A** | **8.458A** | **8.697A** | **2.37A** | 584.955 | 91.4% | 1256 | 39.6 | 44.51°C | 0.99 |
| | 12.001V | 5.025V | 3.219V | 5.065V | 640.038 | | | | 52.5°C | 229.79V |
| **100%** | **46.726A** | **8.969A** | **9.254A** | **2.976A** | 649.784 | 90.868% | 1422 | 42.8 | 45.58°C | 0.991 |
| | 11.987V | 5.017V | 3.209V | 5.042V | 715.067 | | | | 54.06°C | 229.78V |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **110%** | **51.464A** | **9.984A** | **10.421A** | **2.98A** | 714.418 | 90.133% | 1573 | 46.5 | 46.09°C | 0.994 |
| | 11.972V | 5.008V | 3.195V | 5.035V | 792.657 | | | | 56.03°C | 229.76V |
| **CL1** | **0.116A** | **13.09A** | **13.539A** | **0A** | 111.298 | 84.596% | 861 | 27.7 | 40.96°C | 0.915 |
| | 12.103V | 5.057V | 3.227V | 5.162V | 131.505 | | | | 49.68°C | 229.87V |
| **CL2** | **0.116A** | **19.702A** | **0A** | **0A** | 101.359 | 82.938% | 735 | 22.7 | 40.97°C | 0.905 |
| | 12.107V | 5.074V | 3.303V | 5.168V | 122.238 | | | | 48.85°C | 229.89V |
| **CL3** | **0.115A** | **0A** | **20.536A** | **0A** | 67.384 | 75.831% | 665 | 19.8 | 40.62°C | 0.851 |
| | 12.106V | 5.061V | 3.213V | 5.168V | 88.853 | | | | 48.54°C | 229.88V |
| **CL4** | **54.223A** | **0A** | **0A** | **0A** | 649.614 | 91.752% | 1283 | 40 | 45.45°C | 0.991 |
| | 11.980V | 5.04V | 3.278V | 5.131V | 707.906 | | | | 52.25°C | 229.77V |

The results above are not used in the certification process

## 20-80□□□□□

### 115V

| □□ | **12V** | **5V** | **3.3V** | **5VSB** | **DC/AC (□ )** | □□ | □□□□ **(RPM)** | □□□□□□□ **(dB[A])** | □□ **(□□ /□□ )** | **PF/AC □□** |
|---|---|---|---|---|---|---|---|---|---|---|
| **20W** | **1.226A** | **0.491A** | **0.496A** | **0.193A** | 19.996 | 76.967% | 326 | <6.0 | 36.63°C | 0.744 |
| | 12.114V | 5.095V | 3.327V | 5.177V | 26.008 | | | | 39.17°C | 114.88V |
| **40W** | **2.700A** | **0.687A** | **0.695A** | **0.29A** | 39.998 | 82.905% | 327 | <6.0 | 37.73°C | 0.828 |
| | 12.110V | 5.093V | 3.325V | 5.173V | 48.243 | | | | 40.43°C | 114.87V |
| **60W** | **4.174A** | **0.884A** | **0.894A** | **0.387A** | 59.999 | 85.628% | 334 | <6.0 | 38.44°C | 0.862 |
| | 12.106V | 5.091V | 3.322V | 5.169V | 70.075 | | | | 41.17°C | 114.88V |
| **80W** | **5.644A** | **1.081A** | **1.094A** | **0.484A** | 79.94 | 86.513% | 377 | <6.0 | 39.14°C | 0.879 |
| | 12.104V | 5.088V | 3.319V | 5.164V | 92.403 | | | | 42.83°C | 114.86V |

The results above are not used in the certification process

## 230V

| □□ | 12V | 5V | 3.3V | 5VSB | DC/AC (□ ) | □□ | □□□□ (RPM) | □□□□□□□□ (dB[A]) | □□ (□□ /□□ ) | PF/AC □□ |
|---|---|---|---|---|---|---|---|---|---|---|
| **20W** | **1.226A** | **0.491A** | **0.496A** | **0.193A** | 20.007 | 77.251% | 365 | <6.0 | 36.48°C | 0.413 |
| | 12.114V | 5.095V | 3.328V | 5.177V | 25.96 | | | | 41.25°C | 229.89V |
| **40W** | **2.700A** | **0.687A** | **0.695A** | **0.29A** | 40.007 | 83.455% | 363 | <6.0 | 37.2°C | 0.653 |
| | 12.110V | 5.093V | 3.325V | 5.172V | 47.947 | | | | 41.25°C | 229.88V |
| **60W** | **4.174A** | **0.884A** | **0.894A** | **0.387A** | 60.006 | 86.728% | 376 | <6.0 | 38.45°C | 0.786 |
| | 12.106V | 5.09V | 3.321V | 5.168V | 69.192 | | | | 41.92°C | 229.88V |
| **80W** | **5.646A** | **1.081A** | **1.094A** | **0.484A** | 79.956 | 88.284% | 397 | <6.0 | 39.41°C | 0.856 |
| | 12.102V | 5.088V | 3.318V | 5.164V | 90.563 | | | | 43.01°C | 229.88V |

The results above are not used in the certification process

□□□□

## 115V

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 10% Load | 38.77mV | 23.09mV | 20.83mV | 14.98mV | Pass |
| 20% Load | 39.30mV | 24.94mV | 22.98mV | 17.80mV | Pass |
| 30% Load | 36.77mV | 26.74mV | 24.68mV | 18.98mV | Pass |
| 40% Load | 40.61mV | 29.10mV | 26.22mV | 18.73mV | Pass |
| 50% Load | 41.33mV | 27.61mV | 25.04mV | 18.93mV | Pass |
| 60% Load | 44.70mV | 28.17mV | 24.68mV | 17.65mV | Pass |
| 70% Load | 46.24mV | 29.46mV | 26.94mV | 16.52mV | Pass |
| 80% Load | 50.58mV | 29.61mV | 27.14mV | 19.75mV | Pass |
| 90% Load | 59.48mV | 27.20mV | 25.29mV | 16.93mV | Pass |
| 100% Load | 64.44mV | 29.82mV | 27.40mV | 17.44mV | Pass |
| 110% Load | 68.54mV | 30.64mV | 28.78mV | 17.44mV | Pass |
| Crossload1 | 37.90mV | 33.92mV | 30.01mV | 20.47mV | Pass |
| Crossload2 | 60.40mV | 43.73mV | 27.86mV | 21.55mV | Pass |

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| Crossload3 | 50.79mV | 25.97mV | 34.99mV | 19.03mV | Pass |
| Crossload4 | 63.83mV | 26.38mV | 25.03mV | 17.80mV | Pass |

The results above are not used in the certification process


**230V**

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 10% Load | 34.52mV | 24.53mV | 21.39mV | 14.83mV | Pass |
| 20% Load | 27.16mV | 24.99mV | 21.65mV | 14.47mV | Pass |
| 30% Load | 32.02mV | 28.58mV | 23.34mV | 16.11mV | Pass |
| 40% Load | 37.24mV | 27.45mV | 25.19mV | 16.11mV | Pass |
| 50% Load | 41.22mV | 27.66mV | 25.70mV | 15.85mV | Pass |
| 60% Load | 43.22mV | 29.51mV | 28.17mV | 17.09mV | Pass |
| 70% Load | 45.18mV | 30.74mV | 28.93mV | 17.04mV | Pass |
| 80% Load | 51.91mV | 31.41mV | 28.68mV | 20.06mV | Pass |
| 90% Load | 53.96mV | 32.23mV | 29.40mV | 22.22mV | Pass |
| 100% Load | 58.92mV | 33.51mV | 31.40mV | 18.93mV | Pass |
| 110% Load | 62.35mV | 33.98mV | 31.45mV | 18.68mV | Pass |
| Crossload1 | 32.07mV | 31.61mV | 26.78mV | 16.73mV | Pass |
| Crossload2 | 49.05mV | 39.83mV | 24.63mV | 17.29mV | Pass |
| Crossload3 | 47.67mV | 26.89mV | 35.25mV | 17.29mV | Pass |
| Crossload4 | 57.90mV | 28.02mV | 26.52mV | 19.81mV | Pass |

The results above are not used in the certification process

ASUS TUF Gaming 650W Gold EVO









Top side Power specifications label

Third Photo

Fourth Photo

本测试报告中包含的所有数据和图表均可在以下条件下由任何人使用：使用过程需提及测试结果由 Cybenetics提供。
在任何情况下都应提供原始测试结果文档的网站链接

Cybenetics 提供自愿性认证计划：电源方面有 ETA（效率）、 LAMBDA（噪声）与 SAFE （安全与正确运行）；散热产品方面有 DELTA（机箱隔音）与 PHI（风扇风量与静压）

CYBENETICS LTD Syrou 6, Latsia, 2231, Nicosia Cyprus www.cybenetics.com - info@cybenetics.com

Cybenetics - ASUS TUF Gaming 650W Gold EVO - Test Report - Page 24 / 24