# ABKO COREMAX 500W BRONZE

-

Lab ID AB50003398

Certification ID 263398

Test Result Report ID: 26PS3398A

Certificate Issue Date: Sep 3, 2026

115V

Scheme: ETA-EMI PSU




115V




Scheme: LAMBDA PSU



Aristeidis Bitziopoulos, Certification Body General Manager

# General Information

## Test Equipment

| | |
|---|---|
| Electronic Loads | Chroma 63601-5 x2<br>Chroma 63600-2<br>Chroma 63640-80-80 x10<br>Chroma 63610-80-20 |
| AC Sources | Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500 |
| Power Analyzers | Rohde & Schwarz HMC8015 & NPA701 |
| Oscilloscopes | Picoscope 4444, Siglent SDS2104X PLUS |
| Sound Analyzer | Bruel & Kjaer 2270 G4 |
| Microphone | Bruel & Kjaer Type 4955-A |
| Temperature Logger | Picoscope TC-08 |
| Tachometer | UNI-T UT372 |
| Multimeters | Keysight 34465A |
| EMI Analyzer | TekBox TBMR-110M-EU |
| Isolation Transformer | 4kVA |
| UPS | FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA |
| Testing Methodology | Cybenetics PSU Test Protocol |

## DUT Information(Non-accredited measurements)

| | |
|---|---|
| Product Identification Details | |
| Brand | ABKO |
| Model | COREMAX 500W BRONZE |
| OEM/ODM | PREE |
| Serial Number | - |
| Product Specifications | |
| Manufacturer-Provided Information | |
| □□□□ (Vrms) | 115-230 |
| □□□□ (Arms) | 10 |
| □□□□ (Hz) | 50-60 |

| | |
|---|---|
| □□□□ (W) | 500 |
| Operating Temperature (Continuous Full Load) (°C) | 0 - 40 |
| □□ | ATX12V |
| □□□□ | Fixed cables |
| Warranty | No Info |
| Cybenetics Measurements | |
| Dimensions (W x H x D) | 150 x 85 x 140mm |
| Weight | 1.63 kg (3.59 lb) |
| □□ | 120mm Sleeve Bearing Fan (W12025HZ12SEMA) |
| □□□□□ | ✗ |
| Cybenetics Testing Information | |
| Lab ID | AB50003398 |
| Date of receipt | Jul 28, 2026 |
| Testing Date | Aug 27, 2026 |
| Report Issued Date | Sep 3, 2026 |
| Engineer Name | Efstathios Papadopoulos |
| Authorized By the Laboratory Technical Manager | Aristeidis Bitziopoulos |
| Signature |  |

## □□□□ (Non-accredited measurements)

| **????** | | | | |
|---|---|---|---|---|
| □□ | □□□□ | □□□□□□ | **Gauge** | Cable Type |
| ATX □□ 20+4 pin (520mm) | 1 | 1 | 18AWG | Tinned Copper |
| 4+4 pin EPS 12V □□ (630mm+150mm) | 1 | 2 | 18AWG | Tinned Copper |
| 6+2pin PCIe□□ (600mm) | 1 | 1 | 18AWG | Tinned Copper |
| 6+2pin PCIe□□ (600mm+150mm) | 1 | 2 | 18AWG | Tinned Copper |
| SATA□□ (450mm+150mm+150mm+150mm) | 1 | 4 | 18AWG | Tinned Copper |
| SATA□□ (450mm+150mm) / 4-pin Molex (+150mm) | 1 | 2/1 | 18AWG | Tinned Copper |
| 4-pin Molex (450mm+150mm) / SATA□□ (+150mm) | 1 | 2/1 | 18AWG | Tinned Copper |

## Protection Features(Manufacturer)

| | |
|---|---|
| Over Power Protection | ✓ |
| Over Current (+12V) Protection | ✓ |
| Over Temperature Protection | ✓ |
| Short Circuit Protection | ✓ |
| Surge Protection | ✗ |
| Inrush Current Protection | ✓ |
| Fan Failure Protection | ✗ |

□□□□

| □ | | 3.3V | 5V | 12V | 5VSB | -12V |
|---|---|---|---|---|---|---|
| □□□□ | □□ | 20 | 20 | 41.7 | 2.5 | 0.3 |
| | □ | 125 | | 500 | 12.5 | 3.6 |
| □□□□□ (W) | | 500 | | | | |

## Parts Description

| | |
|---|---|
| **General Data** | |
| Manufacturer (OEM) | PREE |
| PCB Type | Double-Sided |
| **Primary Side** | |
| Transient Filter | 4x Y caps, 2x X caps, 2x CM chokes |
| Inrush Protection | NTC Thermistor 2.5D-9 (2.5 Ohm @ 25°C) |
| Bridge Rectifier | 1x Diodes GBU1510 (1000V, 8A @ 100°C) |
| APFC MOSFETs | 2x Maple Semiconductor SLP18N50S (500V, 11.7A @ 100°C, Rds(on): 0.330Ohm) |
| APFC Boost Diode | Microsemi UF860 (600V, 8A @ 25°C) |
| Bulk Cap(s) | Toshin Kogyo (420V, 270uF, 2000h @ 105°C, LA) |
| Main Switchers | 2x Maple Semiconductor SLP18N50S (500V, 11.7A @ 100°C, Rds(on): 0.330Ohm) |
| PFC/PWM Combo Controller | Champion CM6805BG |
| Topology | Primary side: APFC, Double Forward<br>Secondary side: [12V] Passive Rectification & [Minor Rails] DC-DC converters |

| | |
|---|---|
| **Secondary Side** | |
| +12V MOSFETs | 5x HS 6NX014 |
| 5V & 3.3V | DC-DC Converters: 4x AP70N03NF (30V, 51A @ 100°C, Rds(on): 5.5mOhm)<br>PWM Controller(s): ANPEC APW7159C |
| Filtering Capacitors | <br>Electrolytic:<br>12x 12Kuang Jin (2-3,000 @ 105°C, GR )<br>Polymer:<br>2x |
| Supervisor IC | EST 7610FS |
| Fan Model | WAM W12025HZ12SEMA (120mm, 12V, 0.20A, Rifle Bearing Fan) |
| **5VSB Circuit** | |
| Rectifier | HS 6NX014 |
| Standby PWM Controller | EST 2816H |

# Test Results

## Temperature & Compliance Info

| | |
|---|---|
| □□□□ (°C /°F) | 28-32 / 82.4-89.6 |
| □□ ErP Lot3/6□□ | ✓ |
| □□ (EU) No 617/2013□□ | ✓ |
| ALPM (Alternative Low Power Mode) compatible | ✓ |
| Conducted Emissions EN 55032 & CISPR 32 | Passed |

## Performance Summary 115V

| | |
|---|---|
| Accredited | |
| □□□□ (>1450 load combinations) | 83.652% |
| Average Noise Output (>1450 Load Combinations) | 42.77dBA |
| PF□□□ (>1450 Load Combinations) | 0.977 |
| Efficiency With 10W (≤500W) or 2% (>500W) Load | 51.944% |
| □□□□□□ | 0.0702W |
| Non-Accredited | |

| | |
|---|---|
| 12V Ripple (Full Load) | 65.44mV |
| 5V Ripple (Full Load) | 25.35mV |
| 3.3V Ripple (Full Load) | 22.63mV |
| 5VSB Ripple (Full Load) | 19.61mV |
| 12V Load Regulation | 0.43% |
| 5V Load Regulation | 1.69% |
| 3.3V Load Regulation | 2.24% |
| 5VSB Load Regulation | 2.54% |
| Inrush Current | 59.630A |

## □□□□ & PG□□


| | |
|---|---|
| Hold-Up Time (ms) | 13.7 |
| AC Loss to PWR_OK Hold Up Time (ms) | 11.0 |
| PWR_OK Inactive to DC Loss Delay (ms) | 2.7 |

## □□□□

### Tables 115V


| Detailed Results | | | | | | |
|---|---|---|---|---|---|---|
| | Average | Min | Limit Min | Max | Limit Max | Result |
| Mains Voltage RMS: | 115.00 V | 114.96 V | 113.85 V | 115.02 V | 116.15 V | PASS |
| Mains Frequency: | 60.00 Hz | 59.94 Hz | 59.40 Hz | 60.01 Hz | 60.60 Hz | PASS |
| Mains Voltage CF: | 1.416 | 1.416 | 1.340 | 1.418 | 1.490 | PASS |
| Mains Voltage THD: | 0.15 % | 0.07 % | N/A | 0.22 % | 2.00 % | PASS |
| Real Power: | 0.070 W | 0.048 W | N/A | 0.091 W | N/A | N/A |
| Apparent Power: | 5.895 W | 5.710 W | N/A | 5.959 W | N/A | N/A |
| Power Factor: | 0.013 | N/A | N/A | N/A | N/A | N/A |

**115V**





□□

This graph depicts the PSU`s efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations




axis starts at 75




axis starts at 0.94


| Load range | Points | Efficiency 115V | PF 115V |
|---|---|---|---|
| 0-<20 % | 132 | 76.86% | 0.963 |
| 20-<40 % | 370 | 82.95% | 0.974 |
| 40-<60 % | 389 | 84.83% | 0.976 |
| 60-<80 % | 386 | 84.91% | 0.980 |
| 80-100 % | 403 | 84.19% | 0.983 |
| 70-100 % (High-Load) | 596 | 84.39% | 0.982 |
| All (published average) | 1680 | 83.65% | 0.977 |

**INFO**

The average efficiency and power factor in five ranges of load. Calculated from the 1680 (115V) load combinations of the certification sweep, the same data that ETA and LAMBDA use (test 0 excluded). Load is the total DC output as a share of the rated 500 W. These are plain averages of the valid readings, as for the ETA rating, so the ranges combined give back the published averages.

*Informational. Not part of the ETA or LAMBDA rating.*

### 115V





□□

The PSU`s noise in its entire operational range and under 30-32 °C ambient is depicted in this graph. The X axis represents the load on the +12V rail(s) while the Y axis is the load on the minor rails

### Noise by load range

**High-Load Index (70-100 % load)**
Noise **45.8 dB(A)** at 115V · loudest point 45.8 dB(A)

Efficiency 84.39% · power factor 0.982 (115V)




| Load range | Noise 115V avg (loudest) | Fan off 115V |
|---|---|---|
| 0-<20 % | 27.9 (37.8) | 0% |
| 20-<40 % | 32.5 (42.2) | 0% |
| 40-<60 % | 39.9 (45.8) | 0% |
| 60-<80 % | 44.9 (45.8) | 0% |
| 80-100 % | 45.8 (45.8) | 0% |
| 70-100 % (High-Load) | 45.8 (45.8) | 0% |
| All (published average) | 42.8 (45.8) | 0% |

**INFO**

The average noise in five ranges of load, the share of points with the fan stopped (semi-passive operation), and the High-Load Index: the same figures for all points at 70 % of the rated output and above. Calculated from the 1680 (115V) load combinations of the certification sweep, the same data that ETA and LAMBDA use (test 0 excluded). Load is the total DC output as a share of the rated 500 W. Noise is averaged on the energy scale, as for LAMBDA, so the ranges combined give back the published average noise. Each load combination is held for about five seconds; the stabilized readings at fixed loads

are under "Noise under high ambient temperature".

*Informational. Not part of the ETA or LAMBDA rating.*

### Noise under high ambient temperature (indicative)

#### 115V


| Load | Normal ambient<br>fan · noise · intake | High ambient<br>fan · noise · intake | Noise change |
|---|---|---|---|
| 10% | 707 RPM · 15.6 dB(A) · 30.6 °C | 731 RPM · 16.5 dB(A) · 34.4 °C | **+0.9 dB(A)** |
| 20% | 711 RPM · 15.6 dB(A) · 30.3 °C | 735 RPM · 17.1 dB(A) · 34.6 °C | **+1.5 dB(A)** |
| 50% | 1382 RPM · 36.4 dB(A) · 30.2 °C | 1722 RPM · 42.6 dB(A) · 36.2 °C | **+6.2 dB(A)** |
| 100% | 1853 RPM · 46.0 dB(A) · 31.0 °C | 1869 RPM · 46.3 dB(A) · 39.3 °C | **+0.3 dB(A)** |

#### INFO


Fan speed, noise and the measured intake temperature at 10, 20, 50 and 100 % load, from the two load regulation tests: at normal ambient (about 30-32 °C) and at high ambient (about 40-47 °C). These are stabilized readings at fixed loads, not averages over the certification sweep, so they are indicative of how the fan behaves when it is hot. "<6.0" is the floor of our sound meter, with the fan stopped; with the fan stopped, the intake sensor can read higher than the chamber air.

*Informational. Not part of the ETA or LAMBDA rating.*

## Conducted Emissions EN 55032 & CISPR 32





NEUTRAL





PHASE

## Indicative Performance




The PSU`s efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used

**5Vsb□□□□**




□□

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input

**□□□□ □□ 5Vsb □□ (ErP Lot3/6 & CEC) 115V**

| □□ # | 5VSB | DC/AC (□ ) | □□ | PF/AC □□ |
|---|---|---|---|---|
| **1** | **0.045A** | 0.236W | 63.378% | 0.08 |
| | 5.25V | 0.373W | | 114.95V |

| | | | | |
|---|---|---|---|---|
| **2** | **0.09A** | 0.473W | 71.68% | 0.133 |
| | 5.25V | 0.659W | | 114.93V |
| **3** | **0.55A** | 2.879W | 79.766% | 0.341 |
| | 5.233V | 3.609W | | 114.93V |
| **4** | **1A** | 5.218W | 80.248% | 0.378 |
| | 5.216V | 6.502W | | 114.93V |
| **5** | **1.5A** | 7.797W | 80.189% | 0.404 |
| | 5.197V | 9.723W | | 114.94V |
| **6** | **2.501A** | 12.892W | 79.53% | 0.433 |
| | 5.156V | 16.21W | | 114.93V |

## Protection Features

| | |
|---|---|
| OCP (Normal @ 27.2°C) | 12V: 47.600A (114.24%), 12.146V — shut down<br>5V: 30.900A (154.50%), 4.916V — shut down<br>3.3V: 29.800A (149.00%), 3.341V — shut down<br>5VSB: 4.300A (172.00%), 5.056V — shut down |
| OCP (Hot @ 38.1°C) | 12V: 45.800A (109.92%), 11.612V — shut down<br>5V: 31.000A (155.00%), 4.913V — shut down<br>3.3V: 25.300A (126.50%), 3.347V — shut down<br>5VSB: 4.300A (172.00%), 5.051V — shut down |
| OPP (Normal @ 24.9°C) | 608.02W (121.60%) — shut down |
| OPP (Hot @ 40.1°C) | 581.00W (116.20%) — shut down |
| OTP | ✓ (140°C @ 12V Heatsink) |
| SCP | 12V to Earth: ✓<br>5V to Earth: ✓<br>3.3V to Earth: ✓<br>5VSB to Earth: ✓<br>-12V to Earth: ✓ |
| PWR_OK | Accurate but short |
| UVP (Typical Load @ 90V) | ✓ |
| UVP (No Damage @ 80V) | ✓ |
| Conducted Emissions EN 55032 & CISPR 32 | ✓ |
| NLO | ✓ |

| | |
|---|---|
| Fan Failure Protection | ✗ |
| SIP | Surge: None<br>Inrush: NTC & Bypass Relay |

## Supplementary Tests (For Reference)

### 10-110%□□□□ 115V

| □□ | 12V | 5V | 3.3V | 5VSB | DC/AC (□ ) | □□ | □□□□ (RPM) | □□□□□□□ (dB[A]) | □□ (□□ /□□ ) | PF/AC □□ |
|---|---|---|---|---|---|---|---|---|---|---|
| **10%** | **2.306A** | **1.981A** | **1.957A** | **0.96A** | 50.006 | 76.32% | 731 | 16.5 | 34.43°C | 0.952 |
| | 12.317V | 5.05V | 3.372V | 5.211V | 65.521 | | | | 37.26°C | 114.93V |
| **20%** | **5.608A** | **2.977A** | **2.943A** | **1.154A** | 99.956 | 83.199% | 735 | 17.1 | 34.59°C | 0.986 |
| | 12.311V | 5.041V | 3.364V | 5.199V | 120.141 | | | | 38.59°C | 114.91V |
| **30%** | **9.260A** | **3.478A** | **3.44A** | **1.35A** | 149.997 | 84.717% | 1349 | 35.8 | 35.07°C | 0.973 |
| | 12.305V | 5.034V | 3.358V | 5.187V | 177.057 | | | | 39.64°C | 114.9V |
| **40%** | **12.914A** | **3.979A** | **3.938A** | **1.546A** | 200.039 | 85.594% | 1606 | 40.6 | 35.57°C | 0.974 |
| | 12.299V | 5.028V | 3.352V | 5.175V | 233.705 | | | | 41.46°C | 114.85V |
| **50%** | **16.228A** | **4.982A** | **4.935A** | **1.744A** | 249.989 | 85.82% | 1722 | 42.6 | 36.17°C | 0.976 |
| | 12.292V | 5.02V | 3.344V | 5.163V | 291.293 | | | | 41.88°C | 114.84V |
| **60%** | **19.550A** | **5.989A** | **5.937A** | **1.942A** | 300.01 | 85.67% | 1837 | 45.6 | 36.63°C | 0.978 |
| | 12.286V | 5.01V | 3.335V | 5.15V | 350.191 | | | | 43.58°C | 114.83V |
| **70%** | **22.875A** | **7A** | **6.943A** | **2.142A** | 350.045 | 85.302% | 1868 | 46.3 | 37.18°C | 0.98 |
| | 12.280V | 5.001V | 3.328V | 5.137V | 410.362 | | | | 47.02°C | 114.82V |
| **80%** | **26.205A** | **8.014A** | **7.952A** | **2.242A** | 399.572 | 84.778% | 1870 | 46.3 | 37.82°C | 0.982 |
| | 12.275V | 4.992V | 3.319V | 5.129V | 471.318 | | | | 49.39°C | 114.81V |
| **90%** | **29.935A** | **8.526A** | **8.449A** | **2.343A** | 449.802 | 84.226% | 1871 | 46.3 | 38.91°C | 0.983 |
| | 12.270V | 4.985V | 3.313V | 5.122V | 534.04 | | | | 51.13°C | 114.78V |
| **100%** | **33.669A** | **9.039A** | **8.979A** | **2.445A** | 500.141 | 83.173% | 1869 | 46.3 | 39.3°C | 0.985 |
| | 12.264V | 4.978V | 3.307V | 5.114V | 601.326 | | | | 53.35°C | 114.77V |
| **110%** | **37.025A** | **10.063A** | **10.094A** | **2.447A** | 549.532 | 82.38% | 1885 | 46.4 | 40.06°C | 0.985 |
| | 12.254V | 4.969V | 3.298V | 5.108V | 667.388 | | | | 53.39°C | 114.75V |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **CL1** | **0.113A** | **15.184A** | **15.051A** | **0.001A** | 126.288 | 77.569% | 1663 | 41.7 | 34.22°C | 0.974 |
| | 12.297V | 4.959V | 3.295V | 5.231V | 162.808 | | | | 40.76°C | 114.9V |
| **CL2** | **0.113A** | **20.197A** | **0.001A** | **0.001A** | 101.395 | 76.207% | 1578 | 40.4 | 34.58°C | 0.98 |
| | 12.307V | 4.951V | 3.363V | 5.242V | 133.052 | | | | 39.37°C | 114.91V |
| **CL3** | **0.113A** | **0A** | **20.063A** | **0.001A** | 67.388 | 70.59% | 1346 | 35.8 | 34.89°C | 0.978 |
| | 12.307V | 5.04V | 3.289V | 5.239V | 95.464 | | | | 38.96°C | 114.94V |
| **CL4** | **40.734A** | **0A** | **0A** | **0A** | 500.059 | 84.23% | 1875 | 46.4 | 39.95°C | 0.985 |
| | 12.276V | 5.041V | 3.36V | 5.231V | 593.68 | | | | 51.68°C | 114.78V |

The results above are not used in the certification process

## **20-80□□□□ 115V**

| □□ | **12V** | **5V** | **3.3V** | **5VSB** | **DC/AC (□ )** | □□ | □□□□ **(RPM)** | □□□□□□□ **(dB[A])** | □□ **(□□ /□□ )** | **PF/AC □□** |
|---|---|---|---|---|---|---|---|---|---|---|
| **20W** | **1.206A** | **0.494A** | **0.488A** | **0.191A** | 20 | 61.822% | 617 | 12.3 | 30.26°C | 0.897 |
| | 12.317V | 5.062V | 3.381V | 5.244V | 32.351 | | | | 30.65°C | 114.94V |
| **40W** | **2.654A** | **0.692A** | **0.683A** | **0.286A** | 39.999 | 74.909% | 664 | 14.1 | 31.05°C | 0.96 |
| | 12.317V | 5.06V | 3.379V | 5.24V | 53.397 | | | | 32.82°C | 114.93V |
| **60W** | **4.102A** | **0.89A** | **0.879A** | **0.382A** | 59.999 | 79.588% | 703 | 15.6 | 32.26°C | 0.951 |
| | 12.316V | 5.057V | 3.378V | 5.235V | 75.387 | | | | 35.38°C | 114.92V |
| **80W** | **5.548A** | **1.088A** | **1.075A** | **0.478A** | 79.96 | 82.413% | 724 | 16.5 | 33.59°C | 0.98 |
| | 12.315V | 5.055V | 3.375V | 5.23V | 97.023 | | | | 37.09°C | 114.92V |

The results above are not used in the certification process

## □□□□ **115V**

| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 10% Load | 16.84mV | 16.93mV | 11.59mV | 21.75mV | Pass |
| 20% Load | 16.84mV | 17.80mV | 11.44mV | 19.41mV | Pass |
| 30% Load | 21.07mV | 18.26mV | 12.31mV | 18.75mV | Pass |
| 40% Load | 20.56mV | 18.57mV | 12.92mV | 18.95mV | Pass |
| 50% Load | 23.15mV | 19.33mV | 13.83mV | 18.59mV | Pass |
| 60% Load | 27.38mV | 20.91mV | 15.05mV | 19.92mV | Pass |


| Test | 12V | 5V | 3.3V | 5VSB | Pass/Fail |
|---|---|---|---|---|---|
| 70% Load | 30.58mV | 21.52mV | 16.28mV | 17.68mV | Pass |
| 80% Load | 37.14mV | 22.90mV | 20.50mV | 18.90mV | Pass |
| 90% Load | 47.73mV | 23.77mV | 21.92mV | 18.24mV | Pass |
| 100% Load | 65.44mV | 25.35mV | 22.63mV | 19.61mV | Pass |
| 110% Load | 71.41mV | 28.61mV | 22.89mV | 22.06mV | Pass |
| Crossload1 | 20.40mV | 27.95mV | 23.70mV | 20.63mV | Pass |
| Crossload2 | 24.02mV | 33.11mV | 20.24mV | 21.45mV | Pass |
| Crossload3 | 25.09mV | 18.72mV | 24.72mV | 15.90mV | Pass |
| Crossload4 | 71.69mV | 21.78mV | 16.84mV | 16.00mV | Pass |

The results above are not used in the certification process

## ABKO COREMAX 500W BRONZE



Top side




| | | | | | |
|---|---|---|---|---|---|
| AC INPUT 交流输入 | 115V~230VAC | | 10A | 50HZ~60HZ | |
| MAX DC Output 最大直流输出 | +3.3V | +5V | +12V | -12V | +5VSB |
| | 20A | 20A | 41.7A | 0.3A | 2.5A |
| MAX COMBINET POWER 最大功率 | 125W | | 500W | 3.6W | 12.5W |
| Power 功率 | 500W | | | | |

2026072201

Power specifications label




Fan



PSU Internals

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□ Cybenetics□□□ Cybenetics □□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□ ETA□□□□□ LAMBDA□□□□□ SAFE DELTA□□□□□□□ PHI□□□□□□□□□