



SilverStone Nightjar 520W

Serial Number R1602AA1C241119

Lab ID 53

Certification ID 2553

Test Result Report ID:


Certificate Issue Date: Feb 26, 2018

115V 230V

Scheme: ETA-EMI PSU



115V 230V



Scheme: LAMBDA PSU

Aristeidis Bitziopoulos, Certification Body General Manager

General Information

Test Equipment

Electronic Loads	Chroma 63601-5 x2 Chroma 63600-2 Chroma 63640-80-80 x10 Chroma 63610-80-20
AC Sources	Chroma 6530, APM SP300VAC4000W-P, GW Instek ASR-3500
Power Analyzers	Rohde & Schwarz HMC8015 & NPA701
Oscilloscopes	Picoscope 4444, Siglent SDS2104X PLUS
Sound Analyzer	Bruel & Kjaer 2270 G4
Microphone	Bruel & Kjaer Type 4955-A
Temperature Logger	Picoscope TC-08
Tachometer	UNI-T UT372
Multimeters	Keysight 34465A
EMI Analyzer	TekBox TBMR-110M-EU
Isolation Transformer	4kVA
UPS	FSP Champ Tower 3kVA, CyberPower OLS3000E 3kVA
Testing Methodology	Cybenetics PSU Test Protocol

DUT Information(Non-accredited measurements)

Product Identification Details	
Brand	SilverStone
Model	Nightjar 520W
OEM/ODM	Sea Sonic Electronics
Serial Number	R1602AA1C241119
Product Specifications	
Manufacturer-Provided Information	
Rated Voltage (Vrms)	100-240
Rated Current (Arms)	7-4
Rated Frequency (Hz)	50-60

Rated Power (W)	520
Operating Temperature (Continuous Full Load) (°C)	
Type	ATX12V
Cable Design	Fully Modular
Warranty	-
Cybenetics Measurements	
Dimensions (W x H x D)	
Weight	
Cooling	Passive
Semi-Passive Operation	
Cybenetics Testing Information	
Lab ID	53
Date of receipt	Feb 12, 2018
Testing Date	Feb 24, 2018
Report Issued Date	Feb 26, 2018
Engineer Name	-
Authorized By the Laboratory Technical Manager	Aristeidis Bitziopoulos
Signature	

Cables and Connectors(Non-accredited measurements)

Modular Cables			
Description	Cable Count	Connector Count (Total)	Gauge
ATX connector 20+4 pin (600mm)	1	1	18-22AWG
4+4 pin EPS12V (650mm)	1	1	18AWG
6+2 pin PCIe (550mm+100mm)	2	4	18AWG
SATA (400mm+110mm+110mm+110mm)	1	4	18AWG
SATA (300mm+120mm)	1	2	18AWG
4 pin Molex (400mm+120mm+120mm)	1	3	18AWG
4 pin Molex (300mm+120mm)	1	2	18AWG
FDD Adapter (+105mm)	1	1	22AWG

Power Specifications

Rail		3.3V	5V	12V	5VSB	-12V
Max. Power	Amps	20	20	43	2.5	0.5
	Watts	100		516	12.5	6
Total Max. Power (W)		520				

Test Results

Temperature & Compliance Info

Temperature Range (°C /°F)	28-32 / 82.4-89.6
ErP Lot 3/6 Ready	✓
(EU) No 617/2013 Compliance	✓

Performance Summary 115V


Accredited	
Average Efficiency (>1450 load combinations)	90.772%
Average Noise Output (>1450 Load Combinations)	6.00dBA
Average PF (>1450 Load Combinations)	0.987
Efficiency With 10W (≤500W) or 2% (>500W) Load	-
Standby Power Consumption	0.1163W
Non-Accredited	
12V Ripple (Full Load)	28.74mV
5V Ripple (Full Load)	16.49mV
3.3V Ripple (Full Load)	11.58mV
5VSB Ripple (Full Load)	7.40mV
12V Load Regulation	1.07%
5V Load Regulation	0.42%
3.3V Load Regulation	0.80%
5VSB Load Regulation	2.53%
Inrush Current	19.030A

Hold-Up Time & PWR_OK Signal

Hold-Up Time (ms)	19.8
AC Loss to PWR_OK Hold Up Time (ms)	16.6
PWR_OK Inactive to DC Loss Delay (ms)	3.2




Graphs 115V



Efficiency Graph

115V



INFO


This graph depicts the PSU's efficiency throughout its entire operational range. For the generation of the efficiency and noise graphs we set our loaders to auto mode through our custom-made software before trying thousands of possible load combinations.

Indicative Performance

Efficiency under high ambient temperature

Efficiency: SilverStone NJ520

Ambient: 34°C - 41°C (93.2°F - 105.8°F)




INFO

The PSU's efficiency under high ambient temperatures with 115V and 230V input. For this graph the results of the 10-110% load regulation table are used.

5VSB Efficiency

5VSB Efficiency: SilverStone NJ520

Ambient: 34°C - 36°C (93.2°F - 96.8°F)



INFO

This graph depicts the efficiency levels of the 5VSB rail with 115V and 230V input.

5VSB Efficiency (ERP LOT 3/6 & CEC) 115V

Test #	5VSB	DC/AC (Watts)	Efficiency	PF/AC Volts
1	0.042A	0.214	69.256%	0.049
	5.110V	0.309		115.11V

2	0.087A	0.446	74.582%	0.093
	5.109V	0.598		115.11V
3	0.532A	2.712	78.929%	0.330
	5.098V	3.436		115.11V
4	2.502A	12.638	80.272%	0.493
	5.052V	15.744		115.11V

Supplementary Tests (For Reference)

Typical Load Tests 115V

Load Regulation & Efficiency Tests Nidus 500 PG-5001-BR -115V										
Test #	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	Temps (In/Out)	PF/AC Volts
1	2.497A	1.985A	1.965A	0.981A	51.771	85.477%	0000	<6.0	41.62°C	0.946
	12.100V	5.030V	3.355V	5.076V	60.567				36.11°C	115.13V
2	6.030A	2.981A	2.953A	1.181A	103.754	90.035%	0000	<6.0	42.51°C	0.976
	12.087V	5.028V	3.352V	5.065V	115.238				36.68°C	115.12V
3	9.921A	3.489A	3.462A	1.385A	155.909	91.408%	0000	<6.0	43.39°C	0.986
	12.074V	5.025V	3.348V	5.053V	170.563				36.83°C	115.12V
4	13.811A	3.986A	3.944A	1.585A	207.779	91.979%	0000	<6.0	44.10°C	0.995
	12.061V	5.023V	3.345V	5.041V	225.898				36.98°C	115.11V
5	17.367A	4.977A	4.932A	1.788A	259.690	91.863%	0000	<6.0	45.24°C	0.990
	12.047V	5.021V	3.343V	5.029V	282.693				37.71°C	115.11V
6	20.936A	5.975A	5.927A	1.992A	311.698	91.619%	0000	<6.0	48.77°C	0.990
	12.033V	5.020V	3.339V	5.015V	340.212				38.99°C	115.11V
7	24.513A	6.980A	6.921A	2.198A	363.729	91.288%	0000	<6.0	49.35°C	0.992
	12.019V	5.018V	3.336V	5.001V	398.443				39.30°C	115.11V
8	28.095A	7.976A	7.918A	2.404A	415.679	90.861%	0000	<6.0	50.36°C	0.994
	12.005V	5.016V	3.334V	4.988V	457.487				39.72°C	115.11V
9	32.115A	8.475A	8.436A	2.407A	467.680	90.515%	0000	<6.0	51.07°C	0.994
	11.991V	5.014V	3.332V	4.980V	516.686				39.89°C	115.11V

10	36.103A	8.983A	8.920A	2.513A	519.543	90.064%	0000	<6.0	52.60°C	0.995
	11.975V	5.012V	3.329V	4.971V	576.859				40.09°C	115.16V
11	40.495A	8.987A	8.924A	2.516A	571.526	89.639%	0000	<6.0	55.13°C	0.995
	11.960V	5.010V	3.327V	4.964V	637.586				40.87°C	115.11V
CL1	0.099A	12.012A	12.005A	0.005A	101.667	86.347%	0000	<6.0	53.96°C	0.978
	12.074V	5.025V	3.339V	5.073V	117.743				40.50°C	115.12V
CL2	42.962A	1.003A	1.003A	1.002A	527.935	90.857%	0000	<6.0	54.67°C	0.995
	11.976V	5.019V	3.346V	5.021V	581.061				41.26°C	115.11V

The results above are not used in the certification process

Light Load Tests 115V

Efficiency at Low Loads Nidus 500 PG-5001-BR -115V										
Test #	12V	5V	3.3V	5VSB	DC/AC (Watts)	Efficiency	Fan Speed (RPM)	PSU Noise (dB[A])	PF/AC Volts	
1	1.206A	0.492A	0.474A	0.196A	19.670	73.259%	0000	<6.0	0.851	
	12.109V	5.031V	3.358V	5.100V	26.850				115.12V	
2	2.436A	0.991A	0.980A	0.392A	39.759	83.225%	0000	<6.0	0.923	
	12.104V	5.033V	3.356V	5.093V	47.773				115.12V	
3	3.671A	1.488A	1.488A	0.586A	59.874	87.011%	0000	<6.0	0.949	
	12.099V	5.031V	3.355V	5.085V	68.812				115.12V	
4	4.893A	1.986A	1.965A	0.786A	79.745	89.094%	0000	<6.0	0.969	
	12.094V	5.029V	3.354V	5.078V	89.507				115.12V	

The results above are not used in the certification process

Ripple Measurements 115V

Test	12V	5V	3.3V	5VSB	Pass/Fail
10% Load	10.6 mV	10.6 mV	6.1 mV	4.8 mV	Pass
20% Load	14.3 mV	11.8 mV	6.2 mV	5.1 mV	Pass
30% Load	19.0 mV	11.4 mV	6.8 mV	5.0 mV	Pass
40% Load	20.5 mV	11.7 mV	7.0 mV	5.4 mV	Pass

Test	12V	5V	3.3V	5VSB	Pass/Fail
50% Load	22.6 mV	12.0 mV	8.8 mV	5.5 mV	Pass
60% Load	23.4 mV	12.8 mV	8.5 mV	6.0 mV	Pass
70% Load	25.1 mV	13.0 mV	9.4 mV	6.3 mV	Pass
80% Load	25.9 mV	13.5 mV	9.5 mV	6.9 mV	Pass
90% Load	27.8 mV	14.5 mV	10.2 mV	7.1 mV	Pass
100% Load	28.7 mV	16.5 mV	11.6 mV	7.4 mV	Pass
110% Load	30.2 mV	16.7 mV	12.9 mV	7.7 mV	Pass
Crossload 1	15.1 mV	13.5 mV	8.3 mV	19.5 mV	Pass
Crossload 2	27.8 mV	14.6 mV	11.4 mV	7.1 mV	Pass

The results above are not used in the certification process

SilverStone Nightjar 520W



Top side



Power specifications label

Cybenetics [REDACTED] ETA[REDACTED] LAMBDA[REDACTED] SAFE[REDACTED] DELTA[REDACTED] PHI[REDACTED]